

Submit 3 Copies To Appropriate District Office
District I
1625 N French Dr, Hobbs, NM 88240
District II
1301 W Grand Ave, Artesia, NM 88210
District III
1000 Rio Brazos Rd, Aztec, NM 87410
District IV
1220 S St Francis Dr, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

MAR 27 2009

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)		WELL API NO. 30-005-60907
1. Type of Well: Oil Well ☐ Gas Well ☒ Other		5. Indicate Type of Lease STATE ☐ FEE ☒
2. Name of Operator WALTER EXPLORATION INC		6. State Oil & Gas Lease No.
3. Address of Operator 6116 N CENTRAL EXP #313, DALLAS TX 75206		7. Lease Name or Unit Agreement Name J G O'BRIEN (11602)
4. Well Location Unit Letter F : 1980 feet from the N line and 1830 feet from the W line Section 31 Township 07 S Range 29 E NMPM County CHAVES		8. Well Number 003
11. Elevation (Show whether DR, RKB, RT, GR, etc.) GL 4009.4		9. OGRID Number 24581
		10. Pool name or Wildcat SWD;FUSSELMAN (96104)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

See attached before and after wellbore schematic.

Notify NMOCD office Artesia @ 575-748-1283 24 hours prior to commence plugging operations.

- 1) Wellbore previously plugged back to 3068'.
- 2) Drill out CIBP @ 2190.
- 3) Tag top old plug @ 3068'.
- 4) Load hole w/ 9.5 brine mud.
- 5) Set Shoe plug- cement plug 50' in/50' out of 9 5/8" casing shoe @ 2741'. TAG
- * 6) Set cement plug 50' in/50' out of 9 5/8" stub @ 2430'. TAG
- 7) Set Shoe plug- cement plug 50' in/50' out of 13 3/8" casing shoe @ 386'. TAG.
- 8) 60' cement plug from 60' to surface.
- 9) Install dry hole marker.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Eddie W Seay TITLE AGENT DATE 03/26/2009

Type or print name Eddie W Seay E-mail address: SEAY04@LEACO.NET PHONE: 575-392-2236
For State Use Only

APPROVED BY: [Signature] TITLE Captain DATE 3/30/09
Conditions of Approval (if any):

* - YATES required Plug. 887' - 787'

Approval Granted providing work
is complete by 6/30/09

WELLBORE SCHEMATIC After P&A

COMPLETION SCHEMATIC		APINUM: 30-005-60907	
FORM	DEPTH	OPERATOR: WALTER EXPLORATION INC	
13 3/8 @ 386' TOC 0' 837 1443 1898 3141 4545 5288 5952 6428 6746 6770 5 1/2 @ 6872' TOC @ 1928' PLUG 0-60 PLUG 50'in/50'out Shoe @ 386' PLUG 50'in/50'out STUB @ 2430' PLUG 50'in/50'out Shoe @ 2741 TOC Stage 2 @ 2592 CBL TOC on retainer @ 3068 CMNT RETAINER @ 3358 sqz w/300 sxs DV Tool @ 3376' CMNT RETAINER @ 3578 sqz w/280 sxs TOP OF FISH @ 3680' TOC Stage 1 @ 5330 Calc Baker Mdl R pkr @ 5726 PERFS 6762-6784 CMNT RETAINER @ 6790 sqz w/43 sxs PERFS 6794-6797 CMNT RETAINER @ 6802 PERFS 6804-6810 TD 6872			

Yates

Queen

San Andres

Glorieta

Tubb

Abo

Wolfcamp

PENN

Miss Lm

Fusselman

PREPARED BY.

UPDATED

03/24/09

WELLBORE SCHEMATIC AND HISTORY

COMPLETION SCHEMATIC		APINUM: 30-005-60907			
FORM	DEPTH	OPERATOR: WALTER EXPLORATION INC			
13 3/8 @ 386' TOC 0' 837 1443 1898 3141 4545 5288 5952 6428 6746 6770 5 1/2 @ 6872' TOC @ 1928'			LEASENAME: J G O'BRIEN		WELL NO 3
	ELKINS;FUSSELMAN, SOUTH		1980 FNL		1830 FWL
	TD 6872		PBD 6824		KB
	GL 4009		DF		
	POOL		PERFS 6804-6810		
	POOL		PERFS 6794-6797		
	POOL		Open Hole		
	POOL		PERFS		
	POOL		PERFS		
CASING RECORD					
	SIZE	DEPTH	CMT	HOLE SIZE	TOC
SURF.	13 3/8	386	520 sxs	17 1/2	0' CIRC
INT1	9 5/8	2741	1750 sxs	12 1/4	0' CIRC
PROD	5 1/2	6872	715 sxs **	8 3/4	2592
TOC Stage 2 @ 2592 CBL					
** DV Tool @ 3376' Stage 1 315 sxs CL H,					
Stage 2 350 sxs 50:50 POZ CL C & 50 sxs CL H					
TOC on retainer @ 3068					
CMNT RETAINER @ 3358 sqz w/300 sxs					
DV Tool @ 3376'					
CMNT RETAINER @ 3578 sqz w/280 sxs					
TOP OF FISH @ 3680'					
TOC Stage 1 @ 5330 Calc					
Baker Mdl R pkr @ 5726					
PERFS 6762-6784					
CMNT RETAINER @ 6790 sqz w/43 sxs					
PERFS 6794-6797					
CMNT RETAINER @ 6802					
PERFS 6804-6810					
TD 6872					

PREPARED BY.

UPDATED

03/24/09