

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD-ARTESIA

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.

APR 28 2009

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

OXY USA Inc.

16696

3a. Address

P.O. Box 50250, Midland, TX 79710-0250

3b. Phone No. (include area code)

432-685-5717

4. Location of Well (Footage, Sec, T., R., M., or Survey Description)

SL - 1650 FSL 400 FEL NESE(I) Sec 33 T23S R29E

BHL - 1650 FSL 400 FWL NWSW(L) Sec 33 T23S R29E

5. Lease Serial No.

NMNM19848

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.

Cypress 33 #3H

Federal

9. API Well No.

30-015-36987

10. Field and Pool, or Exploratory Area

Cedar Canyon Bone Spring

11. County or Parish, State

Eddy NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Acidize

☐ Alter Casing

☐ Casing Repair

☐ Change Plans

☐ Convert to Injection

☐ Deepen

☐ Fracture Treat

☐ New Construction

☐ Plug and Abandon

☐ Plug Back

☐ Production (Start/Resume)

☐ Reclamation

☐ Recomplete

☐ Temporarily Abandon

☐ Water Disposal

☐ Water Shut-Off

☐ Well Integrity

☒ Other Spud. Set

Csq and Cmt

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

See Attached

ACCEPTED FOR RECORD

APR 25 2009

BUREAU OF LAND MANAGEMENT
CARLSBAD FIELD OFFICE

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

David Stewart

Title

Sr. Regulatory Analyst

Date

4/22/09

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

CYPRESS 33 FEDERAL #3H

SPUD SURFACE HOLE AT 08:00 HRS, 04/15/2009.

DRILLED 17-1/2" SURFACE HOLE TO 550'

RIH W/ 13-3/8" 48# H40 CASING AND SET @ 550' W/ 6 CENTRALIZERS

CEMENT W/ 450sx PP w/ 4% Bentonite + 2% CaCl₂ + .125#/sx Polyflake @ 13.5 PPG, 1.75 YIELD FOLLOWED BY 200sx PP w/ 2% CaCl₂ @ 14.8 PPG, 1.35 YIELD. DROP PLUG. DISPLACE BUMPED PLUG @ 23:45 HRS 4/15/09.

CIRCULATE 79 BBL (254sx) CEMENT TO SURFACE. WOC

NOTE: BOB HOSKINSON WITH BLM WITNESSED CEMENT JOB.

NIPPLE UP BOP EQUIPMENT AND TEST

4/17/08 0200 HRS, RIH W/ 12-1/4" BHA AND TAG CEMENT @ 460', CIRC HOLE TEST CSG TO 1000#, HELD OK.

DRILL 12-1/4" INTERMEDIATE HOLE TO 3063' 4/18/08.

RIH W/ 9-5/8" 47# L80 CASING AND SET @ 3053' W/ 24 CENTRALIZERS

CEMENT W/ 800sx PP w/ 5#/sx Gilsonite + .125#/sx Polyflake + 5% salt + 2.5#/bbl WG-19 @ 12.4 PPG, YIELD 2.12, followed by 200sx PP w/ 2% CaCl₂ @ 14.8 PPG, YIELD 1.34. DROP PLUG. DISPLACE BUMPED PLUG @ 21:30 HRS 4/18/09. CIRCULATE 136 BBL (360sx) CEMENT TO SURFACE. WOC

NIPPLE UP BOP EQUIPMENT AND TEST

4/19/08 1800 HRS RIH W/ 8-1/2" BHA AND TAG CEMENT @ 2967', CIRC HOLE TEST CSG TO 3675#, HELD OK.

DRILL OUT CEMENT AND TEST

DRILL 8-1/2" PRODUCTION HOLE.