

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
May 27, 2004

SEP - 2 2009

WELL API NO. 30-015-22491
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: Empire Abo Unit "K"
8. Well Number 231
9. OGRID Number 00778
10. Pool name or Wildcat Empire Abo

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	2. Name of Operator BP America Production Company
3. Address of Operator P.O. Box 1089 Eunice NM 88231	4. Well Location Unit Letter J : 1700 feet from the S line and 2350 feet from the E line Section 6 Township 18S Range 28E NMPM County Eddy
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3649' GR	
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/> Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____ Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____	

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/20/09: RU PU. LOAD & TEST CSG & TBG. 500 PSI (OK). BULLHEAD 50 BBLS FRESH WATER DN TBG. WELL ON VAC. N/D WH N/U BOP FUNCTION TEST (OK). TIH TO 6150' WITH PKR. R/U GERONIMO LINE POOH HIT TIGHT SPOT @ 3980' WORKED THROUGHT, DVT @ 3987' PKR. DRAGGING FROM 3980'.

8/21/09: P/U 4 3/4" BIT & 5.5" CSG. SCRAPER RIH HIT TIGHT SPOT @ 3989' P/U RUN THRU 4 TIMES SAME TIGHT P/U ABOVE TIGHT CALLED FOR STRING MILL DV TOOL @ 3987'.

8/24/09: RIH W/ BIT & STRING MILL TIGHT @ 3989' MILL THRU. OK P/U / RUN THRU. (OK) CONT. RIH WITH BIT & STRING MILL TO 6151'. P/U 5.5 CIBP TIH TO 5K'.

Continued on page 2.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE Barry C. Price TITLE Area Operations Team Lead DATE 8/31/09

Type or print name Barry C. Price

E-mail address barry.price@bp.com Telephone No. 575-394-1648

For State Use Only

APPROVED BY [Signature] TITLE Approved for plugging of well bore only DATE 9/2/09

Conditions of Approval, if any:

Approved for plugging of well bore only
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms. www.emnrd.state.nm.us/oed

Form C-103
Empire Abo Unit K-231
30-015-22491
Continued from Page 1

8/25/09: RIH WITH 5.5" CIBP SET @ 6150'. LOAD & TEST CIBP & CSG TO 500 PSI (OK). M&P 35 SKS. CLASS C CMT. 15.PPG F- 6150'- T-5800' DISPLACE WITH 22 BBLS. L/D 12 JTS. CIRC. WELL WITH 9.5 PPG PLUG MUD. 135 BBLS. L/D TO 4105' M&P 70 SKS. 14.9 PPG CLASS (C) CMT. DISPLACED WITH 13 BBLS. W.O.C.

8/26/09: RIH TAG CMT. 3422' GLORIETA DV TOOL PLUG F- 4105' T-3422'. L/D TBG. TO 1350'. M&P 140 SKS. CLASS (C) 15.PPG CMT. F- 1350' T-SURFACE POOH L/D TBG. TOP CMT. OFF. N/D BOP. R/D PULLING UNIT.

8/27/09: DIG OUT AROUND WELLHEAD. CUT OFF ALL ANCHORS AND WELL HEAD, WELD IN PLATE, 1" NIPPLE & VALVE, DRY HOLE MARKER, BACKFILL AND LEVEL LOCATION.