

Submit 3 Copies To Appropriate District Office
District I
625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
June 19, 2008

SEP 18 2009

RM

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-005-61341
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other P&A		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation		6. State Oil & Gas Lease No.
3. Address of Operator 105 South Fourth Street, Artesia, NM 88210		7. Lease Name or Unit Agreement Name Sacra SA
4. Well Location Unit Letter M : 660 feet from the South line and 660 feet from the West line Section 35 Township 6S Range 25E NMPM Chaves County		8. Well Number 3
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3714'GR		9. OGRID Number 025575
		10. Pool name or Wildcat Pecos Slope; Abo

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

9/11/09 - MIRU. Pull off old wellhead. POH with tubing. Set an RBP at 240'. Load casing, spear 4-1/2" casing, pulled 90k could not get slips out, remove 8-5/8" cap off wellhead. Dress off broke casing. Weld on bell nipple. NU BOP. Released RBP.
9/14/09 - Spotted 25 sx Class "C" cement plug with 1% CaCl2 at 3550'. WOC. Tagged plug at 3396'. Perforated at 1805'. Spotted 35 sx Class "C" cement plug with 1% CaCl2 from 1805'-1705'. WOC. Tagged plug at 1685'. Perforated at 1527'. Spotted 30 sx Class "C" cement plug from 1527'-1427'. WOC. Tagged plug at 1400'. Perforated at 907'. Spotted 30 sx Class "C" cement plug from 907'-807'. WOC. Tagged plug at 765'. Perforated at 60'. Mixed 25 sx Class "C" cement plug and circulated cement around 5-1/2" and 8-5/8" annulus. Circulated 10 sx to pit.
9/15/09 - Installed dry hole marker and cleaned location as per regulations. **WELL IS PLUGGED AND ABANDONED.**

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE September 17, 2009

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY [Signature] TITLE
Conditions of Approval (if any):

Approved for plugging of well bore only.
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms: www.oand.state.nm.us/oand

DATE 9/21/09