

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
June 19, 2008

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-005-64111
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LO-0729-0002
7. Lease Name or Unit Agreement Name Round Tank State
8. Well Number 1
9. OGRID Number 1092
10. Pool name or Wildcat Round Tank Queen (Assoc.)
11. Elevation (Show whether DR, RKB, RT, GR, etc.)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Armstrong Energy Corporation

575-625-2222

3. Address of Operator

P.O. Box 1973, Roswell, NM 88202

4. Well Location

Unit Letter C : 660' feet from the North line and 1705' feet from the West line  
Section 30 Township 15S Range 29E NMPM County Chaves

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

T.D. @ 1493', Bit @ 1483', Top of Fish @ 1418', Fish- Bit, stabilizer, 28' core barrel, stabilizer, 28' core barrel, shim joint, stabilizer, safety joint box, total 65'

Loss zone at 130'

Surface Casing: 8 5/8"-24 #/ft. J-55, ST&C at 82'

Plugging Procedure: Spot 420 sx plug of Halcem-"C", mixed at 14.8 ppg from 1418'-130'  
Wait 4 hours and tag plug, fill from top of plug to 100' with pea gravel.  
Spot 50 sx plug of Halcem-"C", mixed at 14.8 ppg, from 100' to surface  
Remove wellhead and install dry hole marker

Verbal Approval received from Phil Hawkins 9-24-2009

Spud Date: September 15, 2009

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bruce A. Stubbs TITLE Vice President DATE 9-24-2009

Type or print name Bruce A. Stubbs E-mail address: bastubbs@armstrongenergycorp.com PHONE: 575-625-2222

For State Use Only

APPROVED BY: Phil Hawkins TITLE  DATE 9/24/09

Conditions of Approval (if any):