

SEP 22 2009

Form 3160-5
(August 2007)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB No 1004-0137
Expires July 31, 2010**SUNDRY NOTICES AND REPORTS ON WELLS**
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.***SUBMIT IN TRIPLICATE - Other instructions on page 2**

1 Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Legacy Reserves Operating LP

3a. Address

PO Box 10848, Midland, TX 79702

3b. Phone No (include area code)

432-689-5200

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 1650' FEL**Sec. 10, T-18-S, R-31-E**

5. Lease Serial No

NMLC029388C

6 If Indian, Allottee or Tribe Name

7 If Unit or CA/Agreement, Name and/or No

NMNM85311X

8 Well Name and No

Tamano (BSSC) Unit #303

9. API Well No

30-015-26513

10 Field and Pool, or Exploratory Area

Tamano; Bone Springs

11 County or Parish, State

Eddy County, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

8/18/09 MIRU rig and cementing equipment. Dug out cellar. Unseat pump. Rods parted. NU BOP. tubing parted also. RIH w/ work string and tagged fish @ 480'. POH. Shut well in.

8/19/09 RIH w/ fishing tool Caught tbg. fish. POH w/ 232 jts of tbg. No rods. RIH w/ tbg. and Tagged rods @ 567'. POH. SDFN.

8/20/09 RIH w/ overshot. Tagged fish @ 560'. No catch. POH. RIH w/ overshot. Caught fish. POH w/ 132 FG rods. & 124 steel rods. RIH with wireline and tagged fish @ 7856'. SDFN.

8/21/09 RIH w/ overshot. Caught fish. POH w/ 30 jts. tbg. fish. TIH with CIBP on tubing to 7994'. would not set. POH. piece of FG rod in BP/ SDFN.

8/24/09 RIH w/ CIBP to 8000'. Set plug. Circulated hole w/ mud laden fluid. Spot 25 sx class C cement on top of plug. Pulled out of cement. WOC

8/25/09 Tagged plug @ 7880'. POH to 7570'. Spot 25 sx class C cement. (7570-7400). POH to 5810. Spot 25 sx class C cement. (5810-5650). POH to 4382'. Spot 25 sx class C cement. (4382-4242). POH to 3380'. Spot 25 sx class C cement. (3380-3250). POH w/ tbg. RIH w/ wire line and perf. csg. @ 2510. RIH w/ 5 1/2 packer and set @ 2100'. Pressured up on perfs. Held. RIH w/ tbg. to 2565'. Spot 25 sx class C cement. WOC. 8/26/09 Tagged plug @ 2330'. Per BLM, spot 25 class C cement @ 2330'. (2330-2128). POH w/ tbg. Perf csg. @ 820'. Pressured up to 1500 psi. RIH w/ tbg to 870'. spot 25 sx class C cement WOC. Tagged plug @ 515'. POH Perf'd csg. @ 60'. Sqz'd 40 sx class C cement and circulated cement to surface. cut off well head. Weld on Dry Hole Marker. cut off dead men and clean location. Rigged down moved off.

Accepted as to plugging of the well bore.
Liability under bond is retained until
Surface restoration is completed.

14 I hereby certify that the foregoing is true and correct.)

Name (Printed/Typed)

Berry Johnson

Title Production-Superintendent

Signature

Date

09/03/2009

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon

Title

Office

SEP 19 2009

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make any statement or representation as to any matter within its jurisdiction

(Instructions on page 2)

BUREAU OF LAND MANAGEMENT
CARLSBAD FIELD OFFICEENTERED
9-30-09