



Form 3160-5
(February 2005)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED
OMB No. 1004-0137
Expires: March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No. **NM-102917**
6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on page 2.

1. Type of Well ☒ Oil Well ☐ Gas Well ☐ Other		7. If Unit of CA/Agreement, Name and/or No.
2. Name of Operator RKI Exploration & Production		8. Well Name and No. RDX "21" #14
3a. Address 3817 NW Expressway, Suite 950 Oklahoma City, OK. 73112	3b. Phone No. (include area code) 405-949-2221	9. API Well No. 30-015-37112
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 330' FNL & 990' FEL Sec. 21 T26S - R30E		10. Field and Pool or Exploratory Area Brushy Draw - Delaware
		11. Country or Parish, State Eddy Co. New Mexico

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
☒ Notice of Intent	☐ Acidize	☐ Deepen	☐ Production (Start/Resume)	☐ Water Shut-Off
☒ Subsequent Report	☐ Alter Casing	☐ Fracture Treat	☐ Reclamation	☐ Well Integrity
☐ Final Abandonment Notice	☐ Casing Repair	☐ New Construction	☐ Recomplete	☐ Other
	☐ Change Plans	☐ Plug and Abandon	☐ Temporarily Abandon	
	☐ Convert to Injection	☐ Plug Back	☐ Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Remedial Cementing Procedure for the RDX 21-14:

PROCEDURE:

**SEE ATTACHED FOR
CONDITIONS OF APPROVAL**

1. MIRU workover rig. Pull rods and pump. TOH with tubing.
2. RIH with RBP and set at approximately 4000'. Load casing with produced water.
3. Tie onto backside (8 5/8" x 5 1/2" annulus) and establish Injection rate. DO NOT EXCEED 2000 PSI.
4. Pump 300 sx 35:65 Poz "C" with 5% D44, 6% D20, .2% D46, .2% D13, 2 pps D42, .125 pps D130 mixed at 12.6 ppg (2.08 cf/sk).

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) Bill Aubrey		Title Operations
Signature		Date 10-28-09
THIS SPACE FOR FEDERAL OR STATE OFFICE USE		
Approved by		APPROVED NOV 25 2009 /s/ Chris Walls BUREAU OF LAND MANAGEMENT
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.		

(Instructions on page 2)

**RDX "21" #14
30-015-37112
RKI Exploration & Production
November 3, 2009
Conditions of Approval**

- 1. If injection rate cannot be established contact the appropriate BLM office with an alternative plan.**
- 2. Surface disturbance beyond the existing pad must have prior approval.**
- 3. A minimum of a 2M BOP is required and must be tested prior to starting work.**
- 4. If cement is pumped a cement bond log will be required to verify the cement overlapped the intermediate casing shoe.**
- 5. Subsequent sundry required.**

CRW 112509