

Submit 1 Copy To Appropriate District
Office
District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-005-00158

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other P&A

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 South Fourth Street, Artesia, NM 88210

7. Lease Name or Unit Agreement Name
Ruby Jo ATY

8. Well Number

1

9. OGRID Number

025575

10. Pool name or Wildcat

Wildcat; San Andres

4. Well Location

Unit Letter O : 660 feet from the South line and 1980 feet from the East line
Section 14 Township 8S Range 26E NMPM Chaves County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3888'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/1/09 - NU BOP. Set a 5-1/2" CIBP at 5684' with 35' cement on top. Perforated San Andres 2103'-2120' (102). Acidized with 1700g 15% IC HCL acid. Recompletion was unsuccessful, plan to plug and abandon the well.

12/8/09 - Released packer. Spotted Abo plug up to 4324' with 25 sx = 5.8 bbls = 247'.

12/9/09 - Spotted Glorieta and San Andres plug up to 1758' with 50 sx = 11.7 bbls = 493'. WOC. Tagged plug at 1758'. Perforated 4 squeeze perfs at 1213'. Spotted intermediate shoe plug up to 925' with 30 sx = 7 bbls = 296'. WOC. Tagged plug at 925'. Perforated 4 squeeze holes at 60'. Pumped surface plug with 25 sx = 5.8 bbls, down 5-1/2" casing around 8-5/8" casing to surface.

12/11/09 - Cut off wellhead. Installed dry hole marker as per OCD. **WELL IS PLUGGED AND ABANDONED.**

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE December 14, 2009

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY [Signature] TITLE

Conditions of Approval (if any):

Approved for plugging of well bore only.

Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging)

which may be found at OCD Web Page under DATE 12/17/09

Forms, www.emnrd.state.nm.us/oed.