

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

RN

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

| | | |
|--|--|---|
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) | | WELL API NO. 30-015-37451 |
| 1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> | | 5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 2. Name of Operator Mewbourne Oil Company | | 6. State Oil & Gas Lease No. K-4168 |
| 3. Address of Operator PO Box 5270, Hobbs, NM 88241 | | 7. Lease Name or Unit Agreement Name Parkway 26 State Com |
| 4. Well Location Unit Letter <u>D</u> : <u>660'</u> feet from the <u>North</u> line and <u>330'</u> feet from the <u>West</u> line Section <u>26</u> Township <u>19S</u> Range <u>29E</u> NMPM Eddy County | | 8. Well Number 2H |
| 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3341' GL | | 9. OGRID Number 14744 |
| | | 10. Pool name or Wildcat Turkey Track Bone Spring 60660 |

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

01/02/10...MI & spud 17 1/2" hole. TD'd hole @ 350'. Ran 350' 13 3/8" 48 H40 ST&C csg. Cemented with 400 sks Class "C" with 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Circ 96 sks to pit. WOC 18 hrs. At 8:15 am 01/04/10 tested Csg & annular to 1250# for 30 minutes, held OK. Drilled out with 12 1/4" bit.

01/11/10..TD'ed 12 1/4" hole @ 3303'. Ran 3303' 9 5/8" 36/40# J55 LT&C Csg. Cemented with 700 sks BJ Lite "C" (50:50:10) with additives. Mixed @ 11.7 /g w/ 2.52 yd. Tail with 200 sks Class "C". Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 8:45 am 01/10/10. Circ 165 sks to pit. WOC 18 hrs. At 2:45 am 01/11/10 tested BOPE and casing to 1500# for 30 minutes, held Ok. Drilled out with 8 3/4" bit.

Spud Date: 01/02/2010

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jacqui Lathan TITLE Hobbs Regulatory DATE 01/13/10

Type or print name _____ E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: Jacqui Lathan TITLE Geologist DATE 1/19/2010

Conditions of Approval (if any):