

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTN.M. Oil Cons. DIV-Dist. 2  
1301 W. Grand Avenue  
Artesia, NM 88210FORM APPROVED  
OMB NO 1004-0135  
Expires January 31, 2004

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1 Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other		5 Lease Serial No <b>NM 036718</b>
2 Name of Operator <b>CIMAREX ENERGY CO. OF COLORADO</b> ATTN: <b>ZENO FARRIS</b>		6 If Indian, Allottee or Tribe Name <b>2010</b>
3a Address <b>600 N. MARIENFELD, SUITE 600, MIDLAND, TEXAS 79701</b>	3b Phone No (include area code) <b>(432) 571-7800</b>	7 If Unit or CA/Agreement, Name and/or No <b>NM - 061P3587C431</b>
4 Location of Well (Footage, Sec., T., R., M., or Survey Description) <b>UNIT LETTER J</b> <b>1,980' FSL &amp; 1,980' FEL</b> <b>SEC. 30, T-15S, R-28E</b>		8 Well Name and No <b>FORAN 30 FEDERAL #001</b> <b>COM.</b>
		9 API Well No <b>30-005-62320</b>
		10 Field and Pool, or Exploratory Area <b>DIAMOND MOUND; MORROW (GAS)</b>
		11 County or Parish, State <b>CHAVES COUNTY N.M.</b>

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

## TYPE OF ACTION

- |   |  |  |   |
|---|--|--|---|
| <input type="checkbox"/> Acidize              | <input type="checkbox"/> Deepen                      | <input type="checkbox"/> Production (Start/Resume) | <input type="checkbox"/> Water Shut-Off |
| <input type="checkbox"/> Alter Casing         | <input type="checkbox"/> Fracture Treat              | <input type="checkbox"/> Reclamation               | <input type="checkbox"/> Well Integrity |
| <input type="checkbox"/> Casing Repair        | <input type="checkbox"/> New Construction            | <input type="checkbox"/> Recomplete                | <input type="checkbox"/> Other _____    |
| <input type="checkbox"/> Change Plans         | <input checked="" type="checkbox"/> Plug and Abandon | <input type="checkbox"/> Temporarily Abandon       |   |
| <input type="checkbox"/> Convert to Injection | <input type="checkbox"/> Plug Back                   | <input type="checkbox"/> Water Disposal            |   |

Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

- 1) SET 4-1/2" CIBP @ 8,900'; MIX X PUMP A 25 SX. CMT. PLUG @ 8,900'-8,650'; CIRC. WELL W/ PXA MUD.  
2) MIX X PUMP A 25 SX. CMT. PLUG @ 7,500'-7,250' (T/CISCO).  
3) MIX X PUMP A 35 SX. CMT. PLUG @ 5,600'-5,250' (T/ABO X 4-1/2" CSG. LEAK); WOC X TAG TOP OF CMT. PULG.  
4) MIX X PUMP A 40 SX. CMT. PLUG @ 3,050'-2,800' (T/GLORIETA) - Perforate 4 1/2" Casing @ 3050' - Tag  
5) MIX X PUMP A 80 SX. CMT. PLUG @ 2,005'-1,605' (T/S.A. X 9-5/8" CSG. SHOE); WOC X TAG TOP OF CMT. PLUG.  
6) PERF. 4-1/2" X ATTEMPT TO SQZ. A 50 SX. CMT. PLUG @ 440'-340' (13-3/8" CSG. SHOE); WOC X TAG CMT. PLUG.  
7) PERF. 4-1/2" CSG. X CIRC. TO SURF. A 25 SX. CMT. PLUG @ 63'-3'.  
8) DIG OUT X CUT OFF WELLHEAD 3' B.G.L.; WELD 1/2" STEEL PLATE TO CASINGS X INSTALL DRY HOLE MARKER.

Perforate 4 1/2" Casing @ 2005' - Tag

SEE ATTACHED FOR  
CONDITIONS OF APPROVAL14 I hereby certify that the foregoing is true and correct  
Name (Printed/Typed)

DAVID A. EYLER

Title

AGENT

Date 01/09/10

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

/S/ DAVID R. GLASS

Title PETROLEUM ENGINEER

Date

JAN 25 2010

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

APPROVED FOR 90 DAY MONTH PERIOD

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make any statement or representation to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**CIMAREX**

**Cimarex Energy Co. of Colorado**

**Foran 30 Federal No. 2**

API 30-005-63314

Sec 30 T 15S R 28E

660' FNL & 660' FWL

Chaves County, NM

13 3/8" 48# H-40 @ 403'  
Cmt w/ 375 sx, circ 119 sx

17 1/2" Hole to 403'

8 5/8", 24#, J-55 @ 1837'  
Cmt w/ 600 sx, circ 169 sx

11" Hole to 1838'

TOC @ 5486' by CBL

2 3/8", 4.7#, L-80 @ 8761', pkr @ 8736'  
see next page for detail

CIBP @ 8930'

TCP'guns @ 8997'

4 1/2", 11:6#, P-110 @ 9220'  
Cmt w/ 750 sx

Morrow  
Perfs:  
8898' - 8910'

Morrow  
Perfs:  
8940' - 8964'  
7 7/8" Hole to 9225'  
PBSD 9160'

R Morrison 2010

## BUREAU OF LAND MANAGEMENT

Roswell Field Office  
2909 West Second Street  
Roswell, New Mexico 88201  
(575) 627-0272

### Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within **ninety (90)** days from the approval date of this Notice of Intent to Abandon. **If you are unable to plug the well by the 90<sup>th</sup> day provide the BLM Roswell Field Office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when the BLM Roswell Field Office can expect the well to be plugged. Failure to do so will result in enforcement action.**
2. Notification: Contact the BLM Roswell Field Office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, during office hours call (575) 627-0205 or after office hours call (575) 420-2832. Engineer on call during office hours phone (575) 627-0275 or phone (after hours) call (575) 626-5749.
3. Blowout Preventers: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9090 feet; a 3M system for a well not deeper than 13636 feet; and a 5M system for a well not deeper than 22727 feet.
4. Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at a rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.
5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 50 feet of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either class "C" for up to 7500 feet of depth, mixed at 14.8 lbs./gal with 6.3 gallons of fresh water per sack or class "H" for deeper than 7500 feet plugs, mixed at 16.4 lbs./gal with 4.3 gallons of fresh water per sack.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be capped with a 4-inch pipe, 10 feet in length, 4 feet above the ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: Well name and number, the name of the operator, the lease serial number, the surveyed location (the quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer; such as metes and bounds).

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to the BLM Roswell Field Office. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

Following the submittal and approval of the Subsequent Report of Abandonment, a Notice of Intent for Final Abandonment with the proposed surface restoration procedure must be submitted for approval.