

RM

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

District I
1625 N. French Dr., Hobbs, NM 88240

District II
1301 W. Grand Ave., Artesia, NM 88210

District III
1000 Rio Brazos Rd., Aztec, NM 87410

District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

WELL API NO.
30-015-369415. Indicate Type of Lease
STATE FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Limousine 15 K8. Well Number
19. OGRID Number
1474410. Pool name or Wildcat
Cemetery Yeso

11795

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well Other2. Name of Operator
Mewbourne Oil Company3. Address of Operator
PO Box 5270 Hobbs, NM 88240

4. Well Location

Unit Letter K : 2210 feet from the S line and 1650 feet from the W lineSection 15 Township 20S Range 25E NMPM Eddy County11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3423' GLPit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER:

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☐

CASING/CEMENT JOB

OTHER: Completion Sundry

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/01/09 Ran GR/CCL/CNL

12/05/09 Perforate Yeso @ 2766' - 2842' 1 SPF, 25', 25 holes, 0.40" EHD 120° phasing, 19 GC.

12/09/09 Frac with 1000 gals 10% HCl, 200000 gals 20# slickwater & 100000# 20/40 Texas Gold sand.
Perforate Yeso @ 2513' - 2613' 1 SPF, 25', 25 holes, 0.40" EHD 120° phasing, 19 GC. Frac with 1000 gals 10% HCl, 100000 gals 20# slickwater & 50000# 20/40 Texas Gold sand. Flowback for cleanup.

12/16/09 RIH w/tbg & rods. Put well on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 12/21/09Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com Telephone No. 575-393-5905
For State Use OnlyAPPROVED BY: Jackie R TITLE Geologist DATE 1/27/2010
Conditions of Approval (if any):