

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-37372
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name NO BLUFF STATE COM
8. Well Number #8
9. OGRID Number 255333
10. Pool name or Wildcat: (96836) Red Lake, Glorieta-Yeso NE

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM LDD-1) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
LIME ROCK RESOURCES A, L.P.

3. Address of Operator
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

4. Well Location
Unit Letter D : 600 feet from the NORTH line and 330 feet from the WEST line
Section 36 Township 17-S Range 27-E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3577' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: Spud & Surface & Production Casings ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spud well on 1/18/10. Drilled 12-1/4" hole to 445'. Landed 8-5/8" 24# J-55 csg @ 429'. Cmted lead #1 w/100 sx (163 cf) Thixotropic "C" cmt w/10#/sx cal-seal, 10#/sx gilsonite, 1% Cacl2 & 1/8#/sx p-e-flake. Lead #2 w/175 sx (236 cf) "C" cmt w/2% Cacl2, 1/8#/sx p-e-flake. Tailed w/200 sx (270 cf) C cmt w/2% Cacl2. Circ 146 sx cmt to surface. On 1/19/10, PT 8-5/8" csg to 500 psi for 30 min - OK.

Drilled 7-7/8" hole to TD4637' on 2/1/10. Ran open hole logs. Landed 5-1/2" 17# J-55 csg @ 4622'. Cmted lead w/400 sx (756 cf) 35/65 poz C cmt w/0.125#/sx p-e-flake, 3#/sx salt, & 3#/sx gilsonite & tailed w/600 sx (798 cf) C cmt w/0.125#/sx p-e-flake, 0.4% Lap-1, 0.5% CFR-3, & 1/4#/sx D-air. Circ 164 sx cmt to pit. Released drilling rig on 2/2/10. We plan to pressure test the 5-1/2" csg during completion operations.

Spud Date: 1/18/10

Drilling Rig Release Date: 2/2/10

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 2/14/10

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

For State Use Only

APPROVED BY: David May TITLE Field Supervisor DATE 2-18-2010

Conditions of Approval (if any):