

DIRECTIONAL SURVEY REPORT

MACK ENERGY CORPORATION

VIKINGS FEDERAL COM #1

EDDY COUNTY, NM

PREPARED BY: PHIL LEBLANC

MR



August 13, 2009

MACK ENERGY CORPORATION
Mr. Matt Brewer
11352 Lovington Hwy
Box 960
Artesia, NM 88211-1288

RE: MACK ENERGY CORPORATION
VIKINGS FEDERAL COM #1
EDDY COUNTY, NM
RIG: SILVER OAK #2
API Well No.: 30-015-36781
PES Job No.: 101008675-WT-WT

Dear Mr. Brewer:

We hereby certify that the enclosed Original Field Survey Data contained in this report represents to the best of our knowledge, a true and accurate survey of the well at the time the survey was run.

DIRECTIONAL SURVEY DATA

1 – Original Directional Survey Report
1 – Email PDF to:
charless@mackenergycorp.com
leel@mackenergycorp.com
donaldarcher@mackenergycorp.com
jimkrogman@mackenergycorp.com
sli423@sutlog.com

We appreciate the opportunity to work with you and we look forward to your business support. If you have any questions, I can be reached at (337) 233-3982.

Sincerely,

Phil LeBlanc
M/LWD Service Coordinator
PathFinder Energy Services

PL:ll




DIRECTIONAL SURVEY COMPANY REPORT:

1. NAME OF SURVEYING COMPANY: PATHFINDER ENERGY SERVICES
2. NAME OF PERSON(S) PERFORMING SURVEY:
A) JOHN JOLIVETTE
B) JOHN OVERTON
3. POSITION OF SAID PERSON(S): (A-B) SURVEYORS (FIELD ENGINEERS)
4. DATE(S) ON WHICH SURVEY WAS PERFORMED: 07/09/09 TO 07/30/09
5. STATE IN WHICH SURVEY WAS PERFORMED: EDDY COUNTY
6. LOCATION OF WELL: NEW MEXICO
7. TYPE OF SURVEY(S) PERFORMED: MWD
8. COMPLETE IDENTIFICATION OF WELL:

MACK ENERGY CORPORATION
VIKINGS FEDERAL COM #1
EDDY COUNTY, NM
RIG: SILVER OAK #2
API Well No.: 30-015-36781
9. SURVEY(S) CERTIFIED FROM: 5,220 TO 11,196 FEET MEASURED DEPTH.

THIS IS TO VERIFY THAT ATTACHED DOCUMENTS SHOWING THE WELL TO BE DISPLACED AT 4,412.70 FEET ON A BEARING OF 269.83 DEGREES FROM THE CENTER OF THE ROTARY TABLE AT A PROJECTED BIT DEPTH OF 11,196 FEET, ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE.



PHIL LEBLANC
M/LWD SERVICE COORDINATOR

PathFinder Energy Services, Inc.

BHL Report

Page 01/01
Tie-in Date: 07/08/2009
Date Completed: 07/30/2009

MACK ENERGY CORPORATION
VIKINGS FEDERAL COM #1H
EDDY COUNTY, NEW MEXICO
Rig:SILVEROAK #2
PathFinder Office Supervisor: PHIL LEBLANC
PathFinder Field Engineers:JOHN OVERTON
JOHN JOLIVETTE

Survey Horiz. Reference:WELLHEAD
Ref Coordinates: LAT:32.54.47.9940 N LON:104.5.22.7597 W
GRID Reference:NAD27 new mexico east Transverse Mercator
Ref GRID Coord: X: 574780.6000 Y: 696068.2000
North Aligned To:GRID NORTH
Total Magnetic Correction: 7.96° EAST TO GRID
Vertical Section Plane: 269.97
Survey Vert. Reference: 19.00' Kelly Bushing To Ground
Altitude:3655.00' Ground To MSL

Measured Depth	11196.00	(feet)
Inclination	91.01	(deg)
Azimuth	270.07	(deg)
True Vertical Depth	7024.36	(feet)
Vertical Section	4412.69	(feet)
Survey X cord	570367.92	(feet)
Survey Y cord	696055.20	(feet)
Survey Lat	32.91332314 N	(deg)
Survey Lon	104.10403450 W	(deg)
Rectangular Corr. N/S	13.00 S	(feet)
Rectangular Corr. E/W	4412.68 W	(feet)
Closure Distance	4412.70	(feet)
Direction of Closure	269.83	(deg)
Dogleg Severity	0.00	(deg/100ft)

PathFinder Energy Services, Inc.

Survey Report

MACK ENERGY CORPORATION

VIKINGS FEDERAL COM #1H

EDDY COUNTY, NEW MEXICO

Rig:SILVEROAK #2

PathFinder Office Supervisor: PHIL LEBLANC

PathFinder Field Engineers: JOHN OVERTON

JOHN JOLIVETTE

Survey Horiz. Reference:WELLHEAD

Ref Coordinates: LAT:32.54.47.9940 N LON:104.5.22.7597 W

GRID Reference:NAD27 new mexico east Transverse Mercator

Ref GRID Coord: X: 574780.6000 Y: 696068.2000

North Aligned To:GRID NORTH

Total Magnetic Correction: 7.96° EAST TO GRID

Vertical Section Plane: 269.97

Survey Vert. Reference: 19.00' Kelly Bushing To Ground

Altitude:3655.00' Ground To MSL

Survey Calculations by RX5 V5.11i using Minimum Curvature

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Survey Latitude (deg)	Survey Longitude (deg)	Closure Dist Dir (ft) (deg)		DLS (dg/100ft)
THE FOLLOWING ARE TELEDRIFT SURVEYS.												
384.00	0.00	0.00	384.00	0.00	-0.00	0.00 S	0.00 E	32.91333167 N	104.08965546 W	0.01@	129.10	0.00
419.00	3.70	185.00	418.97	35.00	0.09	1.13 S	0.09 W	32.91332857 N	104.08965578 W	1.13@	184.73	10.57
479.00	3.40	176.00	478.86	60.00	0.14	4.83 S	0.14 W	32.91331839 N	104.08965596 W	4.83@	181.64	1.05
544.00	3.00	160.00	543.76	65.00	-0.57	8.35 S	0.58 E	32.91330871 N	104.08965365 W	8.37@	176.04	1.50
604.00	2.90	170.00	603.68	60.00	-1.37	11.32 S	1.38 E	32.91330054 N	104.08965106 W	11.41@	173.06	0.87
665.00	2.70	167.00	664.60	61.00	-1.96	14.24 S	1.97 E	32.91329251 N	104.08964916 W	14.38@	172.13	0.41
727.00	2.50	172.00	726.54	62.00	-2.48	17.01 S	2.49 E	32.91328492 N	104.08964750 W	17.19@	171.68	0.49
788.00	2.00	157.00	787.49	61.00	-3.08	19.30 S	3.09 E	32.91327860 N	104.08964556 W	19.55@	170.91	1.26
849.00	1.70	153.00	848.46	61.00	-3.90	21.09 S	3.91 E	32.91327369 N	104.08964288 W	21.45@	169.49	0.53
944.00	1.50	168.00	943.43	95.00	-4.80	23.56 S	4.81 E	32.91326689 N	104.08963997 W	24.05@	168.46	0.49
1039.00	1.40	164.00	1038.40	95.00	-5.38	25.89 S	5.39 E	32.91326047 N	104.08963810 W	26.45@	168.24	0.15
1134.00	1.30	164.00	1133.37	95.00	-5.99	28.04 S	6.01 E	32.91325456 N	104.08963611 W	28.68@	167.91	0.10
1225.00	0.90	144.00	1224.35	91.00	-6.70	29.61 S	6.71 E	32.91325023 N	104.08963382 W	30.37@	167.23	0.60
1325.00	1.00	169.00	1324.34	100.00	-7.32	31.11 S	7.34 E	32.91324613 N	104.08963179 W	31.96@	166.72	0.42
1421.00	0.80	154.00	1420.33	96.00	-7.78	32.53 S	7.79 E	32.91324221 N	104.08963032 W	33.45@	166.53	0.32
1516.00	0.70	148.00	1515.32	95.00	-8.37	33.62 S	8.39 E	32.91323922 N	104.08962838 W	34.65@	165.98	0.13
1609.00	0.60	122.00	1608.31	93.00	-9.09	34.36 S	9.11 E	32.91323718 N	104.08962606 W	35.55@	165.16	0.33
1954.00	0.30	174.00	1953.30	345.00	-10.71	36.21 S	10.73 E	32.91323207 N	104.08962077 W	37.77@	163.49	0.14
2244.00	0.40	219.00	2243.30	290.00	-10.16	37.76 S	10.18 E	32.91322783 N	104.08962260 W	39.10@	164.92	0.10
2464.00	0.10	81.00	2463.30	220.00	-9.86	38.32 S	9.88 E	32.91322628 N	104.08962356 W	39.58@	165.54	0.22
2620.00	0.20	322.00	2619.30	156.00	-9.83	38.09 S	9.85 E	32.91322693 N	104.08962367 W	39.34@	165.50	0.17
2769.00	0.00	81.00	2768.30	149.00	-9.67	37.88 S	9.69 E	32.91322749 N	104.08962419 W	39.10@	165.65	0.13
2937.00	0.10	50.00	2936.30	168.00	-9.78	37.79 S	9.80 E	32.91322775 N	104.08962382 W	39.04@	165.46	0.06

PathFinder Energy Services, Inc.

Survey Report

MACK ENERGY CORPORATION
VIKINGS FEDERAL COM #1H
EDDY COUNTY, NEW MEXICO
RIG:SILVEROAK #2

Page 02/06

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Survey Latitude (deg)	Survey Longitude (deg)	Closure Dist (ft)	Dir (deg)	DLS (dg/100ft)
3096.00	0.10	68.00	3095.30	159.00	-10.02	37.65 S	10.04 E	32.91322813 N	104.08962305 W	38.96@	165.07	0.02
3254.00	0.10	157.00	3253.30	158.00	-10.20	37.72 S	10.22 E	32.91322793 N	104.08962246 W	39.08@	164.85	0.09
3412.00	0.10	104.00	3411.30	158.00	-10.38	37.88 S	10.40 E	32.91322748 N	104.08962185 W	39.29@	164.64	0.06
3539.00	0.10	116.00	3538.30	127.00	-10.59	37.96 S	10.61 E	32.91322728 N	104.08962118 W	39.41@	164.38	0.02
3789.00	0.30	181.00	3788.29	250.00	-10.78	38.71 S	10.80 E	32.91322521 N	104.08962058 W	40.19@	164.42	0.11
3946.00	0.30	198.00	3945.29	157.00	-10.64	39.51 S	10.66 E	32.91322301 N	104.08962103 W	40.92@	164.90	0.06
4099.00	0.10	196.00	4098.29	153.00	-10.48	40.02 S	10.50 E	32.91322161 N	104.08962155 W	41.37@	165.30	0.13
4259.00	0.00	264.00	4258.29	160.00	-10.44	40.15 S	10.46 E	32.91322124 N	104.08962168 W	41.49@	165.39	0.06
4416.00	0.50	340.00	4415.29	157.00	-10.21	39.51 S	10.23 E	32.91322301 N	104.08962244 W	40.81@	165.49	0.32
4574.00	0.20	326.00	4573.29	158.00	-9.82	38.63 S	9.84 E	32.91322543 N	104.08962370 W	39.87@	165.71	0.20
4761.00	0.30	338.00	4760.28	187.00	-9.45	37.91 S	9.47 E	32.91322742 N	104.08962489 W	39.07@	165.97	0.06
4916.00	0.10	326.00	4915.28	155.00	-9.23	37.42 S	9.25 E	32.91322876 N	104.08962563 W	38.55@	166.12	0.13
5065.00	0.30	315.00	5064.28	149.00	-8.88	37.04 S	8.90 E	32.91322982 N	104.08962676 W	38.09@	166.49	0.14
** TIED INTO TELEDRIFT SURVEYS AT 5220' MD.												
5220.00	0.30	322.00	5219.28	155.00	-8.34	36.43 S	8.36 E	32.91323149 N	104.08962850 W	37.38@	167.08	0.02
THE FOLLOWING ARE PATHFINDER MWD SURVEYS.												
5364.00	0.35	322.17	5363.28	144.00	-7.84	35.79 S	7.86 E	32.91323327 N	104.08963013 W	36.64@	167.61	0.03
5519.00	1.23	338.25	5518.26	155.00	-6.93	33.87 S	6.95 E	32.91323855 N	104.08963308 W	34.57@	168.40	0.58
5673.00	1.32	338.60	5672.22	154.00	-5.68	30.68 S	5.69 E	32.91324731 N	104.08963716 W	31.20@	169.49	0.06
5827.00	0.88	345.46	5826.19	154.00	-4.73	27.88 S	4.75 E	32.91325501 N	104.08964021 W	28.28@	170.34	0.30
5986.00	0.97	353.37	5985.17	159.00	-4.27	25.36 S	4.29 E	32.91326193 N	104.08964170 W	25.72@	170.41	0.10
6145.00	0.88	3.13	6144.15	159.00	-4.18	22.81 S	4.20 E	32.91326896 N	104.08964197 W	23.19@	169.57	0.11
6303.00	0.79	4.44	6302.14	158.00	-4.34	20.51 S	4.35 E	32.91327527 N	104.08964146 W	20.97@	168.03	0.06
6393.00	0.79	8.29	6392.13	90.00	-4.47	19.28 S	4.48 E	32.91327866 N	104.08964100 W	19.79@	166.90	0.06
6425.00	0.70	9.74	6424.13	32.00	-4.54	18.87 S	4.55 E	32.91327979 N	104.08964079 W	19.41@	166.44	0.29
6456.00	2.29	278.82	6455.12	31.00	-3.96	18.59 S	3.97 E	32.91328057 N	104.08964268 W	19.01@	167.94	7.76
6488.00	6.51	267.51	6487.01	32.00	-1.51	18.57 S	1.52 E	32.91328063 N	104.08965064 W	18.63@	175.31	13.40
6520.00	10.82	264.71	6518.64	32.00	3.29	18.92 S	3.28 W	32.91327969 N	104.08966630 W	19.21@	189.84	13.53

PathFinder Energy Services, Inc.

Survey Report

MACK ENERGY CORPORATION
VIKINGS FEDERAL COM #1H
EDDY COUNTY, NEW MEXICO
RIG:SILVEROAK #2

Page 03/06

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Survey Latitude (deg)	Survey Longitude (deg)	Closure Dist (ft)	Dir (deg)	DLS (dg/100ft)
6552.00	14.68	263.69	6549.85	32.00	10.31	19.65 S	10.30 W	32.91327774 N	104.08968920 W	22.18@	207.68	12.08
6583.00	18.29	263.31	6579.57	31.00	19.05	20.64 S	19.04 W	32.91327505 N	104.08971768 W	28.09@	222.69	11.65
6615.00	21.54	264.42	6609.65	32.00	29.89	21.80 S	29.88 W	32.91327194 N	104.08975300 W	36.99@	233.88	10.23
6647.00	24.36	266.69	6639.12	32.00	42.33	22.75 S	42.32 W	32.91326941 N	104.08979354 W	48.05@	241.73	9.23
6678.00	27.35	266.77	6667.01	31.00	55.82	23.52 S	55.81 W	32.91326737 N	104.08983752 W	60.57@	247.15	9.65
6710.00	30.16	267.96	6695.06	32.00	71.20	24.22 S	71.19 W	32.91326555 N	104.08988762 W	75.20@	251.21	8.96
6741.00	32.36	271.13	6721.56	31.00	87.28	24.34 S	87.27 W	32.91326533 N	104.08994002 W	90.60@	254.42	8.86
6773.00	34.03	272.70	6748.34	32.00	104.79	23.75 S	104.78 W	32.91326707 N	104.08999707 W	107.43@	257.23	5.87
6805.00	36.05	273.39	6774.54	32.00	123.13	22.77 S	123.12 W	32.91326988 N	104.09005684 W	125.21@	259.52	6.43
6837.00	38.51	272.49	6800.00	32.00	142.49	21.78 S	142.48 W	32.91327272 N	104.09011990 W	144.13@	261.31	7.87
6869.00	40.98	270.30	6824.60	32.00	162.94	21.29 S	162.93 W	32.91327419 N	104.09018654 W	164.31@	262.55	8.87
6900.00	42.65	268.88	6847.70	31.00	183.60	21.44 S	183.59 W	32.91327390 N	104.09025388 W	184.84@	263.34	6.19
6932.00	44.67	268.28	6870.85	32.00	205.69	21.99 S	205.68 W	32.91327253 N	104.09032584 W	206.85@	263.90	6.44
6964.00	46.69	269.16	6893.21	32.00	228.58	22.50 S	228.56 W	32.91327128 N	104.09040043 W	229.67@	264.38	6.61
6996.00	49.15	271.12	6914.66	32.00	252.32	22.44 S	252.31 W	32.91327161 N	104.09047781 W	253.31@	264.92	8.93
7027.00	51.35	272.15	6934.48	31.00	276.14	21.75 S	276.13 W	32.91327364 N	104.09055543 W	276.99@	265.50	7.54
7059.00	53.82	272.49	6953.92	32.00	301.54	20.72 S	301.53 W	32.91327663 N	104.09063816 W	302.24@	266.07	7.76
7091.00	56.63	272.29	6972.17	32.00	327.80	19.63 S	327.79 W	32.91327981 N	104.09072372 W	328.37@	266.57	8.80
7123.00	59.62	271.98	6989.06	32.00	354.95	18.62 S	354.94 W	32.91328276 N	104.09081219 W	355.43@	267.00	9.38
7154.00	63.49	271.84	7003.83	31.00	382.18	17.71 S	382.18 W	32.91328543 N	104.09090094 W	382.59@	267.35	12.49
7186.00	67.18	271.45	7017.18	32.00	411.25	16.87 S	411.24 W	32.91328790 N	104.09099564 W	411.58@	267.65	11.58
7218.00	69.64	270.30	7028.95	32.00	441.00	16.42 S	440.99 W	32.91328933 N	104.09109257 W	441.29@	267.87	8.38
7250.00	71.49	270.82	7039.60	32.00	471.17	16.13 S	471.16 W	32.91329033 N	104.09119089 W	471.44@	268.04	5.98
7281.00	74.74	271.35	7048.60	31.00	500.82	15.56 S	500.82 W	32.91329207 N	104.09128752 W	501.06@	268.22	10.61
7313.00	78.35	270.69	7056.05	32.00	531.93	15.01 S	531.93 W	32.91329378 N	104.09138889 W	532.14@	268.38	11.46
7344.00	80.67	268.54	7061.69	31.00	562.41	15.22 S	562.40 W	32.91329341 N	104.09148820 W	562.61@	268.45	10.13
7376.00	83.32	267.91	7066.15	32.00	594.08	16.20 S	594.07 W	32.91329091 N	104.09159141 W	594.29@	268.44	8.51

PathFinder Energy Services, Inc.

Survey Report

MACK ENERGY CORPORATION
VIKINGS FEDERAL COM #1H
EDDY COUNTY, NEW MEXICO
RIG:SILVEROAK #2

Page 04/06

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Survey Latitude (deg)	Survey Longitude (deg)	Closure Dist Dir (ft) (deg)		DLS (dg/100ft)
7407.00	84.45	267.99	7069.45	31.00	624.89	17.30 S	624.88 W	32.91328807 N	104.09169179 W	625.12@	268.41	3.65
7438.00	86.81	268.55	7071.81	31.00	655.78	18.24 S	655.77 W	32.91328570 N	104.09179247 W	656.02@	268.41	7.82
7500.00	91.68	269.79	7072.63	62.00	717.75	19.13 S	717.74 W	32.91328362 N	104.09199440 W	717.99@	268.47	8.10
7595.00	91.18	270.89	7070.26	95.00	812.72	18.57 S	812.71 W	32.91328577 N	104.09230385 W	812.92@	268.69	1.27
7658.00	91.29	270.88	7068.90	63.00	875.69	17.60 S	875.68 W	32.91328884 N	104.09250906 W	875.86@	268.85	0.17
7719.00	90.06	271.49	7068.18	61.00	936.67	16.34 S	936.67 W	32.91329269 N	104.09270776 W	936.81@	269.00	2.25
7783.00	89.33	271.35	7068.52	64.00	1000.65	14.75 S	1000.64 W	32.91329745 N	104.09291622 W	1000.75@	269.16	1.16
7846.00	90.39	271.28	7068.68	63.00	1063.63	13.30 S	1063.63 W	32.91330182 N	104.09312144 W	1063.71@	269.28	1.69
7910.00	90.50	271.61	7068.18	64.00	1127.61	11.69 S	1127.60 W	32.91330665 N	104.09332991 W	1127.66@	269.41	0.54
7973.00	90.34	271.51	7067.72	63.00	1190.58	9.97 S	1190.58 W	32.91331176 N	104.09353510 W	1190.62@	269.52	0.30
8036.00	89.78	271.34	7067.65	63.00	1253.56	8.41 S	1253.56 W	32.91331646 N	104.09374031 W	1253.59@	269.62	0.93
8100.00	91.12	271.88	7067.15	64.00	1317.53	6.61 S	1317.53 W	32.91332180 N	104.09394875 W	1317.55@	269.71	2.26
8163.00	91.62	271.60	7065.64	63.00	1380.48	4.70 S	1380.48 W	32.91332745 N	104.09415387 W	1380.49@	269.81	0.91
8226.00	91.85	270.81	7063.74	63.00	1443.44	3.37 S	1443.44 W	32.91333149 N	104.09435901 W	1443.44@	269.87	1.31
8290.00	91.01	270.63	7062.14	64.00	1507.42	2.57 S	1507.41 W	32.91333409 N	104.09456747 W	1507.42@	269.90	1.34
8352.00	89.44	269.81	7061.89	62.00	1569.41	2.33 S	1569.41 W	32.91333513 N	104.09476949 W	1569.41@	269.91	2.86
8412.00	89.55	269.99	7062.42	60.00	1629.41	2.44 S	1629.41 W	32.91333522 N	104.09496499 W	1629.41@	269.91	0.35
8474.00	90.34	269.40	7062.48	62.00	1691.41	2.77 S	1691.41 W	32.91333470 N	104.09516702 W	1691.41@	269.91	1.59
8537.00	90.84	268.87	7061.83	63.00	1754.40	3.72 S	1754.40 W	32.91333247 N	104.09537228 W	1754.40@	269.88	1.16
8599.00	89.11	268.82	7061.86	62.00	1816.38	4.97 S	1816.38 W	32.91332942 N	104.09557427 W	1816.39@	269.84	2.79
8661.00	88.54	269.57	7063.13	62.00	1878.36	5.84 S	1878.36 W	32.91332741 N	104.09577624 W	1878.37@	269.82	1.52
8724.00	88.71	270.13	7064.64	63.00	1941.34	6.00 S	1941.34 W	32.91332735 N	104.09598147 W	1941.35@	269.82	0.93
8788.00	89.83	269.20	7065.46	64.00	2005.34	6.38 S	2005.33 W	32.91332672 N	104.09618999 W	2005.34@	269.82	2.27
8851.00	91.01	268.51	7065.00	63.00	2068.32	7.64 S	2068.32 W	32.91332365 N	104.09639524 W	2068.33@	269.79	2.17
8914.00	90.78	268.65	7064.01	63.00	2131.30	9.20 S	2131.29 W	32.91331974 N	104.09660045 W	2131.31@	269.75	0.43
8977.00	92.18	268.58	7062.39	63.00	2194.26	10.72 S	2194.25 W	32.91331595 N	104.09680562 W	2194.28@	269.72	2.22
9039.00	91.79	269.33	7060.24	62.00	2256.21	11.85 S	2256.20 W	32.91331322 N	104.09700750 W	2256.23@	269.70	1.36

PathFinder Energy Services, Inc.

Survey Report

MACK ENERGY CORPORATION
VIKINGS FEDERAL COM #1H
EDDY COUNTY, NEW MEXICO
RIG:SILVEROAK #2

Page 05/06

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Survey Latitude (deg)	Survey Longitude (deg)	Closure Dist (ft)	Dir (deg)	DLS (dg/100ft)
9102.00	91.12	270.36	7058.64	63.00	2319.19	12.02 S	2319.18 W	32.91331314 N	104.09721272 W	2319.21@	269.70	1.95
9165.00	89.83	270.96	7058.12	63.00	2382.18	11.29 S	2382.17 W	32.91331553 N	104.09741797 W	2382.20@	269.73	2.26
9228.00	90.39	270.48	7058.00	63.00	2445.17	10.50 S	2445.17 W	32.91331809 N	104.09762324 W	2445.19@	269.75	1.17
9290.00	91.46	270.46	7056.99	62.00	2507.16	9.99 S	2507.16 W	32.91331987 N	104.09782523 W	2507.18@	269.77	1.73
9353.00	91.62	270.41	7055.30	63.00	2570.14	9.52 S	2570.13 W	32.91332157 N	104.09803043 W	2570.15@	269.79	0.27
9416.00	91.40	270.36	7053.64	63.00	2633.11	9.09 S	2633.11 W	32.91332312 N	104.09823564 W	2633.12@	269.80	0.36
9479.00	90.67	270.59	7052.50	63.00	2696.10	8.57 S	2696.10 W	32.91332494 N	104.09844088 W	2696.11@	269.82	1.22
9541.00	90.50	270.75	7051.87	62.00	2758.09	7.85 S	2758.09 W	32.91332731 N	104.09864288 W	2758.10@	269.84	0.38
9605.00	90.73	270.23	7051.18	64.00	2822.08	7.30 S	2822.08 W	32.91332921 N	104.09885141 W	2822.09@	269.85	0.89
9668.00	90.28	270.47	7050.63	63.00	2885.08	6.91 S	2885.08 W	32.91333065 N	104.09905668 W	2885.09@	269.86	0.81
9732.00	90.45	270.42	7050.22	64.00	2949.08	6.42 S	2949.07 W	32.91333241 N	104.09926521 W	2949.08@	269.88	0.28
9795.00	90.84	270.65	7049.51	63.00	3012.07	5.83 S	3012.07 W	32.91333441 N	104.09947047 W	3012.07@	269.89	0.72
9859.00	91.90	270.79	7047.98	64.00	3076.05	5.02 S	3076.04 W	32.91333701 N	104.09967894 W	3076.05@	269.91	1.67
9923.00	91.62	270.54	7046.02	64.00	3140.01	4.28 S	3140.01 W	32.91333944 N	104.09988736 W	3140.01@	269.92	0.59
9986.00	90.67	270.58	7044.76	63.00	3202.99	3.67 S	3202.99 W	32.91334151 N	104.10009260 W	3202.99@	269.93	1.51
10049.00	90.62	270.29	7044.05	63.00	3265.99	3.19 S	3265.99 W	32.91334321 N	104.10029786 W	3265.99@	269.94	0.47
10113.00	90.89	270.56	7043.20	64.00	3329.98	2.71 S	3329.98 W	32.91334490 N	104.10050638 W	3329.98@	269.95	0.60
10176.00	91.29	270.63	7042.01	63.00	3392.96	2.06 S	3392.96 W	32.91334708 N	104.10071162 W	3392.96@	269.97	0.64
10240.00	91.68	270.02	7040.35	64.00	3456.94	1.70 S	3456.94 W	32.91334847 N	104.10092009 W	3456.94@	269.97	1.13
10303.00	91.68	269.05	7038.50	63.00	3519.91	2.21 S	3519.91 W	32.91334744 N	104.10112528 W	3519.91@	269.96	1.54
10367.00	90.67	269.10	7037.19	64.00	3583.89	3.24 S	3583.89 W	32.91334499 N	104.10133376 W	3583.89@	269.95	1.58
10431.00	90.73	268.90	7036.41	64.00	3647.88	4.36 S	3647.87 W	32.91334231 N	104.10154227 W	3647.88@	269.93	0.33
10458.00	90.84	268.68	7036.04	27.00	3674.87	4.93 S	3674.87 W	32.91334091 N	104.10163023 W	3674.87@	269.92	0.91
10522.00	90.66	268.53	7035.20	64.00	3738.84	6.48 S	3738.84 W	32.91333701 N	104.10183870 W	3738.85@	269.90	0.37
10585.00	90.75	268.70	7034.42	63.00	3801.82	8.01 S	3801.82 W	32.91333320 N	104.10204393 W	3801.83@	269.88	0.31
10649.00	90.75	269.19	7033.59	64.00	3865.81	9.19 S	3865.80 W	32.91333035 N	104.10225243 W	3865.81@	269.86	0.76
10712.00	91.01	268.99	7032.62	63.00	3928.79	10.19 S	3928.79 W	32.91332798 N	104.10245768 W	3928.80@	269.85	0.52

PathFinder Energy Services, Inc.

Survey Report

MACK ENERGY CORPORATION
VIKINGS FEDERAL COM #1H
EDDY COUNTY, NEW MEXICO
RIG:SILVEROAK #2

Page 06/06

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Survey Latitude (deg)	Survey Longitude (deg)	Closure Dist Dir (ft) (deg)		DLS (dg/100ft)
10775.00	91.36	268.65	7031.32	63.00	3991.76	11.48 S	3991.76 W	32.91332479 N	104.10266289 W	3991.78@	269.84	0.77
10839.00	91.01	269.37	7029.99	64.00	4055.74	12.59 S	4055.73 W	32.91332214 N	104.10287136 W	4055.75@	269.82	1.25
10902.00	90.84	269.29	7028.97	63.00	4118.73	13.33 S	4118.72 W	32.91332049 N	104.10307662 W	4118.74@	269.81	0.30
10966.00	90.75	270.38	7028.09	64.00	4182.72	13.51 S	4182.71 W	32.91332037 N	104.10328514 W	4182.74@	269.81	1.71
11029.00	90.84	270.12	7027.21	63.00	4245.71	13.23 S	4245.71 W	32.91332150 N	104.10349041 W	4245.73@	269.82	0.44
11092.00	91.01	270.07	7026.20	63.00	4308.71	13.13 S	4308.70 W	32.91332217 N	104.10369567 W	4308.72@	269.83	0.28
STRAIGHT LINE PROJECTION TO BIT DEPTH AT 11196' MD.												
11196.00	91.01	270.07	7024.36	104.00	4412.69	13.00 S	4412.68 W	32.91332314 N	104.10403450 W	4412.70@	269.83	0.00

** The survey data at tie-in point was furnished by a recognized survey company and entered as submitted. Survey stations above the tie-in point represent recalculated data by PathFinder Energy Services, Inc. and may reflect minor changes due to rounding differences between survey programs. Only survey stations taken by qualified PathFinder personnel are subject to certification.