


OCD-ARTESIA

ATS-10-50
EA-10-321 RMForm 3160-3
(April 2004)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

FORM APPROVED
OMB No 1004-0137
Expires March 31, 2007

5 Lease Serial No.
NM-19423

6 If Indian, Allottee or Tribe Name

7. If Unit or CA Agreement, Name and No

8 Lease Name and Well No.
Seldom Seen 15 Federal No. 1

9. API Well No.
30-015- 37714

10. Field and Pool, or Exploratory
Sage Wellcamp Gas
Draw; Midway Gas

11. Sec., T. R. M. or Blk. and Survey or Area
15-25S-26E

12. County or Parish
Eddy

13. State
NM

1a Type of Work ☒ DRILL ☐ REENTER1b. Type of Well ☐ Oil Well ☒ Gas Well ☐ Other ☒ Single Zone ☐ Multiple Zone

2 Name of Operator

Cimarex Energy Co. of Colorado

3a Address

600 N. Marienfeld St., Ste. 600; Midland, TX 79701

3b. Phone No (include area code)

432-571-7800

4. Location of Well (Report location clearly and in accordance with any State requirements. *)

At Surface 660 FSL & 660 FEL

At proposed prod. Zone 1250 FSL & 660 FSL

14. Distance in miles and direction from nearest town or post office*

15 Distance from proposed*
location to nearest
property or lease line, ft.
(Also to nearest drig unit line if
any) 660

16 No of acres in lease
2560

17. Spacing Unit dedicated to this well
E2 320 acres

18 Distance from proposed location*
to nearest well, drilling, completed,
applied for, on this lease, ft.
N/A

19. Proposed Depth
Pilot - 10200 4528 - VD
hole 12500 12543' MD

20 BLM/BIA Bond No. on File
R6H 2/16/10
NM-2575

21. Elevations (Show whether DF, KDB, RT, GL, etc.)

3336' GR

22. Approximate date work will start*

03.01.10

23 Estimated duration

25-35 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

- Well plat certified by a registered surveyor
- A Drilling Plan
- A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).
- Bond to cover the operations unless covered by an existing bond on file (see Item 20 above)
- Operator Certification
- Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature

Zeno Farris

Name (Printed/Typed)

Zeno Farris

Date

01.20.10

Title

Manager Operations Administration

Approved By (Signature)

/s/ Don Peterson

Name (Printed/Typed)

Date

MAR 17 2010

Title

FIELD MANAGER

Office

CARLSBAD FIELD OFFICE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached

APPROVAL FOR TWO YEARS

Title 18 U.S.S. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

* (Instructions on page 2)

Approval Subject to General Requirements
& Special Stipulations Attached

Carlsbad Controlled Water Basin

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

DISTRICT I
1825 N. French Dr., Hobbs, NM 88240

DISTRICT II
1801 N. Grand Avenue, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Artesia, NM 87410

DISTRICT IV
1829 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-102
Revised October 12, 2006

Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, New Mexico 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

☐ AMENDED REPORT

API Number 30-015-37714	Pool Code 96890	Pool Name Sage Draw; Wolfcamp, E
Property Code 380946	Property Name SELDON SEEN "15" FEDERAL	Well Number 1H
GRID No. 162683	Operator Name CIMAREX ENERGY CO. OF COLORADO	Elevation 3336'

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	15	25 S	26 E		660	SOUTH	660	EAST	EDDY



Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
M	15	25 S	26 E		1250	SOUTH	660	WEST	EDDY
Dedicated Acres 160320	Joint or Infill	Consolidation Code	Order No.						

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

<p>PROPOSED BOTTOM HOLE LOCATION Lat - N 32°07'34.17\" Long - W 104°17'13.37\" NMSPC - N 408834.840 E 855665.614 (NAD-83)</p> <p>SURFACE LOCATION Lat - N 32°07'27.79\" Long - W 104°16'27.01\" NMSPC - N 408893.2 E 855652.5 (NAD-83)</p> <p>EOC 707 FSL & 951 FEL</p> <p>Proposed Producing Interval</p>	<p>OPERATOR CERTIFICATION</p> <p>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</p> <p><i>Zeno Farris</i> 2/16/2010 Signature Date</p> <p>Zeno Farris Printed Name</p>
	<p>SURVEYOR CERTIFICATION</p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p><i>GARY L. JONES</i> Date Surveyed</p> <p><i>GARY L. JONES</i> Signature & Seal of Professional Surveyor</p> <p>W.S. JONES Certificate No. Gary L. Jones 7977</p> <p>BASIN SURVEYS</p>

**SECTION 15, TOWNSHIP 25 SOUTH, RANGE 26 EAST, N.M.P.M.,
EDDY COUNTY, NEW MEXICO.**



Directions to Location:

FROM THE JUNCTION OF MEANS ROAD AND PRICKLY
PEAR, GO EAST TURNING SOUTHERLY ON PRICKLY
PEAR FOR 3.7 MILES TO PROPOSED LEASE ROAD.

CIMAREX ENERGY CO. OF COLORADO

REF: SELDOM SEEN "15" FEDERAL #1 / WELL PAD TOPO

THE SELDOM SEEN "15" FEDERAL #1 LOCATED 660'

FROM THE SOUTH LINE AND 660' FROM THE EAST LINE OF

SECTION 15, TOWNSHIP 25 SOUTH, RANGE 26 EAST,

N.M.P.M., EDDY COUNTY, NEW MEXICO.

BASIN SURVEYS P.O. BOX 1786—HOBBS, NEW MEXICO

W.O. Number: 21778 Drawn By: J. SMALL

Date: 10-07-2009 Disk: JMS 21778

Survey Date: 10-02-2009 Sheet 1 of 1 Sheets






Exhibit A - One-Mile Radius Map
Seldom Seen 15 Federal No. 1
Cimarex Energy Co. of Colorado
15-25S-26E
660 FSL & 660 FEL
Eddy County, NM



SELDOM SEEN "15" FEDERAL #1
Located 660' FSL and 660' FEL
Section 15, Township 25 South, Range 26 East,
N.M.P.M., Eddy County, New Mexico.



P.O. Box 1786
 1120 N. West County Rd.
 Hobbs, New Mexico 88241
 (575) 393-7316 - Office
 (575) 392-2206 - Fax
basinsurveys.com

W.O. Number: JMS 21778


Survey Date: 10-02-2009

Scale: 1" = 2 Miles


Date: 10-07-2009

CIMAREX
ENERGY CO.
OF COLORADO

Exhibit B



SELDOM SEEN "15" FEDERAL #1
 Located 660' FSL and 660' FEL
 Section 15, Township 25 South, Range 26 East,
 N.M.P.M., Eddy County, New Mexico.



P.O. Box 1786
 1120 N. West County Rd.
 Hobbs, New Mexico 88241
 (575) 393-7316 - Office
 (575) 392-2206 - Fax
basinsurveys.com

W.O. Number: JMS 21778

Survey Date: 10-02-2009

Scale: 1" = 2000'

Date: 10-07-2009



**CIMAREX
 ENERGY CO.
 OF COLORADO**

Exhibit C

Application to Drill
Seldom Seen 15 Federal No. 1
Cimarex Energy Co. of Colorado
Unit Letter P, Section 15
T25S-R26E, Eddy County, NM

In response to questions asked under Section II B of Bulletin NTL-6, the following information is provided for your consideration:

1. Location: SHL 660 FSL & 660 FEL
2. Elevation above sea level: 3336' GR
3. Geologic name of surface formation: Quaternary Alluvium Deposits
4. Drilling tools and associated equipment: Conventional rotary drilling rig using fluid as a circulating medium for solids removal.

5. Proposed drilling depth: ~~12500'~~ 10200' Pilot Hole, KOP 9340'
Horizontal: 13543' MD / 9528' VD

6. Estimated tops of geological markers:

Top Salt	1102'	3rd Bone Spring Ss	8258'
Base Salt	1686'	Wolfcamp	8610'
Delaware	1885'	Cisco-Canyon	10295'
Cherry Canyon	2854'	Strawn	10612'
Brushy Canyon	3890'	Atoka	10814'
Bone Spring	5413'	Morrow	11403'
1st Bone Spring Ss	6400'	Middle Morrow	11854'
2nd Bone Spring Ss	6954'	Lower Morrow	12182'

7. Possible mineral bearing formations:

Morrow	Gas
Atoka	Gas
Strawn	Gas
Cisco-Canyon	Gas
Wolfcamp	Gas
Bone Spring	Gas
Delaware	Gas

Application to Drill
Seldom Seen 15 Federal No. 1
 Cimarex Energy Co. of Colorado
 Unit Letter P, Section 15
 T25S-R26E, Eddy County, NM

8. Mud Circulating System:

Depth		Mud Wt	Visc	Fluid Loss	Type Mud
0'	to 450'	8.4 - 8.6	30-32	NC	FW spud mud. Sweep as needed to clean hole.
450'	to 1810'	10	28-29	NC	Saturated Brine. Sweep as needed to clean hole.
1810'	to 12500'	9.5 - 9.8	28-29	NC	Cut brine. Sweep as needed to clean hole.

Sufficient mud materials will be kept on location at all times in order to combat lost circulation or unexpected kicks. In order to run DSTs, open hole logs, and casing, the viscosity and water loss may have to be adjusted in order to meet these needs.

9. Casing Program:

	Hole Size	Depth		Casing OD	Weight	Collar	Grade
Surface	17½"	0'	to 450'	New 13½"	48#	STC	H-40
Intermediate	12½"	0'	to 1810'	New 9½"	36#	LTC	J-55
Production	8½"	0'	to 12500'	New 7"	26#	LTC	P-110

10. Cementing Program:

Surface	500 sx Premium Plus + 0.125# Poly-e-flake + 2% CaCl ₂ (wt 14.8, yld 1.34) TOC Surface
Intermediate	Lead: 250 sx Interfill C + 1/4# Flocele (wt 11.9, yld 2.45) Tail: 250 sks Premium Plus + 1% CaCl ₂ (wt 14.8, yld 1.33) TOC Surface
Production	Lead: 1500 sx Interfill H + 0.25% HR-7 + 5# Gilsonite + 0.25# Flocele (wt 11.9, yld 2.47) Tail: 500 sx Super H + 0.5% Halad-344 + 0.4% CFR-3 + 1# Salt + 5# Gilsonite + 0.125# Poly-e-flake + 0.25% HR-7 (wt 13.2, yld 1.67) TOC 1610'

Fresh water zones will be protected by setting 13½" casing at 450' and cementing to surface. Hydrocarbon zones will be protected by setting 9½" casing at 1810' and 7" casing at 12500' and cementing to 12500'.

<u>Collapse Factor</u>	<u>Burst Factor</u>	<u>Tension Factor</u>
1.125	1.125	1.6

3160-5 Revised Casing Plans
Seldom Seen 15 Federal No. 1
 Cimarex Energy Co. of Colorado
 Eddy County, NM

Casing

<u>String</u>	<u>Hole Size</u>	<u>Csg Size</u>	<u>Csg Wt</u>	<u>Csg Grd</u>	<u>Collar</u>	<u>From</u>	<u>To</u>
Surface	17½"	13⅝"	48#	H-40	STC	0'	450'
Intermediate	12¼"	9⅝"	40#	J-55	LTC	0'	1806' See CCA
Production	8¾"	7"	26#	P-110	LTC	0'	9280'
Fiberglass	8¾"	2⅝"	2.18#	IJ		9280'	10200'
Lateral Pt. 1	6⅝"	4½"	11.6#	P-110	BTC	9080'	9798'
Lateral Pt. 2	6⅝"	4½"	11.6#	P-111	LTC	9798'	13543'

Cement

Surface & No Change
Intermediate

Production Lead: 620 sx Interfill H with 0.3% HR-601, 5 lb/sx Gilsonite, 0.125 lb/sx Poly-E-Flake (wt 11.9, yld 2.47)
Tail: 480 sx Super H with 0.5% Halad ® 344, 0.25% D-Air 3000, 0.4% CFR-3, 1 lb/sx Salt, 5 lb/sx Gilsonite, 0.125 lb/sx Poly-E-Flake, 0.35% HR-7 (wt 13.2, yld 1.61) **Estimated TOC 1600'**

Lateral Lateral liner will be PEAK completion assembly liner and will require no cement.

Drilling Plans

After drilling and setting surface and intermediate casing, drill to vertical TD 10200' and log. Set 7" casing to 9280' and cross over to 2⅝" 2000 psi IJ fiberglass tubing underneath (to 10200') and cement in place. Drill out of the bottom of the 7" with a 6⅝" bit and through cement and fiberglass tubing to KOP @ 9340' and kick off to drill the lateral. The fiberglass tubing effectively circulates cement to surface and plugs back the open hole.

Application to Drill
Seldom Seen 15 Federal No. 1
Cimarex Energy Co. of Colorado
Unit Letter P, Section 15
T25S-R26E, Eddy County, NM

11. Pressure control Equipment:

Exhibit "E". A 13 5/8" 5000 PSI working pressure B.O.P. consisting of one set of blind rams and one set of pipe rams and a 5000# annular type preventer. A choke manifold and 120 gallon accumulator with floor and remote operating stations and auxiliary power system. Rotating head below 450.' A kelly cock will be installed and maintained in operable condition and a drill string safety valve in the open position will be available on the rig floor.

BOP unit will be hydraulically operated. BOP will be nipped up and operated at least once a day while drilling and the blind rams will be operated when out of hole during trips. No abnormal pressure or temperature is expected while drilling. From the base of the surface pipe through the running of production casing, the well will be equipped with a 5000 psi BOP system.

12. Testing, Logging and Coring Program:

- See
Corr
- A. Mud logging program: 2-man unit from 1810' to TD.
 - B. Electric logging program: CNL / LDT / CAL / GR, DLL / CAL / GR
 - C. No DSTs or cores are planned.

13. Potential Hazards:

No abnormal pressures or temperatures are expected. In accordance with Onshore Order 6, Cimarex has encountered H₂S in a one-time encounter in an Intra-salt Pocket and while drilling and completing wells in the Delaware Mountain Group. In this regard, attached is an H₂S Drilling Operations Plan. The ROEs encountered do not meet the BLM's minimum requirements for the submission of a "Public Protection Plan" for the drilling and completion of this well. Adequate flare lines will be installed off the mud / gas separator where gas may be flared safely. All personnel will be familiar with all aspects of safe operation of equipment being used.

Estimated BHP 4000 psi Estimated BHT 175°

14. Road and location construction will begin after BLM approval of APD. Anticipated spud date as soon as approved.

Drilling expected to take 25-35 days

If production casing is run an additional 30 days will be required to complete and construct surface facilities.

16. Other Facets of Operations:

After running casing, cased hole gamma ray neutron collar logs will be run from total depth over possible pay intervals.

Wellcamp — ~~Morrow~~ pay will be perforated and stimulated.

The proposed well will be tested and potentialied as a gas well.

Cimarex Energy Co.

Eddy County (NM83E)

Sec 15 - T25S - R26E

Seldom Seen 15 Fed #1

Wellbore #1

Plan: Plan #1

Standard Planning Report

15 February, 2010

Great White Directional Services Planning Report

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well Seldom Seen 15 Fed #1
Company:	Cimarex Energy Co.	TVD Reference:	WELL @ 0.0usft (Original Well Elev)
Project:	Eddy County (NM83E)	MD Reference:	WELL @ 0.0usft (Original Well Elev)
Site:	Sec 15 - T25S - R26E	North Reference:	Grid
Well:	Seldom Seen 15 Fed #1	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Plan #1		

Project:	Eddy County (NM83E)
Map System:	US State Plane 1983
Geo Datum:	North American Datum 1983
Map Zone:	New Mexico Eastern Zone
System Datum:	Mean Sea Level

Site:	Sec 15 - T25S - R26E				
Site Position:		Northing:	408,993.20 usft	Latitude:	32° 7' 27.795 N
From:	Map	Easting:	559,652.50 usft	Longitude:	104° 16' 27.013 W
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16"	Grid Convergence:	0.03°

Well:	Seldom Seen 15 Fed #1					
Well Position	+N/-S	0.0 usft	Northing:	408,993.20 usft	Latitude:	32° 7' 27.795 N
	+E/-W	0.0 usft	Easting:	559,652.50 usft	Longitude:	104° 16' 27.013 W
Position Uncertainty	0.0 usft		Wellhead Elevation:		Ground Level:	0.0 usft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination	Dip Angle	Field Strength
	IGRF200510	2010/02/15	(°)	(°)	(nT)
			8.05	60.02	48,667

Design	Plan #1			
Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W	Direction
	(usft)	(usft)	(usft)	(°)
	0.0	0.0	0.0	279.14

Plan Sections										
Measured	Inclination	Azimuth	Vertical	+N/-S	+E/-W	Dogleg	Build	Turn	TFO	Target
Depth	(°)	(°)	Depth	(usft)	(usft)	Rate	Rate	Rate	(°)	
(usft)			(usft)			(°/100ft)	(°/100ft)	(°/100ft)		
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
9,340.0	0.00	0.00	9,340.0	0.0	0.0	0.00	0.00	0.00	0.00	
9,797.5	91.50	279.14	9,626.4	46.7	-290.2	20.00	20.00	0.00	279.14	
13,543.0	91.50	279.14	9,528.3	641.5	-3,986.9	0.00	0.00	0.00	0.00	Seldom Seen #1 PI

Great White Directional Services

Planning Report

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well Seldom Seen 15 Fed #1
Company:	Cimarex Energy Co.	TVD Reference:	WELL @ 0.0usft (Original Well Elev)
Project:	Eddy County (NM83E)	MD Reference:	WELL @ 0.0usft (Original Well Elev)
Site:	Sec.15 - T25S - R26E	North Reference:	Grid
Well:	Seldom Seen 15 Fed #1	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Plan #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	
9,340.0	0.00	0.00	9,340.0	0.0	0.0	0.0	0.00	0.00	0.00	
KOP: 20°/100 DLS, 279.14° AZI										
9,350.0	2.00	279.14	9,350.0	0.0	-0.2	0.2	20.00	20.00	0.00	
9,375.0	7.00	279.14	9,374.9	0.3	-2.1	2.1	20.00	20.00	0.00	
9,400.0	12.00	279.14	9,399.6	1.0	-6.2	6.3	20.00	20.00	0.00	
9,425.0	17.00	279.14	9,423.8	2.0	-12.4	12.5	20.00	20.00	0.00	
9,450.0	22.00	279.14	9,447.3	3.3	-20.6	20.9	20.00	20.00	0.00	
9,475.0	27.00	279.14	9,470.1	5.0	-30.8	31.2	20.00	20.00	0.00	
9,500.0	32.00	279.14	9,491.8	6.9	-43.0	43.5	20.00	20.00	0.00	
9,525.0	37.00	279.14	9,512.4	9.2	-57.0	57.7	20.00	20.00	0.00	
9,550.0	42.00	279.14	9,531.7	11.7	-72.6	73.6	20.00	20.00	0.00	
9,575.0	47.00	279.14	9,549.5	14.5	-89.9	91.1	20.00	20.00	0.00	
9,600.0	52.00	279.14	9,565.7	17.5	-108.7	110.1	20.00	20.00	0.00	
9,625.0	57.00	279.14	9,580.3	20.7	-128.8	130.5	20.00	20.00	0.00	
9,650.0	62.00	279.14	9,592.9	24.1	-150.1	152.0	20.00	20.00	0.00	
9,675.0	67.00	279.14	9,603.7	27.7	-172.3	174.5	20.00	20.00	0.00	
9,700.0	72.00	279.14	9,612.5	31.4	-195.4	198.0	20.00	20.00	0.00	
9,725.0	77.00	279.14	9,619.1	35.3	-219.2	222.0	20.00	20.00	0.00	
9,750.0	82.00	279.14	9,623.7	39.2	-243.5	246.6	20.00	20.00	0.00	
9,775.0	87.00	279.14	9,626.1	43.1	-268.0	271.5	20.00	20.00	0.00	
9,797.5	91.50	279.14	9,626.4	46.7	-290.2	294.0	20.00	20.00	0.00	
EOC - Hold to TD										
9,800.0	91.50	279.14	9,626.3	47.1	-292.7	296.5	0.00	0.00	0.00	
9,900.0	91.50	279.14	9,623.7	63.0	-391.4	396.4	0.00	0.00	0.00	
10,000.0	91.50	279.14	9,621.1	78.9	-490.1	496.4	0.00	0.00	0.00	
10,100.0	91.50	279.14	9,618.5	94.7	-588.8	596.4	0.00	0.00	0.00	
10,200.0	91.50	279.14	9,615.8	110.6	-687.5	696.3	0.00	0.00	0.00	
10,300.0	91.50	279.14	9,613.2	126.5	-786.2	796.3	0.00	0.00	0.00	
10,400.0	91.50	279.14	9,610.6	142.4	-884.9	896.3	0.00	0.00	0.00	
10,500.0	91.50	279.14	9,608.0	158.2	-983.6	996.2	0.00	0.00	0.00	
10,600.0	91.50	279.14	9,605.4	174.1	-1,082.3	1,096.2	0.00	0.00	0.00	
10,700.0	91.50	279.14	9,602.8	190.0	-1,181.0	1,196.2	0.00	0.00	0.00	
10,800.0	91.50	279.14	9,600.1	205.9	-1,279.7	1,296.1	0.00	0.00	0.00	
10,900.0	91.50	279.14	9,597.5	221.8	-1,378.4	1,396.1	0.00	0.00	0.00	
11,000.0	91.50	279.14	9,594.9	237.6	-1,477.1	1,496.1	0.00	0.00	0.00	
11,100.0	91.50	279.14	9,592.3	253.5	-1,575.8	1,596.0	0.00	0.00	0.00	
11,200.0	91.50	279.14	9,589.7	269.4	-1,674.5	1,696.0	0.00	0.00	0.00	
11,300.0	91.50	279.14	9,587.0	285.3	-1,773.2	1,796.0	0.00	0.00	0.00	
11,400.0	91.50	279.14	9,584.4	301.2	-1,871.9	1,895.9	0.00	0.00	0.00	
11,500.0	91.50	279.14	9,581.8	317.0	-1,970.6	1,995.9	0.00	0.00	0.00	
11,600.0	91.50	279.14	9,579.2	332.9	-2,069.2	2,095.9	0.00	0.00	0.00	
11,700.0	91.50	279.14	9,576.6	348.8	-2,167.9	2,195.8	0.00	0.00	0.00	
11,800.0	91.50	279.14	9,574.0	364.7	-2,266.6	2,295.8	0.00	0.00	0.00	
11,900.0	91.50	279.14	9,571.3	380.6	-2,365.3	2,395.8	0.00	0.00	0.00	
12,000.0	91.50	279.14	9,568.7	396.4	-2,464.0	2,495.7	0.00	0.00	0.00	
12,100.0	91.50	279.14	9,566.1	412.3	-2,562.7	2,595.7	0.00	0.00	0.00	
12,200.0	91.50	279.14	9,563.5	428.2	-2,661.4	2,695.7	0.00	0.00	0.00	
12,300.0	91.50	279.14	9,560.9	444.1	-2,760.1	2,795.6	0.00	0.00	0.00	
12,400.0	91.50	279.14	9,558.3	460.0	-2,858.8	2,895.6	0.00	0.00	0.00	
12,500.0	91.50	279.14	9,555.6	475.8	-2,957.5	2,995.6	0.00	0.00	0.00	
12,600.0	91.50	279.14	9,553.0	491.7	-3,056.2	3,095.5	0.00	0.00	0.00	
12,700.0	91.50	279.14	9,550.4	507.6	-3,154.9	3,195.5	0.00	0.00	0.00	
12,800.0	91.50	279.14	9,547.8	523.5	-3,253.6	3,295.4	0.00	0.00	0.00	

Great White Directional Services

Planning Report

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well Seldom Seen 15 Fed #1
Company:	Cimarex Energy Co.	TVD Reference:	WELL @ 0.0usft (Original Well Elev)
Project:	Eddy County (NM83E)	MD Reference:	WELL @ 0.0usft (Original Well Elev)
Site:	Sec 15 - T25S - R26E	North Reference:	Grid
Well:	Seldom Seen 15 Fed #1	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Plan #1		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
12,900.0	91.50	279.14	9,545.2	539.4	-3,352.3	3,395.4	0.00	0.00	0.00
13,000.0	91.50	279.14	9,542.5	555.2	-3,451.0	3,495.4	0.00	0.00	0.00
13,100.0	91.50	279.14	9,539.9	571.1	-3,549.7	3,595.3	0.00	0.00	0.00
13,200.0	91.50	279.14	9,537.3	587.0	-3,648.4	3,695.3	0.00	0.00	0.00
13,300.0	91.50	279.14	9,534.7	602.9	-3,747.1	3,795.3	0.00	0.00	0.00
13,400.0	91.50	279.14	9,532.1	618.7	-3,845.8	3,895.2	0.00	0.00	0.00
13,500.0	91.50	279.14	9,529.5	634.6	-3,944.5	3,995.2	0.00	0.00	0.00
13,543.0	91.50	279.14	9,528.3	641.5	-3,986.9	4,038.2	0.00	0.00	0.00

TD at 13543.0 - Seldom Seen #1 PBHL

Design Targets

Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
- hit/miss target									
- Shape									
Seldom Seen #1 PBH	0.00	0.00	9,527.0	641.7	-3,986.9	409,634.95	555,665.62	32° 7' 34.165 N	104° 17' 13.374 W
- plan misses target center by 1.4usft at 13543.0usft MD (9528.3 TVD, 641.5 N, -3986.9 E)									
- Point									

Plan Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
9,340.0	9,340.0	0.0	0.0	KOp 20°/100 DLS, 279.14° AZI
9,797.5	9,626.4	46.7	-290.2	EOC - Hold to TD
13,543.0	9,528.3	641.5	-3,986.9	TD at 13543.0

Cimarex Energy Co.

Project: Eddy County (NM33E)
 Site: Sec 15 - T29S - R66E
 Well: Seldom Seen 15 Fed #1
 Wellbore: Wellbore #1
 Design: Plan #1

WELL DETAILS: Seldom Seen 15 Fed #1



+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
0.0	0.0	408993.20	559652.50	32° 7' 27.795 N	104° 16' 27.013 W
SHL: 375' FSL / 330' FWL					
BHL: 330' FSL / 330' FEL					



Azimuths to Grid North
 True North: -0.03°
 Magnetic North: 8.01°
 Magnetic Field
 Strength: 48666.5nT
 Dip Angle: 60.02°
 Date: 2010/02/15
 Model: IGRF200510

WELLBORE TARGET DETAILS



Name	TVD	+N/-S	+E/-W	Northing	Easting
Seldom Seen #1 PBHL	9527.0	641.7	-3986.9	409634.95	555665.61

PLAN DETAILS


MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSec	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
9340.0	0.00	0.00	9340.0	0.0	0.0	0.00	0.00	0.0	
9797.5	91.50	279.14	9626.4	46.7	-290.2	20.00	279.14	294.0	
13543.0	91.50	279.14	9528.3	641.5	-3986.9	0.00	0.00	4038.2	Seldom Seen #1 PBHL

ANNOTATIONS

TVD	MD	Inc	Azi	+N/-S	+E/-W	VSec	Departure	Annotation
9340.0	9340.0	0.00	0.00	0.0	0.0	0.0	0.0	KOp 20°/100 DLS, 279.14° AZI
9626.4	9797.5	91.50	279.14	46.7	-290.2	294.0	294.0	EOC - Hold to TD
9528.3	13543.0	91.50	279.14	641.5	-3986.9	4038.2	4038.2	TD at 13543.0



Key Rig 880







-  Wind Direction Indicators
(wind sock or streamers)
-  H2S Monitors
(alarms at bell nipple and shale shaker)
-  Briefing Areas
-  Remote BOP Closing Unit

Exhibit D – Rig Diagram
Seldom Seen 15 Federal No. 1
 Cimarex Energy Co. of Colorado
 15-25S-26E
 660 FSL & 660 FEL
 Eddy County, NM

SR & A




Exhibit E – 5000# BOP

Seldom Seen 15 Federal No. 1

Cimarex Energy Co. of Colorado


15-25S-26E

660 FSL & 660 FEL

Eddy County, NM

Drilling Operations
Choke Manifold
5M Service (tested to 3M)

Exhibit E-1 – Choke Manifold Diagram
Seldom Seen 15 Federal No. 1
Cimarex Energy Co. of Colorado
15-25S-26E
660 FSL & 660 FEL
Eddy County, NM





Cimarex Energy Co. of Colorado

600 N. Marienfeld St. ♦ Suite 400 ♦ Midland, TX 79701 ♦ (432) 571-7800 ♦ Fax (432) 620-1940
A subsidiary of Cimarex Energy Co • A NYSE Listed Company • "XEC"

January 20, 2010

Oil Conservation Division
District II Office
1301 W. Grand Ave.
Artesia, New Mexico 88210
Attn: Ms. Linda Bratcher

Re: Statewide Rule 118
Hydrogen Sulfide Gas Contingency Plan
Proposed Seldom Seen 15 Federal No. 1 Well

Dear Ms. Bratcher:

In accordance with NMAC 19.15.3.118 C. (1) governing the determination of the hydrogen sulfide concentration in gaseous mixtures in each of its operations, Cimarex Energy Co. of Colorado does not anticipate that there will be enough H₂S from the surface to the Morrow formations to meet the OCD's minimum requirements for the submission of a contingency plan for the drilling and completion of the following test(s):

Seldom Seen 15 Federal No. 1
15-25S-26E
660 FSL & 660 FEL
Eddy County, NM

If anything further is needed regarding this issue, or if you have any questions, please feel free to contact the undersigned at 432-620-1938.

Yours truly,

Zeno Farris
Manager Operations Administration

RECEIVED
JAN 21 2010
12:21 PM
DISTRICT II
OFFICE

Hydrogen Sulfide Drilling Operations Plan
Seldom Seen 15 Federal No. 1
Cimarex Energy Co. of Colorado
Unit Letter P, Section 15
T25S-R26E, Eddy County, NM

H₂S equipment will be rigged up at Surface. The plan should be implemented before drilling out from the surface.

1. Due to a one-time encounter on a previous well, an Intra-salt Pocket was charged with H₂S and a burnable amount of hydrocarbons.

First Potential Problem Zone:

Initial suspected problem zone	Salt Zone @ 1,333'
Potential Open Flow Capacity	1 mcf
Expected H ₂ S Concentration	11,000 ppm
100' ROE	6'
500' ROE	3'

Cimarex will have 24-hour H₂S Safety Supervisors on location while drilling the first 2,000' on this well.

2. Second Potential Problem Zone:

Initial suspected problem zone	Delaware Mountain Group @ 1,800'
Potential Open Flow Capacity	100 mcf
Expected H ₂ S Concentration	1,000 ppm
100' ROE	24'
500' ROE	11'

3. All Company and Contract personnel admitted on location must be trained by a qualified H₂S safety instructor to the following:

- A. Characteristics of H₂S
- B. Physical effects and hazards
- C. Proper use of safety equipment and life support systems.
- D. Principle and operation of H₂S detectors, warning system and briefing areas.
- E. Evacuation procedure, routes and first aid.
- F. Proper use of 30 minute pressure demand air pack.

4. H₂S Detection and Alarm Systems:

- A. H₂S detectors and audio alarm system to be located at bell nipple, end of flow line (mud pit) and on derrick floor or doghouse.

5. Windsock and/or wind streamers:

- A. Windsock at mudpit area should be high enough to be visible.
- B. Windsock at briefing area should be high enough to be visible.

6. Condition Flags and Signs:

- A. Warning sign on access road to location.
- B. Flags to be displayed on sign at entrance to location. Green flag indicates normal safe condition. Yellow flag indicates potential pressure and danger. Red flag indicates danger (H₂S present in dangerous concentration). Only emergency personnel admitted to location.

Hydrogen Sulfide Drilling Operations Plan
Seldom Seen 15 Federal No. 1
Cimarex Energy Co. of Colorado
Unit Letter P, Section 15
T25S-R26E, Eddy County, NM

7. Well control equipment:

A. See exhibit "E"

8. Communication:

- A. While working under masks chalkboards will be used for communication.
- B. Hand signals will be used where chalk board is inappropriate.
- C. Two way radio will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at most drilling foreman's trailer or living quarters.

9. Drillstem Testing:

No DSTs are planned at this time.

- 10. Drilling contractor supervisor will be required to be familiar with the effects H₂S has on tubular goods and other mechanical equipment.
- 11. If H₂S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H₂S scavengers if necessary.

Emergency Procedures

In the event of a release of gas containing H₂S, the first responder(s) must:

- ★ Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- ★ Evacuate any public places encompassed by the 100 ppm ROE.
- ★ Be equipped with H₂S monitors and air packs in order to control the release.
- ★ Use the "buddy system" to ensure no injuries occur during the response.
- ★ Take precautions to avoid personal injury during this operation.
- ★ Contact operator and/or local officials to aid in operation. See list of phone numbers attached.
- ★ Have received training in the:
 - ◆ Detection of H₂S, and
 - ◆ Measures for protection against the gas,
 - ◆ Equipment used for protection and emergency response.

Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO₂). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally, the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas.

Characteristics of H₂S and SO₂

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H ₂ S	1.189 Air=1	10 ppm	100 ppm/hr	600 ppm
Sulfur Dioxide	SO ₂	2.21 Air=1	2 ppm	N/A	1000 ppm

Contacting Authorities

Cimarex Energy Co. of Colorado's personnel must liaise with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available including directions to site. The following call list of essential and potential responders has been prepared for use during a release. Cimarex Energy Co. of Colorado's response must be in coordination with the State of New Mexico's "Hazardous Materials Emergency Response Plan" (HMER).

H₂S Contingency Plan Emergency Contacts

Seldom Seen 15 Federal No. 1

Cimarex Energy Co. of Colorado

Unit Letter P, Section 15

T25S-R26E, Eddy County, NM

Company Office

Cimarex Energy Co. of Colorado	800-969-4789
Co. Office and After-Hours Menu	

Key Personnel

Name	Title	Office	Mobile
Doug Park	Drilling Manager	432-620-1934	972-333-1407
Dee Smith	Drilling Super	432-620-1933	972-882-1010
Jim Evans	Drilling Super	432-620-1929	972-465-0564
Roy Shirley	Field Super		432-634-2136

Artesia

Ambulance	911
State Police	575-746-2703
City Police	575-746-2703
Sheriff's Office	575-746-9888
Fire Department	575-746-2701
Local Emergency Planning Committee	575-746-2122
New Mexico Oil Conservation Division	575-748-1283

Carlsbad

Ambulance	911
State Police	575-885-3137
City Police	575-885-2111
Sheriff's Office	575-887-7551
Fire Department	575-887-3798
Local Emergency Planning Committee	575-887-6544
US Bureau of Land Management	575-887-6544

Santa Fe

New Mexico Emergency Response Commission (Santa Fe)	505-476-9600
New Mexico Emergency Response Commission (Santa Fe) 24 Hrs	505-827-9126
New Mexico State Emergency Operations Center	505-476-9635

National

National Emergency Response Center (Washington, D.C.)	800-424-8802
---	--------------

Medical

Flight for Life - 4000 24th St.; Lubbock, TX	806-743-9911
Aerocare - R3, Box 49F; Lubbock, TX	806-747-8923
Med Flight Air Amb - 2301 Yale Blvd S.E., #D3; Albuquerque, NM	505-842-4433
SB Air Med Service - 2505 Clark Carr Loop S.E.; Albuquerque, NM	505-842-4949

Other

Boots & Coots IWC	800-256-9688	or	281-931-8884
Cudd Pressure Control	432-699-0139	or	432-563-3356
Halliburton	575-746-2757		
B.J. Services	575-746-3569		

Surface Use Plan
Seldom Seen 15 Federal No. 1
Cimarex Energy Co. of Colorado
Unit Letter P, Section 15
T25S-R26E, Eddy County, NM

1. Existing Roads: Area maps, Exhibit "B" is a reproduction of Eddy Co. General Highway Map. Exhibit "C" is a reproduction of a USGS Topographic Map, showing existing roads and proposed roads. All existing roads will be maintained in a condition equal to or better than current conditions. Any new roads will be constructed to BLM specifications.
 - A. Exhibit "A" shows the proposed well site as staked.
 - B. From the junction of Means Rd and Prickly Pear, go East turning Southerly on Prickly Pear for 3.7 miles to proposed lease road.
2. Planned Access Roads: 1004.1' of new, on-lease access road will be constructed.
3. Location of Existing Wells in a One-Mile Radius - Exhibit A
 - A. Water wells - None known
 - B. Disposal wells - None known
 - C. Drilling wells - None known
 - D. Producing wells - As shown on Exhibit "A"
 - E. Abandoned wells - As shown on Exhibit "A"
4. If on completion this well is a producer, Cimarex Energy Co. of Colorado will furnish maps and/or plats showing on site facilities or off site facilities if needed. This will be accompanied by a Sundry Notice.
5. Location and Type of Water Supply:

Water will be purchased locally from a commercial source and trucked over the access roads or piped in flexible lines laid on top of the ground.
6. Source of Construction Material:

If possible, construction will be obtained from the excavation of drill site. If additional material is needed, it will be purchased from a local source and transported over the access route as shown on Exhibit "C".
7. Methods of Handling Waste Material:
 - A. Drill cuttings will be separated by a series of solids removal equipment and stored in steel containment pits and then hauled to a state-approved disposal facility.
 - B. All trash, junk and other waste material will be contained in trash cages or bins to prevent scattering. When the job is completed all contents will be removed and disposed of in an approved sanitary land fill.
 - C. Salts remaining after completion of well will be picked up by supplier including broken sacks.
 - D. Sewage from living quarters will drain into holding tanks and be cleaned out periodically. A Porta-John will be provided for the rig crews. This equipment will be properly maintained during the drilling operations and removed upon completion of the well.
 - E. Drilling fluids will be contained in steel pits in a closed circulating system. Fluids will be cleaned and reused. Water produced during testing will be contained in the steel pits and disposed of at a state approved disposal facility. Any oil or condensate produced will be stored in test tanks until sold and hauled from the site.

Surface Use Plan
Seldom Seen 15 Federal No. 1
Cimarex Energy Co. of Colorado
Unit Letter P, Section 15
T25S-R26E, Eddy County, NM

8. Ancillary Facilities:

- A. No camps or airstrips to be constructed.

9. Well Site Layout:

- A. Exhibit "D" shows location and rig layout.
- C. Mud pits in the closed circulating system will be steel pits and the cuttings will be stored in steel containment pits.
- D. Cuttings will be stored in steel pits until they are hauled to a state-approved disposal facility.
- E. If the well is a producer, those areas of the location not essential to production facilities will be reclaimed and seeded per BLM requirements.

10. Plans for Restoration of Surface:

Rehabilitation of the location will start in a timely manner after all drilling operations cease. The type of reclamation will depend on whether the well is a producer or a dry hole.

Drainage systems, if any, will be reshaped to the original configuration with provisions made to alleviate erosion. These may need to be modified in certain circumstances to prevent inundation of the location's pad and surface facilities. After the area has been shaped and contoured, topsoil from the spoil pile will be placed over the disturbed area to the extent possible. Revegetation procedures will comply with BLM standards.

If the well is a dry hole, the pad and road area will be recountoured to match the existing terrain. Topsoil will be spread to the extent possible. Revegetation will comply with BLM standards.

Should the well be a producer, the previously noted procedures will apply to those areas which are not required for production facilities.

11. Other Information

- A. Topography consists of a sloping plane with loose tan sands. Vegetation is mainly yucca, mesquite and shin oak.
- B. The wellsite is on surface owned by Department of the Interior, Bureau of Land Management. The land is used mainly for farming, cattle ranching, recreational use, and oil and gas production.
- C. An Archaeological survey will be conducted on the location and proposed roads, and this report will be filed with the Bureau of Land Management in the Carlsbad BLM office.
- D. There are no known dwellings within 1½ miles of this location.

Operator Certification Statement
Seldom Seen 15 Federal No. 1
Cimarex Energy Co. of Colorado
Unit Letter P, Section 15
T25S-R26E, Eddy County, NM

Operator's Representative

Cimarex Energy Co. of Colorado
600 N. Marienfeld St., Ste. 600
Midland, TX 79701
Office Phone: (432) 620-1938
Zeno Farris

CERTIFICATION: I hereby certify that the statements and plans made in this APD are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by Cimarex Energy Co. of Colorado and/or its contractors/subcontractors and is in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provision of U.S.C. 1001 for the filing of a false statement.

NAME: Zeno Farris
Zeno Farris
DATE: January 20, 2010
TITLE: Manager Operations Administration

PECOS DISTRICT CONDITIONS OF APPROVAL

OPERATOR'S NAME:	Cimarex Energy Co of Colo
LEASE NO.:	NM19423
WELL NAME & NO.:	1 Seldom Seen 15 Federal
SURFACE HOLE FOOTAGE:	660' FSL & 660' FEL
BOTTOM HOLE FOOTAGE:	1250' FSL & 660' FWL
LOCATION:	Section 15, T. 25 S., R 26 E., NMPM
COUNTY:	Eddy County, New Mexico

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- ☐ **General Provisions**
- ☐ **Permit Expiration**
- ☐ **Archaeology, Paleontology, and Historical Sites**
- ☐ **Noxious Weeds**
- ☒ **Special Requirements**
 - Cave/Karst
- ☐ **Construction**
 - Notification
 - V-Door Direction
 - Topsoil
 - Closed Loop System
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- ☐ **Road Section Diagram**
- ☒ **Drilling**
 - Critical cave/karst
 - H2S – Onshore Order 6 requirements
 - Logging Requirements
- ☐ **Production (Post Drilling)**
 - Well Structures & Facilities
 - Pipelines
 - Electric Lines
- ☒ **Interim Reclamation**
- ☒ **Final Abandonment & Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5972 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. V-DOOR DIRECTION: East

C. TOPSOIL

The operator shall stockpile the topsoil in a low profile manner in order to prevent wind/water erosion of the topsoil. The topsoil will be used for interim and final reclamation.

D. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

E. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

F. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation.

The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

G. ON LEASE ACCESS ROADS

Road Width

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed thirty (30) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning


Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts

Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall be constructed on all blind curves. Turnouts shall conform to the following diagram:




Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outslowing and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

Culvert Installations

Appropriately sized culvert(s) shall be installed at the deep waterway channel flow crossing.

Cattleguards

An appropriately sized cattleguard(s) sufficient to carry out the project shall be installed and maintained at fence crossing(s).

Any existing cattleguard(s) on the access road shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattleguard(s) that are in place and are utilized during lease operations.

A gate shall be constructed and fastened securely to H-braces.

Fence Requirement


Where entry is required across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting.

The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fence(s).

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Figure 1 – Cross Sections and Plans For Typical Road Sections



VII. DRILLING

A. DRILLING OPERATIONS REQUIREMENTS

The BLM is to be notified a minimum of 4 hours in advance for a representative to witness:

- a. Spudding well
- b. Setting and/or Cementing of all casing strings
- c. BOPE tests

☒ **Eddy County**

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

1. A Hydrogen Sulfide (H₂S) Drilling Plan should be activated 500 feet prior to drilling into the **Delaware** formation. **As a result, the Hydrogen Sulfide area must meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, please provide measured values and formations to the BLM.**
2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
3. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works is located, this does not include the dog house or stairway area.
4. **The record of the drilling rate along with the CAL/GR/N well log run from TD to surface will be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top (if present) and top and bottom of Salt are to be recorded on the Completion Report.**

B. CASING

Changes to the approved APD casing and cement program require submitting a sundry and receiving approval prior to work. Failure to obtain approval prior to work will result in an Incident of Non-Compliance being issued.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

Wait on cement (WOC) time for a primary cement job will be a minimum 18 hours for a water basin, 24 hours in the potash area, or 500 pounds compressive strength, whichever is greater for all casing strings. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. See individual casing strings for details regarding lead cement slurry requirements.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

Possible lost circulation in the Delaware Group.

Possible high pressures in the Wolfcamp and Pennsylvanian Sections (pilot hole).

CRITICAL CAVE/KARST – ALL THREE CASING STRINGS ARE TO BE CEMENTED TO SURFACE IN CRITICAL CAVE/KARST AREAS. THE CEMENT MUST BE IN A SOLID SHEATH THEREFORE, ONE INCH OPERATIONS WILL NOT BE PERMITTED. IF LOST CIRCULATION OCCURS ON ANY STRING, OPERATOR IS TO CONTACT BLM ENGINEER PRIOR TO RUNNING CASING AS A DV TOOL MAY BE REQUIRED.

1. The 13-3/8 inch surface casing shall be set **below useable water and above the Salt at approximately 450 feet** and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.**
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Formation below the 13-3/8" shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe (not the mud weight required to prevent dissolving the salt formation) and the mud weight for the bottom of the hole. Report results to BLM office.

2. The minimum required fill of cement behind the 9-5/8 inch intermediate casing is:
Casing to be set at approximately 1910 feet within the Lamar Limestone.

☒ Cement to surface. If cement does not circulate see B.1.a, c-d above. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst.**

~~Formation below the 9-5/8" shoe to be tested according to Onshore Order 2.III.B.1.i.~~
Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe (not the mud weight required to prevent dissolving the salt formation) and the mud weight for the bottom of the hole. Report results to BLM office.

3. The minimum required fill of cement behind the 7 inch production casing is:

☒ Cement to surface. If cement does not circulate, contact the appropriate BLM office. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst.**

Formation below the 7" shoe to be tested according to Onshore Order 2.III.B.1.i.
Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe (not the mud weight required to prevent dissolving the salt formation) and the mud weight for the bottom of the hole. Report results to BLM office.

4. The minimum required fill of cement behind the 4-1/2 inch production liner is:

☒ Cement not required, operator is using the PEAK completion assembly.
Liner should tie-back at least 200 feet into previous casing string.

5. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

C. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.

2. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M) psi. 5M system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.**
3. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. Casing cut-off and BOP installation will not be initiated until the cement has had 4-6 hours of setup time in a water basin and 12 hours in the potash areas. This time will start after the cement plug is bumped. Testing the BOP/BOPE against a plug can commence after meeting the above conditions plus the BOP installation time.
 - b. The tests shall be done by an independent service company using a test plug.
 - c. The results of the test shall be reported to the appropriate BLM office.
 - d. All tests are required to be recorded on a calibrated test chart. **A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.**
 - e. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug.
 - f. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the **Wolfcamp** formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

D. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the **Wolfcamp** formation, and shall be used until production casing is run and cemented.

Proposed mud weight may not be adequate for drilling through Wolfcamp.

E. DRILL STEM TEST

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

RGH 021710

VIII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Containment Structures

The containment structure shall be constructed to hold the capacity of the entire contents of the largest tank, plus 24 hour production, unless more stringent protective requirements are deemed necessary by the Authorized Officer.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color Shale Green, Munsell Soil Color Chart # 5Y 4/2

B. PIPELINES

Not applied for in APD

C. ELECTRIC LINES

Not applied for in APD

IX. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

X. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared; these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Seed Mixture 1, for Loamy Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed will be either certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (small/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

<u>Species</u>	<u>lb/acre</u>
Plains lovegrass (<i>Eragrostis intermedia</i>)	0.5
Sand dropseed (<i>Sporobolus cryptandrus</i>)	1.0
Sideoats grama (<i>Bouteloua curtipendula</i>)	5.0

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed