

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources


Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-37490
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Wyatt Draw 24 L
8. Well Number 1
9. OGRID Number 14744
10. Pool name or Wildcat Undesignated Yeso

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>
2. Name of Operator Mewbourne Oil Company
3. Address of Operator PO Box 5270 Hobbs, NM 88241
4. Well Location Unit Letter <u>L</u> : 2310 feet from the <u>South</u> line and <u>330</u> feet from the <u>West</u> line Section <u>24</u> Township <u>19S</u> Range <u>25E</u> NMPM Eddy County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3411'



12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/13/10... MI & spud 11" hole. Ran 833' 8 5/8" 24# J55 ST&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed @ 14.6 #/g w/1.52 yd. Tail with 400 sks Class C with additives. Mixed @ 14.8 /g w/1.34 yd. Plug down @ 12:30 pm 03/14/10. Did not circ cmt. Slow rate lift pressure @ 80# @ 2.7 BPM. WOC. Ran temp survey indication TOC @ 274'. RIH with 1" pipe. Tag at 227'. Ran 1" pipe in 2 stages with 99 sks Thixad Class H with additives. Mixed @ 14.8 #/g w/ 1.34 yd. Circ 8 sks to pit. WOC 18 hrs. At 4:30 pm 03/15/10 tested casing & BOPE to 1500# for 30 minutes, held OK. Drilled out with 7 7/8" bit.

03/20/10 TD'ed 7 7/8" hole @ 4300'. Ran 4300' 4 1/2" 11.6# J55 LT&C csg. Cemented w/325 sks BJ Lite Class C (50:50:10) with additives. Mixed @ 11.8/g w/2.45 yd. Tail with 400 sks Class C with additives. Mixed @ 14.8/g w/1.33 yd. Plug down @ 9:30 pm 03/21/10. At 9:30 pm 03/21/10, tested csg to 1750# for 30 mins, held OK. Set wellhead slips w/45k.

03/22/10...Released rig at 4:30 am.

Spud Date: 03/13/10

Rig Release Date: 03/22/10

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 03/26/10

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: David Day TITLE Field Supervisor DATE 3-29-2010

Conditions of Approval (if any):