

9 Submit To Appropriate District Office
Two Copies
District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources



Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-105
July 17, 2008

1. WELL API NO.

30-015-37593

2 Type of Lease

☒ STATE ☐ FEE ☐ FED/INDIAN

3 State Oil & Gas Lease No

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

4 Reason for filing

☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Federal wells only)

☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33, attach this and the plat to the C-144 closure report in accordance with 19 NMS 17 13 K NMAC)

7 Type of Completion.

☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER

8 Name of Operator

Marbob Energy Corporation

10 Address of Operator

P.O Box 227

Artesia, NM 88211-0227

5 Lease Name or Unit Agreement Name
N B Tween State

6 Well Number

13

9. OGRID

14049

11 Pool name or Wildcat

Artesia; Glorieta-Yeso (O)

12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	C	25	17S	28E	C	800	North	1550	West	Eddy
Bit:	C	25	17S	28E	C	800	North	1650	West	Eddy

13 Date Spudded 3/16/10 14 Date T D Reached 3/22/10 15 Date Rig Released 3/24/10 16 Date Completed (Ready to Produce) 4/17/10 17 Elevations (DF and RKB, RT, GR, etc) 3682' GR

18 Total Measured Depth of Well 5600' 19 Plug Back Measured Depth 5576' 20 Was Directional Survey Made? No 21. Type Electric and Other Logs Run DSN, DLL

22 Producing Interval(s), of this completion - Top, Bottom, Name
3714-4962' Yeso

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB /FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	350'	12 1/4"	350 sx	0
5 1/2"	17#	5598'	7 7/8"	1300 sx	0

24 LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25 TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2 7/8"	4663'	

26 Perforation record (interval, size, and number)

4705', 11', 20', 28', 38', 46', 55', 78', 97', 4808', 14', 20', 34', 48', 65', 97', 4940', 48', 56', 62' (20)

4298', 4309', 24', 56', 82', 4400', 10', 25', 41', 64', 90', 4504', 11', 41', 48', 63', 75', 92', 98', 4604' (20)

3714', 53', 59', 65', 71', 92', 3800', 14', 27', 37', 54', 64', 71', 85', 3902', 12', 20', 26', 38', 44', 51', 58', 76', 4011' (25)

27 ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC

DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED

4705-4962' Acdz w/2000 gal 15% NEFE; Frac w/82980 gal Wtr Frac G, 33444 gal 20% HCL, 5097 gal 15% NEFE & 4881 gal fresh wtr

4298-4604' Acdz w/2000 gal 15% NEFE; Frac w/90 bbls 20% Frac G-R & 67.5 bbls 20% HCL

3714-4011' Acdz w/2500 gal 15% NEFE; Frac w/45612 gal 20% HCL & 6714 gal Wtr Frac G

PRODUCTION

Date First Production 4/18/10		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping				Well Status (Prod. or Shut-in) Producing	
Date of Test 4/20/10	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 29	Gas - MCF 32	Water - Bbl 943	Gas - Oil Ratio
Flow Tubing Press	Casing Pressure	Calculated 24- Hour Rate	Oil - Bbl	Gas - MCF	Water - Bbl	Oil Gravity - API - (Corr)	

29 Disposition of Gas (Sold, used for fuel, vented, etc)
Sold

30 Test Witnessed By
Tommy Willyard

31 List Attachments
Logs & Inclination Report

32 If a temporary pit was used at the well, attach a plat with the location of the temporary pit.

33. If an on-site burial was used at the well, report the exact location of the on-site burial:

Latitude

Longitude

NAD 1927 1983

I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature: Stormi Davis Printed: Stormi Davis Title: Production Assistant Date: 4/20/10

E-mail Address: sdavis@marbob.com

MR

completions, items 11, 12 and 26-31 shall be reported for each zone.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt 420'	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates 669'	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers 925'	T. Devonian	T. Cliff House	T. Leadville
T. Queen 1504'	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Tubb	T. Point Lookout	T. Elbert
T. San Andres 2181'	T. Simpson	T. Mancos	T. McCracken
T. Glorieta 3607'	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Rustler 366'	T. Morrison	
T. Drinkard	T. Bowers	T. Todilto	
T. Abo	T. Lovington	T. Entrada	
T. Wolfcamp	T. Yeso 3701'	T. Wingate	
T. Penn	T. Tubb 5234'	T. Chinle	
T. Cisco-Canyon	T. _____	T. Permian	

OIL OR GAS SANDS OR ZONES

No. 3, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology