Submit 3 Copies To Appropriate District Office	State of New Mexico			Form C-103 June 19, 2008		
<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources rench Dr., Hobbs, NM 88240			WELL API 1	WELL API NO. 30-015-37377	
<u>District II</u> 1301 W. Grand Ave, Artesia, NM 88210				5. Indicate T	vne of Lease	
District III 1220 South St. Francis Dr.			STAT			
District IV Santa Fe, NM 87505 1220 S. St Francis Dr., Santa Fe, NM 87505			6. State Oil 8	& Gas Lease No.		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)				Quick Draw 2	7. Lease Name or Unit Agreement Name Quick Draw 22 D	
1. Type of Well: Oil Well X Gas Well Other					8. Well Number 1	
2. Name of Operator Mewbourne Oil Company	RECEIVED		9. OGRID N 14744	umber		
3. Address of Operator PO Box 5270				10. Pool nam	!	
Hobbs, NM 88241		APR 2 9 2010		Cemetery Ye	so 11795	
4. Well Location Unit Letter D : 330 feet from the NMOCD ARTESIA 0 feet from the West line						
Section 22 Township 20S Range 25E NMPM Eddy County						
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3452'						
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data						
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:						
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORL					ALTERING CASING	
TEMPORARILY ABANDON				_		
DOWNHOLE COMMINGLE			0, (011 (0, 0211)		1	
OTHER:		П	OTHER:	Γ		
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.						
04/13/10MI & spud 11" hole. Ran 824' 8 %" 24# J55 ST&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed 14.6 #/g w/1.52 yd. Tail with 400 sks Class C with additives. Mixed @ 14.8 /g w/1.34 yd. Plug down @ 4:00 am 04/15/10. Did not circ cmt. Slow rate lift pressure @ 417# @ 3.2 BPM. WOC. Ran temp survey indication TOC @ 54'. RIH with 1" pipe. Tag at 96'. Ran 1" pipe in 15 stages with 250 sks Class C w/CACl2. Mixed @ 14.8 #/g w/1.34 yd. And 150 sks Thixad H w/additives. Mixed @ 14.6 #/g w/1.52 yd. Circ 8 sks to pit. WOC 18 hrs. At 7:45 am 04/17/10 tested BOPE & casing to 1500# for 30 minutes, held OK. Drilled out with 7 %" bit.						
04/19/10 TD'ed 7 %" hole @ 3200'. Ran 3200' 4 ½" 11.6# J55 LT&C csg. Cemented w/350 sks BJ Lite Class C (50:50:10) with additives. Mixed @ 11.8/g w/2.45 yd. Tail with 350 sks Class C with additives. Mixed @ 14.8/g w/1.33 yd. Plug down @ 5:15 am 04/20/10. At 5:45 pm 04/19/10, tested csg to 1500# for 30 mins, held OK. Set wellhead slips w/45k.						
04/20/10Released rig at 11:00 am.						
Spud Date: 04/13/10 Rig Release Date: 04/20/10						
I hereby certify that the information above is true and complete to the best of my knowledge and belief.						
SIGNATURE JOCKIE J	gthan_11	TLE _Hobbs	Regulatory		DATE_04/27/10	
Type or print name Tackie Lathan E-mail address: jlathan@mewbourne.comPHONE: 575-393-5905 For State Use Only						
APPROVED BY: Double & Conditions of Approval (if any):	hay Ti	rle Fie	ld Superv	isor	date 5-3-2010	