Form 3160-5 (August 2007)

## UNITED STATES DEPARTMENT OF THE INTERIOR

O	ORM APPROVED  THE PROPERTY OF
5 Lease Serial No LC-064488-	
6 If Indian, Allotte NA	Or Tribe Name  NMOCD ARTES
I	

BUREAU OF LAND MANAG	Ex fires fings 600 EIVEL		
SUNDRY NOTICES AND REPOR  Do not use this form for proposals to dril  abandoned well. Use Form 3160-3 (APD) f	5 Lease Serial Nd LC-064488- JUN 28 2010 6 If Indian, Allottee or Tribe Name NA NMOCD ARTES		
SUBMIT IN TRIPLICATE - Other instructions on page 2.		7 If Unit or CA/Agreement, Name and/or No.	
1 Type of Well		NA	
Oıl Well Gas Well X Other	8 Well Name and No		
2 Name of Operator	Ottawa AOW Federal #6		
Yates Petroleum Corporation	3b Phone No (include area code)	9. API Well No 30-015-29453	
<sup>3a</sup> Address 105 S. 4th Str., Artesia, NM 88210	575-748-1471	10 Field and Pool or Exploratory Area	
4 Location of Well (Footage, Sec., T, R, M, OR Survey Description)	0.074014.1	Dagger Draw; Upper Penn, North	
	11 County or Parish, State		
3 1980'FNL & 1730'FEL of Section 10-T19S-R25E (Unit G, SWNE)		Eddy County, New Mexico	
12. CHECK APPROPRIATE BOX(ES) TO	INDICATE NATURE OF NOTICE,	REPORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTIO	Ν	
Acidize	Deepen Product	ion (Start/Resume) Water Shut-Off	
Notice of Intent    Alter Casing	Fracture Treat Reclama	tion Well Integrity	
Casing Repair	New Construction Recomp	lete Other	
Subsequent Report Change Plans	X Plug and Abandon Tempor	anly Abandon	
Final Abandonment Notice Convert to Injection	n Plug Back Water D	nsposal	
testing has been completed. Final Abandonment Notices must be filed only aft determined that the site is ready for final inspection.	ı	npieted and the operator has	
6/1/10 NU BOP. Set a CIBP at 7627' with 35' cement on top 6/3/10 Spotted a 40 sx cement plug at 5711'. Did not tag plug. Tested casing to 1000 psi. Lost 800 psi in 8 min. Ran GR/JB to check CIBP at 7627', could not get past 7060'.			
6/4/10 Tagged up at 7084'. Tested casing to 1000 psi, held good. Pumped 40 sx Class "C" cement with 2% CaCl			
at 5711'. BLM wanted to tag plug. WOC 3-1/2 hrs. Tagged cement plug at 5518'. Pumped 25 sx Class "C"			
cement at 3807'. TOC at 3653'. Did not have to tag. Pumped 25 sx Class "C" cement at 2369'. TOC at 2215' Did not have to tag. Pumped 30 sx Class "C" cement at 1233'			
6/7/10 Tagged plug at 1038' (TOC). Spotted a 150' surface plug.			
6/8/10 Removed wellhead Installed dry hole m ABANDONED.			
Redomation Due 12-4-10	Liabi	pted as to plugging of the well bore. lity under bond is retained until	
14 I hereby certify that the foregoing is true and correct	Surfa	co restoration is completed.	
Name <i>(Printed/Typed)</i> Tina Hu <b>e</b> rta	Title Regulatory Com	oliance-Supervisor-	
Signature ( )	Date June 11, 2010	CCEPTED FOR RECORD	
	FOR FEDERAL OR STATE OFFICE USE		
Approved by	Title	JUNDat 9 2010	
Conditions of approval, if any, are attached. Approval of this notice docertify that the applicant holds legal or equitable title to those rights in which would entitle the applicant to conduct operations thereon.	es not warrant or	4 Como	
Title 18 U S C Section 1001 and Title 43 U S C Section 1212, make it a		ketto hy/department orladencylol the writebl States	
any false, fictitious or fraudulent statements or representations as to any	matter within its jurisdiction	CARLSBAD FIELD OFFICE	