

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N French Dr, Hobbs, NM 88240  
District II  
1301 W Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd, Aztec, NM 87410  
District IV  
1220 S. St Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
May 27, 2004

RM

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.  
30-015-37376

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Parkway State Com

8. Well Number

003

9. OGRID Number

162683

10. Pool name or Wildcat

Turkey Track; Bone Spring

RECEIVED

JUN 25 2010

NMOCD ARTESIA

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Cimarex Energy Co. of Colorado

3. Address of Operator

600 N. Marienfeld, Ste. 600; Midland, TX 79701

4. Well Location

SHL Unit Letter M : 330 feet from the South line and 330 feet from the West line  
Section 15 Township 19S Range 29E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3343' GR

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water

Pit Liner Thickness: Below-Grade Tank: Volume bbls: Construction Material

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS ☐ P AND A ☐  
CASING/CEMENT JOB ☒  
OTHER: ☐ Surface Casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12-15-09 Spudded 17 1/2" hole. Ran 13 3/8" 48# H-40 STC to 278'. Cemented with Lead 100 sx Thixotropic + 10# Cal-Seal + 10# Gilsonite + 1% CaCl<sub>2</sub> + 0.125# Poly-e-flake (wt 14.2, yld 1.63) and Tail 300 sx Halcem C + 2% CaCl<sub>2</sub> (wt 14.8, yld 1.35). Did not circulate. TS TOC 150'. One-inched @ 150' w/ 100 sx Prelum Plus + 3% CaCl<sub>2</sub> (wt 14.8, yld 1.35). One-inched @ 40' w/ 60 sx Premium Plus + 2% CaCl<sub>2</sub> (wt 14.8, yld 1.35). Circulated 3 bbls to surface. WOC 28 hours.

12-16-09 Pressure-tested surface casing to 1200 psi for 30 minutes.

12-18-09 Lost circulation. Pumped cement plug @ 317' w/ 150 sx Swift-Cem C + 10# Cal-Seal 60 + 1% CaCl<sub>2</sub> flake + 10# Poly-e-flake (wt 14.2, yld 1.63). No returns, tagged @ 299'. Pumped cement plug @ 284' w/ 150 sx Swift-cem C + 10# Cal-Seal 60 + 1% CaCl<sub>2</sub> flake + 10# Poly-e-flake (wt 14.2, yld 1.63). No returns, tagged @ 290'. Pumped cement plug @ 284' w/ 150 sx Swift-cem C + 10# Cal-Seal 60 + 1% CaCl<sub>2</sub> flake + 10# Poly-e-flake (wt 14.2, yld 1.63). Circulated to surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Natalie Krueger TITLE Regulatory Analyst DATE June 24, 2010

Type or print name Natalie Krueger email address: nkrueger@cimarex.com Telephone No. 432-620-1936

For State Use Only

APPROVED BY: David May TITLE Field Supervisor DATE 6-30-10  
Conditions of Approval (if any):