Submit 1 Copy To Appropriate District Office District I 1625 N. French Dr., Hobbs, NM 88240 State of New Mexico Energy, Minerals and Natural Resources		Form C-103 October 13, 2009 WELL API NO.
District III 1220 South	VATION DIVISION a St. Francis Dr. e, NM 87505	30-015-37860 5. Indicate Type of Lease STATE X FEE 6. State Oil & Gas Lease No. VB-1788 (SL) VO-1576 (BHL)
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFPEN OF THE BANK TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM PAID TORSICN PROPOSALS.) 1. Type of Well: Oil Well		
2. Name of Operator Mewbourne Oil Company 3. Address of Operator PO Box 5270, Hobbs, NM 88241	NMOCD ARTESIA	1H 9. OGRID Number 14744 10. Pool name or Wildcat Parkway; Bone Spring 49622
4. Well Location Unit Letter_A : 660'_feet from the _North line and _330'feet from the _Eastline Section 36 Township 19S Range 29E NMPM Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3326' GL		
12. Check Appropriate Box to Inc NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL DOWNHOLE COMMINGLE	SUBS	SEQUENT REPORT OF: (
OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: The starting any proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
07/22/10MI & spud 26" hole. TD'd hole @ 210'. Ran 210' 20" 94# K55 BT&C csg. Cemented with 180 sks Thixad Class "H" with additives. Mixed @ 14.6 #/g w/ 1.52 yd. Followed w/250 sks BJ Lite Class "C: (35:65:6) w/additives. Mixed @ 12.5#/g w/2.01 yd. Tail with 200 sks Class "C" w/2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 5:30 am 07/22/10. Circ 125 sks to pit. WOC 18 hrs. Drilled out with 17 ½" bit.		
07/27/10TD'ed 17 ½" hole @ 1458'. Ran 1485' 13 ¾" 48/54.5# J55/H40 ST&C Csg. Cemented with 800 sks BJ Lite "C" (35:65:6) with additives. Mixed @ 12.5 /g w/ 2.05 yd. Tail with 200 sks Class "C" w/2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 1:00 am 07/27/10. Circ 125 sks to pit. WOC 18 hrs. Drilled out with 12 ¼" bit.		
Spud Date: 07/19/2010 F	Rig Release Date:	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNATURE		
For State Use Only APPROVED BY: TITLE Conditions of Approval (if any):	E Compliance Offic	DATE 8-17-10