Office Copies To Appropriate District	State of New Me	exico		Form C-103	
District I	Energy, Minerals and Natu	ral Resources	WELL ADINO	June 19, 2008	
1625 N French Dr, Hobbs, NM 88240 District II	OH GOVERNMENT TO COMPANY		WELL API NO. 30-005-62925		
1301 W. Grand Ave., Artesia, NM 88210			5. Indicate Type of Lease		
District III 1220 South St. Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410		STATE	FEE X		
District IV Santa Fe, NM 87505  1220 S St Francis Dr., Santa Fe, NM			6. State Oil & Gas	Lease No.	
87505 SUNDRY NOTIC	CES AND REPORTS ON WELLS		7. Lease Name or I	Jnit Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			Thompson AHD		
1. Type of Well: Oil Well Gas Well X Other			8. Well Number	1	
2. Name of Operator  Lime Rock Resources A, L.P.			9. OGRID Number	2453 <b>83</b> FOFWED	
3. Address of Operator			10. Pool name or V	Vildcat NECEIVED	
Heritage Plaza, 1111 Bagby St. Suite 4600, Houston, TX 77002			Pecos S	lope Abo AUG 1 9 2010	
4. Well Location	feet from the North line	and 1,090 fee	et from the <u>East</u>		
Unit Letter: G: 1,980 Section 10	Township 5S	Range 24E		Chaves County	
Section 10	11. Elevation (Show whether DR)			maves County	
	3,924' GR			Market 1	
12. Check A	appropriate Box to Indicate N	ature of Notice,	Report or Other I	<b>D</b> ata	
NOTICE OF INTENTION TO: SUBS			SEQUENT REP	ORT OF:	
PERFORM REMEDIAL WORK   PLUG AND ABANDON   REMEDIAL WORK				ALTERING CASING	
TEMPORARILY ABANDON			P AND A X		
PULL OR ALTER CASING DOWNHOLE COMMINGLE	MOETIFEE COMFE	CASING/CEIVIEN	1 306		
_	_				
OTHER:	atad anavations (Classic state all	OTHER:	d aive nortinent dates	including agtimated data	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion					
or recompletion.	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	. • • • • • • • • • • • • • • • • • • •	·····	p. op eeee eeeeppersoon	
Dlugging Danguts					
Plugging Report:					
<u>07/26/2010:</u>					
Pulled tubing and packer. Set cast iron bridge plug at 3,450'. TIH with tubing and circulated hole with mud. Placed 25 sacks cement					
on top of plug. 07/27/2010:					
Attempted to tag cement on top of plug. Re-spotted 25 sacks cement. POOH and WOC. Tagged top of cement at 3,140'. Perforated					
the 4-1/2" casing at 1,590'. Pressured up on casing to 500# - held ok. Spotted 25 sacks cement at 1,615'.					
07/28/2010: Tagged top of cement at 1,222'. Spotted 25 sacks cement plug 887'. WOC. Tagged top of plug at 573'. Circulated 10 sacks cement					
from 60' back to surface.					
07/29/2010: Cut off wellhead and installed PA marker. Cut off anchors, filled in cellar, and leveled location.					
Cut on weilinead and installed FA	A marker. Cut on anchors, fined in	cenar, and leveled	location.	`	
Well P&A'd on 07/29/2010.					
I hereby certify that the information a	bove is true and complete to the bo	est of my knowledg	e and belief.		
	(				
SIGNATURE Heun.	TITLE Produc	ction Manager	DATE 08/1	1/2010	
			D/11D_00/1	112010	
Type or print name Steven J. Hunter	Abriet	ed for plugging of well i	ore omy.	(713) 292-9516	
For State Use Only	■ A Filabila	v under bond is retained 3 (Subsequent Report o	pending receipt	/ /	
APPROVED BY:	TITLE which	may be found at OCD-W	ch Page under DAT	E8/19/20/0	
Conditions of Approval (if any):	Forms.	www.cmnrd.state.nm.us	/oed.	MX	



## WELLBORE AFTER ABANDONMENT



Circulated cement from 60' back to surface

13-3/8", 54.5#, J-55, ST&C Surface Casing @ 856'


Spotted 25 sacks cement plug at 887'. Tagged top of cement at 573'.

Cemented from 1,540' back to surface using 1" pipe

Perforated 4-1/2" casing at 1,590'. Spotted 25 sacks cement from 1,615' to 1,222'. Tagged top of cement.

<u>Zone</u>	<u>Top</u>	
San Andres	250'	
Yeso	1,289'	
Abo	3,466'	

TOC @ 2,870'



Abo Perfs: 3,519-21'; 3,526-28'; 3,542-44' & 3,548-49' (11 - 0.42" DIA holes)

PBTD @ 4,005'

4-1/2", 10.5#, J-55, ST&C, Casing @ 4,050'

TD @ 4,050'

Lime Rock Resources Thompson AHD 1 Sec 10-5S-24E Chaves County, NM