

Submit 1 Copy To Appropriate District
Office
District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd, Aztec, NM 87410
District IV
1220 S St Francis Dr, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-37860 ✓	
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
6. State Oil & Gas Lease No. VB-1788 (SL) VO-1576 (BHL)	
7. Lease Name or Unit Agreement Name Three Palms 36 State Corn	
8. Well Number 1H	RECEIVED AUG 19 2010 NMOCD ARTESIA
9. OGRID Number 14744	
10. Pool name or Wildcat Parkway; Bone Spring 49622	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator
PO Box 5270, Hobbs, NM 88241

4. Well Location

Unit Letter A: 660' feet from the North line and 330' feet from the East line
Section 36 Township 19S Range 29E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3326' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

08/02/10...TD 12 1/4" hole at 3515'. Ran 3515' 9 5/8" 36/40# J55 ST & C & LT&C csg. Cemented with 180 sks Thixad Class H with additives. Mixed @ 14.6 #/g w/ 1.52 yd. Followed w/1000 sks BJ Lite Class C (35:65:6) w/additives. Mixed @ 12.5#/g w/2.05 yd. Tail w/200 sks Class C w/2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Pressured up after pumping 40 bbls displacement. Pumped 10 additional bbls displacement before pressure max'd out @ 2800#. Cmt in place @ 11:00 pm 08/01/10. RIH with 1" pipe. Tag at 1558'. Ran 1" pipe in 9 stages with 430 sks Class C w/4% CaCl2. Mixed @ 14.8 #/g w/1.34 yd, and 190 sks Thixad Class H 12/3. Mixed @ 14.6 #/g w/1.52 yd. Tag 1" pipe @ 427'. Circulated 10 sks to pit. Tested BOPE & csg to 1500# for 30 minutes, held OK. Drilled out with 8 3/4" bit.

Spud Date: 07/19/2010

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 08/12/10

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY Donald Gray TITLE Compliance Officer-A DATE 8-19-10
Conditions of Approval (if any):

dm