

DISTRICT I  
1625 N French Dr., Hobbs, NM 88240

DISTRICT II  
1301 W. Grand Avenue, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV  
1220 S St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-102  
Revised July 16, 2010

Submit one copy to appropriate  
District Office

**OIL CONSERVATION DIVISION**  
1220 South St. Francis Dr.  
Santa Fe, New Mexico 87505

**WELL LOCATION AND ACREAGE DEDICATION PLAT**

☐ AMENDED REPORT

API Number <b>70-015-38125</b>	Pool Code <b>96210</b>	Pool Name <b>Empire; Glorieta-Yeso</b>
Property Code <b>38705</b>	Property Name <b>CRUISER "5" STATE</b>	Well Number <b>12</b>
OGRID No. <b>162683</b>	Operator Name <b>CIMAREX ENERGY CO. OF COLORADO</b>	Elevation <b>3616'</b>

**Surface Location**

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
J	5	17 S	29 E		1650	SOUTH	1805	EAST	EDDY

**Bottom Hole Location If Different From Surface**

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Dedicated Acres <b>40</b>	Joint or Infill	Consolidation Code	Order No.						

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED  
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

<p>LOT 4 LOT 3 LOT 2 LOT 1</p> <p><b>SURFACE LOCATION</b> Lat - N 32°51'39.15" Long - W 104°05'39.48" NMSPE- N 677003.1 E 614734.9 (NAD-83)</p> <p><b>Cruiser 5 St #11</b> 2310 FSL &amp; 2135 FEL</p> <p><b>Cruiser 5 St #5</b> 2175 FSL &amp; 1650 FEL</p> <p><b>Cruiser 5 St #6</b> 1650 FSL &amp; 2150 FEL</p> <p><b>Cruiser 5 St #12</b> 1650 FSL &amp; 1805 FEL</p> <p>EO-4200-0000</p> <p>S.L.</p> <p>1805'</p> <p>1650'</p>	<p><b>OPERATOR CERTIFICATION</b></p> <p>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</p> <p><b>Zeno Farris</b> 8/31/2010</p> <p>Signature _____ Date _____</p> <p><b>Zeno Farris</b></p> <p>Printed Name _____</p> <p><b>zfarris@cimarex.com</b></p> <p>Email Address _____</p> <p><b>SURVEYOR CERTIFICATION</b></p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision and that the same is true and correct to the best of my belief.</p> <p><b>AUGUST 6, 2010</b></p> <p>Date Surveyed _____</p> <p><b>GARY L. JONES</b></p> <p>Signature of Professional Surveyor _____</p> <p><b>7977</b></p> <p>Certificate No. _____</p> <p><b>7977</b></p> <p><b>23174</b></p> <p><b>BASIN SURVEYS</b></p>
---	--

Mud, Casing, Cementing, and BOP Attachment  
**Cruiser 5 State No. 12**  
Cimarex Energy Co. of Colorado  
Unit J, Section 5  
T17S-R29E, Eddy County, NM

In response to questions asked under Section II B of Bulletin NTL-6, the following information is provided for your consideration:

Location: 1650 FSL & 1805 FEL

Elevation above sea level: 3616' GR

Proposed drilling depth: 6000'

Proposed Mud Circulating System:

Depth	Mud Wt	Visc	Fluid Loss	Type Mud
0' to 450'	8.4 - 8.6	28	NC	FW
0' to 1100'	10.0	30-32	NC	Brine water
0' to 6000'	8.4 - 9.5	30-32	NC	FW, brine

Sufficient mud materials will be kept on location at all times in order to combat lost circulation or unexpected kicks. In order to run DSTs, open hole logs, and casing, the viscosity and water loss may have to be adjusted in order to meet these needs.

Mud, Casing, Cementing, and BOP Attachment  
**Cruiser 5 State No. 12**  
 Cimarex Energy Co. of Colorado  
 Unit J, Section 5  
 T17S-R29E, Eddy County, NM

Casing & Cementing Plan:

String	Hole Size	Depth			Casing OD		Weight	Collar	Grade
<i>Surface</i>	16"	0'	to	450'	New	11¼"	42#	STC	H-40
<i>Intermediate</i>	11"	0'	to	1100'	New	8⅝"	24#	STC	J-55
<i>Production</i>	7⅞"	0'	to	6000'	New	5½"	17#	LTC	P-110

Cementing Plan:

**Surface** 530 sx Class H + 2% CaCl<sub>2</sub> (wt 14.8, yld 1.34)  
**TOC Surface**

**Intermediate** Lead: 300 sx Class C Lite + 6# Salt + 1/4# CF (wt 12.7, yld 1.99)  
Tail: 200 sx Class C + 2% CaCl<sub>2</sub> (wt 14.8, yld 1.34)  
**TOC Surface**

**Production** **Stage 1**  
 580 sx 50/50/2 Class C + 1% FL25 + 0.3% FL52 + 5% Salt + 0.5% SMS (wt 13, yld 1.68)  
**Stage 2**  
Lead: 550 sx Class H Lite + 6# Salt + 1/4# CF (wt 12.7, yld 1.92)  
Tail: 200 sx Class H + 2% CaCl<sub>2</sub> (wt 13, yld 1.68)  
**TOC 900'**

Fresh water zones will be protected by setting 11¼" casing at 450' and cementing to surface. Hydrocarbon zones will be protected by setting 8⅝" casing at 1100' and cementing to surface, and by setting 5½" casing at 6000' and cementing to 900'.

<u>Collapse Factor</u>	<u>Burst Factor</u>	<u>Tension Factor</u>
1.125	1.125	1.6

Pressure control Equipment:

An 11¼" 3000 PSI working pressure B.O.P. consisting of a one set of blind rams and one set of pipe rams and a 3000 psi annular-type preventor. A choke manifold and 120 gallon accumulator with floor and remote operating stations and auxiliary power system. A kelly cock will be installed and maintained in operable condition and a drill string safety valve in the open position will be available on the rig floor. Test BOP equipment and choke manifold to 250-psi low and 3000 psi high and annular BOP to 250 psi low and 1500 psi high by an independent service company.

BOP unit will be hydraulically operated. Below intermediate casing shoe, BOP will be operated at least once a day while drilling and the blind rams will be operated when out of hole during trips. No abnormal pressure or temperature is expected while drilling. From the base of the surface pipe through the running of production casing, the well will be equipped with a 3000 psi BOP system.

BOPS will be tested by an independent service company to 250 psi low and 3000 psi high. Hydril will be tested to 250 psi low and 1500 psi high.