

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-10110
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 648
7. Lease Name or Unit Agreement Name: East Millman Unit
8. Well Number 189
9. OGRID Number 019958
10. Pool name or Wildcat Millman Yates-SR-QN-GB-SA, East
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3451' KB; 3450' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other Water Injection

2. Name of Operator
Stephens & Johnson Operating Co.

3. Address of Operator
P.O. Box 2249, Wichita Falls, TX 76307-2249

4. Well Location
Unit Letter M : 330 feet from the South line and 990 feet from the West line
Section 11 Township 19S Range 28E NMPM County Eddy

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☒ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐


SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC.. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

This well has a shallow casing leak. We plan to locate the shallow casing leak, back off the 4 1/2" casing below the leak and run back in the hole with new 4 1/2" casing and screw back into the casing in the hole. Work to begin as soon as possible.



Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE William M. Kincaid TITLE Petroleum Engineer DATE 11-4-2010
Type or print name William M. Kincaid E-mail address: mkincaid@sjoc.net PHONE (940) 723-2166

For State Use Only

APPROVED BY Richard Inoue TITLE Compliance Officer DATE 11/10/10
Conditions of Approval (if any):