

## **Bill Richardson**

Governor

Jim Noel Cabinet Secretary

Karen W. Garcia
Deputy Cabinet Secretary

Mark Fesmire
Division Director
Oil Conservation Division



December 15, 2010

30-015-38262

Yates Petroleum Corporation 105 S. 4<sup>th</sup> Street Artesia, NM 88210

Dear Operator,

On 12/14/2010 our office was notified of 2 "lease hold" spuds on Trojans BQT State #1H and Yaddock BQY State #1H.

This operation is not in compliance with the Condition of Approval (COA) as attached to your approved APD. The COA states: "Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the water zone or zones and shall immediately set in cement the water protection string."

In order to come into compliance with the COA, NMOCD requests that you set a conductor and cement in place, with cement to surface. The conductor may be of an adequate size to allow continued operations, set at a depth of 10 feet. Top of conductor shall be at least 1 foot above ground surface level and be equipped with a locking cap type device to prevent potential ground water contamination.

Failure to satisfy the COA within 60 days of the receipt of this letter will be an acknowledgement of non-compliance, and further enforcement action will occur.

Sincerely,

Randy Dade

District Supervisor

NMOCD

N.



## Bill Richardson

Governor

Jim Noel
Cabinet Secretary

Karen W. Garcia Deputy Cabinet Secretary Mark Fesmire
Division Director
Oil Conservation Division



December 15, 2010

Yates Petroleum Corporation 105 S. 4<sup>th</sup> Street Artesia, NM 88210 30-015-3826)

Dear Operator,

On 12/14/2010 our office was notified of 2 "lease hold" spuds on <u>Trojans BQT State #1H</u> and Yaddock BQY State #1H.

This operation is not in compliance with the Condition of Approval (COA) as attached to your approved APD. The COA states: "Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the water zone or zones and shall immediately set in cement the water protection string."

In order to come into compliance with the COA, NMOCD requests that you set a conductor and cement in place, with cement to surface. The conductor may be of an adequate size to allow continued operations, set at a depth of 10 feet. Top of conductor shall be at least 1 foot above ground surface level and be equipped with a locking cap type device to prevent potential ground water contamination.

Failure to satisfy the COA within 60 days of the receipt of this letter will be an acknowledgement of non-compliance, and further enforcement action will occur.

Sincerely,

Randy Dade

**District Supervisor** 

Eurs D. Dade

**NMOCD**