

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-38069
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Wyatt Draw North 18-19 LD
8. Well Number 1H
9. OGRID Number 14744
10. Pool name or Wildcat Undesignated Yeso
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3401' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator PO Box 5270
Hobbs, NM 88241

4. Well Location

Unit Letter L : 2490 feet from the South line and 350 feet from the West line
Section 18 Township 19S Range 26E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐


13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/07/10..MI & spud 12 1/4" hole. Ran 750' 9 5/8" 36# J55 ST&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed 14.6 #/g w/1.52 yd. Tail with 400 sks Class C with additives. Mixed @ 14.8 /g w/1.34 yd. Did not circ cmt. Slow rate lift pressure @ 270# @ 2 BPM. Plug down @ 12:00 pm 10/08/10. WOC. Ran temp survey indication TOC @ 85'. RIH with 1" pipe. Tag at 85'. Ran 1" pipe in 2 stages with 75 sks Thixad Class H (12:2) Mixed @ 14.6 #/g w/1.52 yd. Tag 1" pipe @ 30'. Circ 11 sks cement to pit. WOC 18 hrs. 10/09/10 tested BOPE & casing to 1500# for 30 minutes, held OK. Drilled out with 8 3/4" bit.

10/16/10...TD'ed 8 3/4" hole @ 3093'. Ran 3093' 7" 26# J55 LT&C Csg. Cemented with 150 sks BJ Lite "C" (35:65:6) with additives. Mixed @ 12.5 /g w/ 2.05 yd. Tail with 400 sks Class "C" w/additives. Mixed @ 14.8 #/g w/1.33 yd. Plug down @ 11:15 am 10/15/10. Circ 118 sks to pit. At 2:00 pm on 10/16/10 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 6 1/8" bit.

Spud Date: 10/07/10

Rig Release Date:



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 11/15/10

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: David Gray TITLE Field Supervisor DATE 12-6-2010
Conditions of Approval (if any):

Colt