Perm 3160-3 UNITED STATES (August 2007) DEPARTMENT OF THE INTERIOR OPERATO BUREAU OF LAND MANAGEMENT	P'S COPY PORM APPROVED OMB No. 1004-0137 Expires July 31, 2010
SUNDRY NOTICES AND REPORTS ON WELLS	5, Lease Serial,No.
Do not use this form for proposals to drill or to re-enter an	NM-0557148 FR
abandoned well, Use Form 3160-3 (APD) for such proposals.	8. If Indian, Allottee or Tribe Name
	NA NA
"SUBMIT IN TRIPLICATE - Other Instructions on page	7. If Unit or CA/Agreement, Name and/or No.
1. Type of Well	NMNM-111025X
Oil Well Gas Well X Other P&A	8. Well Name and No.
2. Name of Operator	NDDUP Unit #78
Yates Petroleum Corporation	9. API Well No.
3a. Address 3b. Phone No. (include are	30-015-25732
105 S. 4th Str., Artesia, NM 88210 575-748-1471 10. Field and Pool or Exploratory Area	
4. Location of Well (Footage, Sec.,T.,R.,M., OR Survey Description) Dagger Draw; Upper Penn, North	
1980'FSL & 1980'FEL of Section 19-T19S-R25E (Unit J, NWSE) 11. County or Parish, State Eddy County, New Mexico	
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
TYPE OF SUBMISSION TYPE OF ACTION	
Acidize Deepen	Production (Start/Resume) Water Shut-Off
Notice of Intent Alter Casing Fracture Treat	Reclamation Well Integrity
	H H
X Subsequent Report Casing Repair New Construction	Recomplete Other
Change Plans X Plug and Abandon	Temporarily Abandon
Final Abandonment Notice Convert to Injection Plug Back	Water Disposal
9/9/10 NU BOP. 9/10/10 Drill down to 7208', solid. TIH with bit and set down at 7208'. 9/13/10 Porill down to 7208', solid. TIH with bit and set down at 7208'. 9/13/10 Porill down to 7208' for 15 min. Went down and worked tubing down to 7610'. Pumped 260 bbis produced water. Did not load. Pumped 100 sx Class "C" Neat with 2% CaCl at 7610'., WOC. 9/14/10 Did not tag plug. RIH with GR/JB to 7605'. Set a 7" CIBP at 7600'. Loaded hole with produced water. Tested casing to 500 psi. Circulated hole with salt gel. 9/15/10 Spotted 35 sx Class "H" Neat cement at 7600'. Calc TOC at 7427'. Tagged plug at 7590'. 9/16/10 Spotted 30 sx Class "H" Neat cement at 7585'. TOC at 7410'. Spotted 35 sx Class "C" cement at 7032'. TOC at 6817'. WOC. 9/17/10 Tagged plug at 6820'. Spotted 35 sx Class "C" Neat cement at 5542'. Calc TOC at 5327'. Did not tag. Perforated 4 holes at 4200'. Squeezed with 65 sx Class "C" Neat cement. WOC. 9/20/10 Tagged plug at 3935', Perforated 4 holes at 3053'. Pumped through perf and circulated out 9-5/8" x 7". Pumped 60 sx Class "C" Neat cement. Calc TOC at 1909'. WOC. 9/21/10 Tagged plug at 1897'. Perforated at 1197'. Pumped 60 sx Class "C" Neat cement inside and outside. WOC. Tagged at 975'. Perforated at 1197'. Pumped 60 sx Class "C" Neat cement inside and outside. WOC. Tagged at 975'. Perforated at 1197'. Pumped 45 sx Class "C" Neat cement and circulated to surface. ND BOP. 9/24/10 Dug out cellar and cut off wellhead. Installed dry hole marker and filled cellar. Cut off anchors and cleaned location. WELL IS PLUGGED AND ABANDONED.	
14. Thereby certify that the foregoing is true and correct	abject to OCD Approval
Name (Prinled/Typed)	ACCEPTED FOR OCCORD
Tina Huerta Tille Re	egulatory Compliance Supervisor (1/(\^-\)
Signature (Ina) huerta Date Se	eptember 28, 2010
THIS SPACE FOR FEDERAL OR STA	TE OFFICE USE OCT 2
Approved by T	Ille / Dajer)
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the adolegal to conduct operations traven.	ffice OLIVERY OF LAND MANAGEMENT
Title 16 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or perceyof the United States eny false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction	
(Instructions on page (14 Sept to Pathew 10/27/10 pg	

-