

OCD-ARTESIA

ATS-10-778

FORM APPROVED
OMB No. 1004-0136
Expires January 31, 2004

EA10-1153

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

5. Lease Serial No.

NM 14758

6. If Indian, Allottee or Tribe Name

7. If Unit or CA Agreement, Name and No.

8. Lease Name and Well No.

Long Draw 9 AP Fed Com #1H 38411

9. API Well No.

30-05-38310

10. Field and Pool, or Exploratory

Cemetery Yeso

11. Sec., T., R., M., or Blk. and Survey or Area

Sec 4 - T20S - R25E

12. County or Parish

Eddy

13. State

NM

1a. Type of Work: ☒ DRILL

☐ REENTER

1b. Type of Well: ☒ Oil Well ☐ Gas Well ☐ Other

Split Estate
☐ Single Zone ☐ Multiple Zone

2. Name of Operator

Mewbourne Oil Company - 14744

3a. Address

PO Box 5270 Hobbs, NM 88241

3b. Phone No. (include area code)

575-393-5905

4. Location of Well (Report location clearly and in accordance with any State requirements. *)

At surface (SL) 330' FSL & 950' FEL (Unit P)

At proposed prod. zone (BHL) Sec 9, 330' FSL & 950' FEL Unit P

14. Distance in miles and direction from nearest town or post office*

16 Miles N of Carlsbad

15. Distance from proposed*

location to nearest

property or lease line, ft.

(Also to nearest drig. unit line, if any) 330'

16. No. of Acres in lease

1442

17. Spacing Unit dedicated to this well

160

18. Distance from proposed location*

to nearest well, drilling, completed,

applied for, on this lease, ft. 620

19. Proposed Depth

7793' MD

20. BLM/BIA Bond No. on file

NM1693, Nationwide

21. Elevations (Show whether DF, KDB, RT, GL, etc.)

3462' GL

22. Approximate date work will start*

ASAP

23. Estimated duration

15

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, shall be attached to this form:

1. Well plat certified by a registered surveyor.

2. A Drilling Plan.

3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).

4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).

5. Operator certification.

6. Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature

Jackie Lathan

Name (Printed/Typed)

Jackie Lathan

Date

08/26/10

Title

Hobbs Regulator

Approved by (Signature)

/s/ Don Peterson

Name (Printed/Typed)

/s/ Don Peterson

Date

NOV 17 2010

Title

FIELD MANAGER

Office

CARLSBAD FIELD OFFICE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

APPROVAL FOR TWO YEARS

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*(Instructions on reverse)

Roswell Controlled Water Basin

RECEIVED

NOV 22 2010

NMOCD ARTESIA

Approval Subject to General Requirements
& Special Stipulations Attached

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

DISTRICT I
1625 N. French Dr., Hobbs, NM 88240

DISTRICT II
1301 W. Grand Avenue, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-102
Revised July 18, 2010

Submit one copy to appropriate
District Office

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, New Mexico 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

☐ AMENDED REPORT

API Number 30-015-38310	Pool Code 11795	Pool Name CEMETERY YESO
Property Code 38411	Property Name LONG DRAW "9" AP FEDERAL COM	Well Number 1H
OGRID No. 14744	Operator Name MEWBOURNE OIL COMPANY	Elevation 3462'

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	4	20 S	25 E		330	SOUTH	950	EAST	EDDY


Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	9	20 S	25 E		330	SOUTH	950	EAST	EDDY


Dedicated Acres	Joint or Infill	Consolidation Code	Order No.
160			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

<p>SURFACE LOCATION Lat - N 32°35'45.57" Long - W 104°29'01.79" NMSPCE- N 580566.443 E 453650.328 (NAD-27)</p>	<p>Diagram showing a grid with sections 4 and 9. A well location is marked with a circle and crosshair. Dimensions are given: 3466.9' and 3461.9' for the horizontal distance from the section line, and 330' and 950' for the vertical distance from the township line. The bottom hole location is marked with a circle and crosshair, with dimensions 3461.9' and 3456.1' for the horizontal distance, and 250' and 950' for the vertical distance. The map also shows a 330' wide strip labeled 'PRODUCING AREA' and 'PROJECT AREA'.</p>	<p>OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</p> <p><i>Jackie Lathan</i> 8/25/10 Signature Date Printed Name Email Address <i>JLathan@newbourne.com</i></p>
<p>PROPOSED BOTTOM HOLE LOCATION Lat - N 32°34'53.37" Long - W 104°29'01.98" NMSPCE- N 575290.862 E 453627.273 (NAD-27)</p>		<p>SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p><i>GARY L. JONES</i> Date Surveyed Signature & Seal of Professional Surveyor 7977</p> <p>Certificate No. Gary L. Jones 7977 BASIN SURVEYS 23074</p>



LONG DRAW "9" AP FEDERAL COM #1H *Exhibit 3A*
 Located 330' FSL and 950' FEL
 Section 4, Township 20 South, Range 25 East,
 N.M.P.M., Eddy County, New Mexico.



P.O. Box 1786
 1120 N. West County Rd.
 Hobbs, New Mexico 88241
 (575) 393-7316 - Office
 (575) 392-2206 - Fax
 basinsurveys.com

W.O. Number: JMS 23074


Survey Date: 07-21-2010

Scale: 1" = 2000'

Date: 07-30-2010



MEWBOURNE
 OIL COMPANY



LONG DRAW "9" AP FEDERAL COM #1H *Exhibit 3B*
 Located 330' FSL and 950' FEL
 Section 4, Township 20 South, Range 25 East,
 N.M.P.M., Eddy County, New Mexico.

basin
surveys
 focused on excellence
 in the oilfield

P.O. Box 1786
 1120 N. West County Rd.
 Hobbs, New Mexico 88241
 (575) 393-7316 - Office
 (575) 392-2206 - Fax
 basinsurveys.com

W.O. Number: JMS 23074

Survey Date: 07-21-2010

Scale: 1" = 2 Miles

Date: 07-30-2010

MEWBOURNE
OIL COMPANY

SECTION 4, TOWNSHIP 20 SOUTH, RANGE 25 EAST, N.M.P.M.,
EDDY COUNTY, NEW MEXICO.




Exhibit 3

Directions to Location:

FROM JUNCTION OF HWY 285 AND ROCK DAISY, GO WEST ON ROACH DAISY FOR 4.8 MILES TO LEASE ROAD, ON LEASE ROAD GO SOUTH 1.4 MILES TO LEASE ROAD, GO EAST 0.1 MILES TO PROPOSED LOCATION.

BASIN SURVEYS P.O. BOX 1786-HOBBS, NEW MEXICO

W.O. Number: 23074 Drawn By: J. SMALL

Date: 07-30-2010 Disk: JMS 23074

MEWBOURNE OIL COMPANY

REF: LONG DRAW "9" AP FEDERAL COM #1H / WELL PAD TOPO

THE LONG DRAW "9" AP FEDERAL COM #1H LOCATED 330'

FROM THE SOUTH LINE AND 950' FROM THE EAST LINE OF

SECTION 4, TOWNSHIP 20 SOUTH, RANGE 25 EAST,


N.M.P.M., EDDY COUNTY, NEW MEXICO.

Survey Date: 07-21-2010

Sheet 1 of 1 Sheets



Exhibit 3C



- Location (Permit)
- ⊗ Drilling (Well Start)
- × Abandoned Location (Permit)
- ★ Gas Well
- Oil Well
- ★● Oil and Gas Well
- Other (Observation, etc)
- ★⊗ Injection Well
- ⊗ Suspended
- ★⊗ Plugged Gas Well
- ★⊗ Plugged Oil Well
- ★⊗ Plugged Oil and Gas
- ⊗ Dry Hole (No Shows)
- ★⊗ Dry Hole w/Gas Show
- ★⊗ Dry Hole w/Oil Show
- ★⊗ Dry Hole w/Oil and Gas Show




Exhibit 6

Drilling Program
Mewbourne Oil Company
Long Draw "9" AP Federal Com #1H
330' FSL & 950' FEL (SHL)
Sec 4-T20S-R25E
Eddy County, New Mexico

1. The estimated tops of geological markers are as follows:

San Andres	760'
*Glorietta	2310'
*Yeso	2430'

2. Estimated depths of anticipated fresh water, oil, or gas:

Water	Below 100'.
Hydrocarbons	Oil and gas are anticipated in the above (*) formations. These zones will be protected by casing as necessary.

3. Pressure control equipment:

A 2000# WP annular BOP will be installed after running 9 5/8" casing. Pressure tests will be conducted and BOPE will remain in use until completion of drilling operations. The BOP will be inspected and operated daily to ensure mechanical integrity and the inspection will be recorded on the daily drilling report.
Will test the BOPE to 1500# with a third party testing company before drilling below shoe as per BLM Onshore Oil and Gas Order #2.

4. MOC proposes to drill a vertical wellbore to 2215' & kick off to horizontal @ 2788' TVD. The well will be drilled to ~~2793~~ MD (2788' TVD). See attached directional plan.
7818 per directional plan

5. Proposed casing and cementing program:

A. Casing Program:

<u>Hole Size</u>	<u>Casing</u>	<u>Wt/Ft.</u>	<u>Grade</u>	<u>Depth</u>	<u>Jt Type</u>
12 1/4"	9 5/8" (new)	36#	J55	0'-785'	LT&C
8 3/4"	5 1/2" (new)	17#	J55	0'-2215'	LT&C
8 3/4"	5 1/2" (new)	17#	J55	2215'-3115' MD	BT&C
7 7/8"	4 1/2" (new)	11.6#	J55	3115'- 2793 MD	LT&C

7818

Minimum casing design factors: Collapse 1.125, Burst 1.0, Tensile strength 1.8.

See COA *Subject to availability of casing.

B. Cementing Program:

- i. Surface Casing: 225 sacks class "C" w/2% CaCl₂. Yield at 1.34 cuft/sk. Cmt circulated to surface.
- ii. Production Casing: Lateral hole will utilize a packer/port system of isolation. An ECP will be placed to isolate the Glorietta from the San Andres. A FO cement tool will be placed immediately above the KOP and cemented w/180 sacks light class "C" w/additives. Yield at 2.45 cuft/sk. And 100 sacks class "C". Yield at 1.32 cuft/sk. Cmt calculated to circulate from FO cementer to surface.

Option (1): Plans are to run a packer/port completion system in the lateral production hole. A FO Cementer will be placed at KOP. After casing has been run and the hole is circulated clean, the isolation packers will be set. Drilling rig will set casing slips, ND drilling equipment, NU wellhead, NU completion BOPE/frac valve, RD&MO drilling rig. BOPE will be tested to 1000#. Gauges will be installed and checked daily on the 9 5/8" x 5 1/2" annulus and on the 5 1/2" casing. A pressure relief valve set at 150 psi will release excess pressure into a frac tank. A completion rig will MI&RU within one week after the drilling equipment is moved off location. Run tubing with cementer opening tool, and circulate cement to surface. Then normal completion operations will begin.

Option (2): If hole conditions do not allow option one to be put into place, the drilling rig will run tubing with opening tool, cement casing to surface, and normal operations will continue.

*Mewbourne Oil Company reserves the right to change cement designs as hole conditions may warrant.

6. Mud Program:

Interval	Type System	Weight	Viscosity	Fluid Loss
0'-775'	FW spud mud	8.6-9.0	32-34	NA
775'-2200'	Fresh water	8.4-8.6	28-30	NA
2200'- TD	FW w/Polymer	8.5-8.7	32-35	20

7. Evaluation Program:

Samples: 10' samples from surface casing to TD
Logging: GR from 2200' to TD. Gyro Surface to 2200'.

8. Downhole Conditions

Zones of abnormal pressure: None anticipated
Zones of lost circulation: Anticipated in surface and intermediate holes
Maximum bottom hole temperature: 100 degree F
Maximum bottom hole pressure: 8.4 lbs/gal gradient or less

9. Anticipated Starting Date:

Mewbourne Oil Company intends to drill this well as soon as possible after receiving approval with approximately 15 days involved in drilling operations and an additional 10 days involved in completion operations on the project.

Mewbourne Oil Company

Location: Eddy County, NM
Field: (Long) Sec 4, T20S, R25E
Facility: Long Draw 9 AP Fed Corn No. 1H

Slot: No. 1H SHL
Well: No. 1H
Wellbore: No. 1H PWB


Well Profile Data

Design Comment	MD (ft)	Inc (°)	Az (°)	TVD (ft)	Local N (ft)	Local E (ft)	DLS (°/100ft)	VS (ft)
Tie On	0.00	0.000	180.250	0.00	0.00	0.00	0.00	0.00
EST. KOP	2215.00	0.000	180.250	2215.00	0.00	0.00	0.00	0.00
END OF CURVE	3114.99	89.999	180.250	2787.96	-572.95	-2.50	10.00	572.95
No. 1H PBHL	7818.15	89.999	180.250	2788.00	-5276.06	-23.06	0.00	5276.11



Mewbourne Oil Company

Plot reference wellpath is Preim 1	Old System: NAD83 / TM New Mexico State Plane, Eastern Zone (2001), US feet
True vertical depths are referenced to Rig 101 on No. 1H SHL (R/S)	North Reference: Grid north
Measured depths are referenced to Rig 101 on No. 1H SHL (R/S)	Scale: True distance
Rig 101 on No. 1H SHL (R/S) to Mean Sea Level: 3476 feet	Depths are in feet
Mean Sea Level to Mad line Facility: Long Draw 9 AP Fed Corn No. 1H - 3452 feet	Created by: Victor Hernandez on 8/25/2010
Coordinates are in feet referenced to Slot	




BGGM (1945.0 to 2011.0) Dip: 60.40° Field: 48876.7 nT
Magnetic North is 8.17 degrees East of True North (at 8/25/2010)
Grid North is 0.08 degrees West of True North

To correct azimuth from True to Grid add 0.08 degrees

To correct azimuth from Magnetic to Grid add 8.25 degrees

For example: if the Magnetic North Azimuth = 90 degs, then the Grid North Azimuth = 90 + 8.25 = 98.25



Planned Wellpath Report

Prelim_1
Page 1 of 4



REFERENCE WELLPATH IDENTIFICATION			
Operator	Mewbourne Oil Company	Slot	No. 1H SHL
Area	Eddy County, NM	Well	No. 1H
Field	(Long) Sec 4, T20S, R25E	Wellbore	No. 1H PWB
Facility	Long Draw 9 AP Fed Com No. 1H		

REPORT SETUP INFORMATION			
Projection System	NAD27 / TM New Mexico State Planes, Eastern Zone (3001), US feet	Software System	WellArchitect® 2.0
North Reference	Grid	User	Victor Hernandez
Scale	0.999912	Report Generated	8/25/2010 at 9:42:06 AM
Convergence at slot	0.08° West	Database/Source file	WA_Midland/No. 1H_PWB.xml

WELLPATH LOCATION						
	Local coordinates		Grid coordinates		Geographic coordinates	
	North[ft]	East[ft]	Easting[USft]	Northing[USft]	Latitude	Longitude
Slot Location	0.00	0.00	453650.33	580566.44	32°35'45.573"N	104°29'01.797"W
Facility Reference Pt			453650.33	580566.44	32°35'45.573"N	104°29'01.797"W
Field Reference Pt			452952.66	581878.03	32°35'58.542"N	104°29'09.974"W

WELLPATH DATUM			
Calculation method	Minimum curvature	Rig 101 on No. 1H SHL (KB) to GL	16.00ft
Horizontal Reference Pt	Slot	Rig 101 on No. 1H SHL (KB) to Mean Sea Level	3478.00ft
Vertical Reference Pt	Rig 101 on No. 1H SHL (KB)	GL to Mud Line (Facility)	0.00ft
MD Reference Pt	Rig 101 on No. 1H SHL (KB)	Section Origin	N 0.00, E 0.00 ft
Field Vertical Reference	Mean Sea Level	Section Azimuth	180.25°

Planned Wellpath Report

Prelim 1

Page 2 of 4



REFERENCE WELLPATH IDENTIFICATION			
Operator	Mewbourne Oil Company	Slot	No. 1H SHL
Area	Eddy County, NM	Well	No. 1H
Field	(Long) Sec 4, T20S, R25E	Wellbore	No. 1H PWB
Facility	Long Draw 9 AP Fed Com No. 1H		

WELLPATH DATA (60 stations) † = interpolated/extrapolated station												
MD [ft]	Inclination [°]	Azimuth [°]	TVD [ft]	Vert Sect [ft]	North [ft]	East [ft]	Grid East [srv ft]	Grid North [srv ft]	Latitude	Longitude	DLS [°/100ft]	Comments
0.00	0.000	180.250	0.00	0.00	0.00	0.00	453650.33	580566.44	32°35'45.573"N	104°29'01.797"W	0.00	Tie On
2215.00	0.000	180.250	2215.00	0.00	0.00	0.00	453650.33	580566.44	32°35'45.573"N	104°29'01.797"W	0.00	EST. KOP
2315.00†	10.000	180.250	2314.49	8.70	-8.70	-0.04	453650.29	580557.74	32°35'45.486"N	104°29'01.797"W	10.00	
2415.00†	20.000	180.250	2410.96	34.55	-34.55	-0.15	453650.18	580531.89	32°35'45.231"N	104°29'01.798"W	10.00	
2515.00†	30.000	180.250	2501.48	76.76	-76.76	-0.34	453649.99	580489.69	32°35'44.813"N	104°29'01.800"W	10.00	
2615.00†	40.000	180.250	2583.29	134.05	-134.05	-0.59	453649.74	580432.41	32°35'44.246"N	104°29'01.802"W	10.00	
2715.00†	50.000	180.250	2653.91	204.67	-204.67	-0.89	453649.43	580361.80	32°35'43.547"N	104°29'01.804"W	10.00	
2815.00†	60.000	180.250	2711.20	286.48	-286.48	-1.25	453649.08	580279.99	32°35'42.738"N	104°29'01.807"W	10.00	
2915.00†	70.000	180.250	2753.40	376.99	-376.99	-1.65	453648.68	580189.49	32°35'41.842"N	104°29'01.810"W	10.00	
3015.00†	80.000	180.250	2779.25	473.46	-473.46	-2.07	453648.26	580093.03	32°35'40.888"N	104°29'01.813"W	10.00	
3114.99	89.999	180.250	2787.96	572.95	-572.95	-2.50	453647.82	579993.55	32°35'39.903"N	104°29'01.817"W	10.00	END OF CURVE
3115.00†	89.999	180.250	2787.96	572.96	-572.95	-2.50	453647.82	579993.54	32°35'39.903"N	104°29'01.817"W	0.00	
3215.00†	89.999	180.250	2787.96	672.96	-672.95	-2.94	453647.39	579893.55	32°35'38.914"N	104°29'01.820"W	0.00	
3315.00†	89.999	180.250	2787.96	772.96	-772.95	-3.38	453646.95	579793.56	32°35'37.924"N	104°29'01.824"W	0.00	
3415.00†	89.999	180.250	2787.96	872.96	-872.95	-3.81	453646.51	579693.57	32°35'36.935"N	104°29'01.827"W	0.00	
3515.00†	89.999	180.250	2787.96	972.96	-972.95	-4.25	453646.08	579593.58	32°35'35.945"N	104°29'01.831"W	0.00	
3615.00†	89.999	180.250	2787.96	1072.96	-1072.95	-4.69	453645.64	579493.59	32°35'34.956"N	104°29'01.834"W	0.00	
3715.00†	89.999	180.250	2787.96	1172.96	-1172.95	-5.13	453645.20	579393.60	32°35'33.966"N	104°29'01.837"W	0.00	
3815.00†	89.999	180.250	2787.96	1272.96	-1272.95	-5.56	453644.77	579293.61	32°35'32.977"N	104°29'01.841"W	0.00	
3915.00†	89.999	180.250	2787.96	1372.96	-1372.94	-6.00	453644.33	579193.62	32°35'31.987"N	104°29'01.844"W	0.00	
4015.00†	89.999	180.250	2787.97	1472.96	-1472.94	-6.44	453643.89	579093.63	32°35'30.998"N	104°29'01.848"W	0.00	
4115.00†	89.999	180.250	2787.97	1572.96	-1572.94	-6.87	453643.45	578993.64	32°35'30.008"N	104°29'01.851"W	0.00	
4215.00†	89.999	180.250	2787.97	1672.96	-1672.94	-7.31	453643.02	578893.65	32°35'29.019"N	104°29'01.855"W	0.00	
4315.00†	89.999	180.250	2787.97	1772.96	-1772.94	-7.75	453642.58	578793.66	32°35'28.029"N	104°29'01.858"W	0.00	
4415.00†	89.999	180.250	2787.97	1872.96	-1872.94	-8.18	453642.14	578693.67	32°35'27.040"N	104°29'01.862"W	0.00	
4515.00†	89.999	180.250	2787.97	1972.96	-1972.94	-8.62	453641.71	578593.68	32°35'26.050"N	104°29'01.865"W	0.00	
4615.00†	89.999	180.250	2787.97	2072.96	-2072.94	-9.06	453641.27	578493.69	32°35'25.061"N	104°29'01.869"W	0.00	
4715.00†	89.999	180.250	2787.97	2172.96	-2172.94	-9.50	453640.83	578393.70	32°35'24.071"N	104°29'01.872"W	0.00	
4815.00†	89.999	180.250	2787.97	2272.96	-2272.94	-9.93	453640.40	578293.71	32°35'23.082"N	104°29'01.875"W	0.00	
4915.00†	89.999	180.250	2787.97	2372.96	-2372.94	-10.37	453639.96	578193.72	32°35'22.092"N	104°29'01.879"W	0.00	

Planned Wellpath Report

Prelim_1

Page 3 of 4



REFERENCE WELLPATH IDENTIFICATION

Operator	Mewbourne Oil Company	Slot	No. 1H SHL
Area	Eddy County, NM	Well	No. 1H
Field	(Long) Sec 4, T20S, R25E	Wellbore	No. 1H PWB
Facility	Long Draw 9 AP Fed Com No. 1H		

WELLPATH DATA (60 stations) † = interpolated/extrapolated station

MD [ft]	Inclination [°]	Azimuth [°]	TVD [ft]	Vert Sect [ft]	North [ft]	East [ft]	Grid East [srv ft]	Grid North [srv ft]	Latitude	Longitude	DLS [°/100ft]	Comments
5015.00†	89.999	180.250	2787.97	2472.96	-2472.93	-10.81	453639.52	578093.73	32°35'21.103"N	104°29'01.882"W	0.00	
5115.00†	89.999	180.250	2787.98	2572.96	-2572.93	-11.24	453639.08	577993.74	32°35'20.114"N	104°29'01.886"W	0.00	
5215.00†	89.999	180.250	2787.98	2672.96	-2672.93	-11.68	453638.65	577893.75	32°35'19.124"N	104°29'01.889"W	0.00	
5315.00†	89.999	180.250	2787.98	2772.96	-2772.93	-12.12	453638.21	577793.76	32°35'18.135"N	104°29'01.893"W	0.00	
5415.00†	89.999	180.250	2787.98	2872.96	-2872.93	-12.56	453637.77	577693.77	32°35'17.145"N	104°29'01.896"W	0.00	
5515.00†	89.999	180.250	2787.98	2972.96	-2972.93	-12.99	453637.34	577593.78	32°35'16.156"N	104°29'01.900"W	0.00	
5615.00†	89.999	180.250	2787.98	3072.96	-3072.93	-13.43	453636.90	577493.79	32°35'15.166"N	104°29'01.903"W	0.00	
5715.00†	89.999	180.250	2787.98	3172.96	-3172.93	-13.87	453636.46	577393.80	32°35'14.177"N	104°29'01.907"W	0.00	
5815.00†	89.999	180.250	2787.98	3272.96	-3272.93	-14.30	453636.03	577293.81	32°35'13.187"N	104°29'01.910"W	0.00	
5915.00†	89.999	180.250	2787.98	3372.96	-3372.93	-14.74	453635.59	577193.82	32°35'12.198"N	104°29'01.913"W	0.00	
6015.00†	89.999	180.250	2787.98	3472.96	-3472.92	-15.18	453635.15	577093.83	32°35'11.208"N	104°29'01.917"W	0.00	
6115.00†	89.999	180.250	2787.98	3572.96	-3572.92	-15.61	453634.72	576993.84	32°35'10.219"N	104°29'01.920"W	0.00	
6215.00†	89.999	180.250	2787.99	3672.96	-3672.92	-16.05	453634.28	576893.85	32°35'09.229"N	104°29'01.924"W	0.00	
6315.00†	89.999	180.250	2787.99	3772.96	-3772.92	-16.49	453633.84	576793.86	32°35'08.240"N	104°29'01.927"W	0.00	
6415.00†	89.999	180.250	2787.99	3872.96	-3872.92	-16.93	453633.40	576693.87	32°35'07.250"N	104°29'01.931"W	0.00	
6515.00†	89.999	180.250	2787.99	3972.96	-3972.92	-17.36	453632.97	576593.88	32°35'06.261"N	104°29'01.934"W	0.00	
6615.00†	89.999	180.250	2787.99	4072.96	-4072.92	-17.80	453632.53	576493.89	32°35'05.271"N	104°29'01.938"W	0.00	
6715.00†	89.999	180.250	2787.99	4172.96	-4172.92	-18.24	453632.09	576393.90	32°35'04.282"N	104°29'01.941"W	0.00	
6815.00†	89.999	180.250	2787.99	4272.96	-4272.92	-18.67	453631.66	576293.91	32°35'03.292"N	104°29'01.945"W	0.00	
6915.00†	89.999	180.250	2787.99	4372.96	-4372.92	-19.11	453631.22	576193.92	32°35'02.303"N	104°29'01.948"W	0.00	
7015.00†	89.999	180.250	2787.99	4472.96	-4472.92	-19.55	453630.78	576093.93	32°35'01.313"N	104°29'01.951"W	0.00	
7115.00†	89.999	180.250	2787.99	4572.96	-4572.91	-19.98	453630.35	575993.94	32°35'00.324"N	104°29'01.955"W	0.00	
7215.00†	89.999	180.250	2787.99	4672.96	-4672.91	-20.42	453629.91	575893.95	32°34'59.334"N	104°29'01.958"W	0.00	
7315.00†	89.999	180.250	2788.00	4772.96	-4772.91	-20.86	453629.47	575793.96	32°34'58.345"N	104°29'01.962"W	0.00	
7415.00†	89.999	180.250	2788.00	4872.96	-4872.91	-21.30	453629.03	575693.97	32°34'57.355"N	104°29'01.965"W	0.00	
7515.00†	89.999	180.250	2788.00	4972.96	-4972.91	-21.73	453628.60	575593.98	32°34'56.366"N	104°29'01.969"W	0.00	
7615.00†	89.999	180.250	2788.00	5072.96	-5072.91	-22.17	453628.16	575493.99	32°34'55.376"N	104°29'01.972"W	0.00	
7715.00†	89.999	180.250	2788.00	5172.96	-5172.91	-22.61	453627.72	575394.00	32°34'54.387"N	104°29'01.976"W	0.00	
7815.00†	89.999	180.250	2788.00	5272.96	-5272.91	-23.04	453627.29	575294.01	32°34'53.397"N	104°29'01.979"W	0.00	
7818.15	89.999	180.250	2788.00†	5276.11†	-5276.06	-23.06	453627.27	575290.86	32°34'53.366"N	104°29'01.979"W	0.00	No. 1H PBHL

Planned Wellpath Report

Prelim_1
Page 4 of 4

REFERENCE WELLPATH IDENTIFICATION			
Operator	Mewbourne Oil Company	Slot	No. 1H SHL
Area	Eddy County, NM	Well	No. 1H
Field	(Long) Sec 4, T20S, R25E	Wellbore	No. 1H PWB
Facility	Long Draw 9 AP Fed Com No. 1H		

TARGETS									
Name	MD [ft]	TVD [ft]	North [ft]	East [ft]	Grid East [srv ft]	Grid North [srv ft]	Latitude	Longitude	Shape
1) AP No. 1H PBHL	7818.15	2788.00	5276.06	23.06	453627.27	575290.86	32°34'53.366"N	104°29'01.979"W	point

SURVEY PROGRAM Ref Wellbore: No. 1H PWB Ref Wellpath: Prelim_1				
Start MD [ft]	End MD [ft]	Positional Uncertainty Model	Log Name/Comment	Wellbore
16.00	7818.15	NaviTrak (Standard)		No. 1H PWB





Exhibit 5



Top Soil Stockpile

Notes Regarding Blowout Preventer

Mewbourne Oil Company

Long Draw "9" AP Federal Com #1H

330' FSL & 950' FEL (SHL)

Sec 4-T20S-R25E

Eddy County, New Mexico

- I. Drilling nipple (bell nipple) to be constructed so that it can be removed without the use of a welder through the opening of the rotary table, with minimum internal diameter equal to blowout preventer bore.
- II. Blowout preventer and all fittings must be in good condition with a minimum 2000 psi working pressure on 9 5/8" casing.
- III. Safety valve must be available on the rig floor at all times with proper connections to install in the drill string. Valve must be full bore with minimum 2000 psi working pressure.
- IV. Equipment through which bit must pass shall be at least as large as internal diameter of the casing.
- V. A kelly cock shall be installed on the kelly at all times.

Blowout preventer closing equipment to include and accumulator of at least 40 gallon capacity, two independent sources of pressure on closing unit, and meet all other API specifications.

Mewbourne Oil Company
BOP Schematic for
8 3/4" & 7 7/8" Hole





Exhibit #2

Long Draw 9 AP Fed Com #1H
330' FSL & 950' FEL
Sec 4-T20S-R25E
Eddy, County
New Mexico



2000#/3000#BOP manifold system

For Exhibit 2 + 2A

Hydrogen Sulfide Drilling Operations Plan

Mewbourne Oil Company

Long Draw "9" AP Federal Com #1H

330' FSL & 950' FEL

Sec 4-T20S-R25E

Eddy County, New Mexico

1. General Requirements

Rule 118 does not apply to this well because MOC has researched this area and no high concentrations of H₂S were found. MOC will have on location and working all H₂S safety equipment before the Yates formation for purposes of safety and insurance requirements.

2. Hydrogen Sulfide Training

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will have received training from a qualified instructor in the following areas prior to entering the drilling pad area of the well:

1. The hazards and characteristics of hydrogen sulfide gas.
2. The proper use of personal protective equipment and life support systems.
3. The proper use of hydrogen sulfide detectors, alarms, warning systems, briefing areas, evacuation procedures.
4. The proper techniques for first aid and rescue operations.

Additionally, supervisory personnel will be trained in the following areas:

- 1 The effects of hydrogen sulfide on metal components. If high tensile tubular systems are utilized, supervisory personnel will be trained in their special maintenance requirements.
- 2 Corrective action and shut in procedures, blowout prevention, and well control procedures while drilling a well.
- 3 The contents of the Hydrogen Sulfide Drilling Operations Plan.

There will be an initial training session prior to encountering a known hydrogen sulfide source. The initial training session shall include a review of the site specific Hydrogen Sulfide Drilling Operations Plan.

3. Hydrogen Sulfide Safety Equipment and Systems

All hydrogen sulfide safety equipment and systems will be installed, tested, and operational prior to drilling below the intermediate casing.

1. Well Control Equipment

- A. Flare line with automatic igniter or continuous ignition source.
- B. Choke manifold with minimum of one adjustable choke.
- C. Blowout preventers equipped with blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
- D. Auxiliary equipment including annular type blowout preventer.

2. Protective Equipment for Essential Personnel

Thirty minute self contained work unit located at briefing area as indicated on wellsite diagram.

3. Hydrogen Sulfide Protection and Monitoring Equipment

Two portable hydrogen sulfide monitors positioned on location for optimum coverage and detection. The units shall have audible sirens to notify personnel when hydrogen sulfide levels exceed 20 PPM.

4. Visual Warning Systems

A. Wind direction indicators as indicated on the wellsite diagram.

B. Caution signs shall be posted on roads providing access to location. Signs shall be painted a high visibility color with lettering of sufficient size to be readable at reasonable distances from potentially contaminated areas.

4. **Mud Program**

The mud program has been designed to minimize the amount of hydrogen sulfide entrained in the mud system. Proper mud weight, safe drilling practices, and the use of hydrogen sulfide scavengers will minimize hazards while drilling the well.

5. **Metallurgy**

All tubular systems, wellheads, blowout preventers, drilling spools, kill lines, choke manifolds, and valves shall be suitable for service in a hydrogen sulfide environment when chemically treated.

6. **Communications**

State & County Officials phone numbers are posted on rig floor and supervisors trailer. Communications in company vehicles and toolpushers are either two way radios or cellular phones.

7. **Well Testing**

Drill stem testing is not an anticipated requirement for evaluation of this well. A drill stem test is required, it will be conducted with a minimum number of personnel in the immediate vicinity. The test will be conducted during daylight hours only.

8. **Emergency Phone Numbers**

Eddy County Sheriff's Office	911 or 575-887-7551
Ambulance Service	911 or 575-885-2111
Carlsbad Fire Dept	911 or 575-885-2111
Loco Hills Volunteer Fire Dept.	911 or 575-677-3266
Closest Medical Facility - Columbia Medical Center of Carlsbad	575-492-5000

Mewbourne Oil Company	Hobbs District Office	575-393-5905
	Fax	575-397-6252
	2 nd Fax	575-393-7259

District Manager	Micky Young	575-390-0999
Drilling Superintendent	Frosty Lathan	575-390-4103
Engineer	Charles Martin	575-441-2081

MULTI-POINT SURFACE USE AND OPERATIONS PLAN

MEWBOURNE OIL COMPANY

Long Draw "9" AP Federal #1H

330' FSL & 950' FEL

Sec 4-T20S-R25E

Eddy County, New Mexico

This plan is submitted with Form 3160-3, Application for Permit to Drill, Covering the above described well. The purpose of this plan is to describe the location of the proposed well, the proposed construction activities and operations plan, the magnitude of the surface disturbance involved, and the procedures to be followed in restoring the surface so that a complete appraisal can be made of the environmental impact associated with the proposed operations.

1. Existing Roads:

- A. Exhibit #3 is a road map showing the location of the proposed well. Existing roads are highlighted in black. Exhibits #3-#3C are maps showing the location of the proposed well and access road. Existing and proposed roads are highlighted in black.
- B. Directions to location: From Carlsbad on US 285, north 16 miles to Rock Daisy Rd. Turn left (west) 4.7 miles to lease road. Turn left (south) 1.4 miles. Turn left (east) ½ mile to location.
- C. Existing roads will be maintained in a condition the same as or better than before operations begin.

2. Proposed Access Road:

- A. 46 feet of new road construction will be needed.
- B. The maximum width of the driving surface will be 14 feet. The road will be crowned and ditched with a 2% slope from the tip of the crown to the edge of the driving surface. The ditches will be 1 foot deep with 3:1 slopes. The road will be surfaced with 6" of rolled and compacted caliche.
- C. Mewbourne Oil Co. will cooperate with other operators in the maintenance of lease roads.

3. Location of Existing Wells:

There are producing wells within the immediate vicinity of the well site. Exhibit #4 shows existing wells within a one mile radius.

4. Location of Existing and/or Proposed Facilities:

- A. There are production facilities on this lease at the present time.
- B. In the event that the well is productive, existing production facility (at Long Draw "9"H Battery) in unit letter H of Sec. 9, T20S, R25E will be utilized. The entire (approx 7,000') polypipe flowline will lay 11' parallel to existing roads with estimated 65 psi. Exhibit #3D shows the proposed flowline.
- C. All production vessels left on location will be painted to conform to BLM painting stipulations within 180 days of installation.

5. Location and Type of Water Supply

The well will be drilled with a combination of fresh water and brine water based mud systems. The water will be obtained from commercial suppliers in the area and/or hauled to the location by

transport trucks over existing and proposed roads as indicated in Exhibit #3.

6. Source of Construction Materials

All material required for construction of the drill pad and access roads will be obtained from private, state, or federal pits. The construction contractor will be solely responsible for securing construction materials required for this operation and paying any royalties that may be required on those materials.

7. Methods of Handling Waste Disposal:

- A. Drill cuttings not retained for evaluation purposed will be hauled to CRI permit# NM-010006.
- B. Water produced during operations will be hauled to an off-site permitted SWD in the area.
- C. If any liquid hydrocarbons are produced during operations, those liquids will be stored in suitable tanks until sold.
- D. Sewage and gray water will be safely contained on-site, and then waste will be disposed at an approved off-site facility.
- E. All trash, junk, and other waste materials will be stored in proper containers to prevent dispersal and will be removed to an appropriate facility within one week of cessation of drilling and completion activities.

8. Ancillary Facilities

There are no ancillary facilities within the immediate vicinity of the proposed well site.

9. Well Site Layout

- A. A diagram of the drill pad is shown in Exhibit #5. Dimensions of the pad and location of major rig components are shown.
- B. The pad dimension of 230' x 300' has been staked and flagged.
- C. An archaeological survey is in the process of being conducted on the proposed location pad.

10. Plans for Restoration of Surface

- A. Within 90 days of cessation of drilling and completion operations, all equipment not necessary for production operations will be removed. The location will be cleaned of all trash and junk to assure the well site is left as aesthetically pleasing as reasonably possible.
- B. Interim reclamation:
 - i. All areas not needed for production operations will be reclaimed.
 - ii. Caliche will be removed, the land will be recontoured, the top soil from stockpile will be spread over these areas.
 - iii. The disturbed area will be restored by re-seeding during the proper growing season.
 - iv. Any additional caliche required for production facilities will be obtained from the area shown in exhibit #6 as interim reclamation.
- C. Final Reclamation:

- i. Upon cessation of the proposed operations, if the well is abandoned, all equipment and trash will be removed and taken to a proper facility.
- ii. The location and road surfacing material will be removed and used to patch area lease roads. The entire location will be restored to the original contour as much as reasonable possible. The top soil used for interim reclamation will be spread over the entire location. All restoration work will be completed within 180 days of cessation of activities.

11. Surface Ownership:

The surface is owned by Herrick Family Trust 8817 SE 60th, Mercer Island, WA 98040. Phone # (206) 232-7100. A copy of this surface use plan has been sent to the above address. A surface access agreement between the surface owner and Mewbourne Oil Co. has been reached, (to conduct drilling operations).

12. Other Information:

- A. Topography: Refer to the archaeological report for a detailed description of flora, fauna, soil characteristics, dwellings, and historical or cultural sites.
- B. The primary use of the surface at the location is for grazing of livestock.

13. Operator's Representative:

- A. Through APD approval, drilling, completion and production operations:

N.M. Young, District Manager
Mewbourne Oil Company
PO Box 5270
Hobbs, NM 88241
575-393-5905

**United States Department of the Interior
Bureau of Land Management
Carlsbad Field Office
620 E Greene Street
Carlsbad, New Mexico 88201-1287**

Statement Accepting Responsibility for Operations

Operator Name: Mewbourne Oil Company
Street or Box: P.O. Box 5270
City, State: Hobbs, New Mexico
Zip Code: 88241

The undersigned accepts all applicable terms, conditions, stipulations, and restrictions concerning operations conducted of the leased land or portion thereof, as described below.

Lease Number: Lease Number NMNM-14758


Legal Description of Land: Section 4, T-20S, R-25E, Eddy County, New Mexico.
Location @ 330' FSL & 950' FEL.

Formation (if applicable): Yeso

Bond Coverage: \$150,000

BLM Bond File: NM1693, Nationwide

Authorized Signature: _____



Name: NM (Micky) Young

Title: District Manager

Date: August 25, 2010

Mewbourne Oil Company

PO Box 5270
Hobbs, NM 88241
(575) 393-5905

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of State and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

Executed this 25 day of August, 2010.

Name: NM Young

Signature: 

Position Title: Hobbs District Manager

Address: PO Box 5270, Hobbs NM 88241

Telephone: 575-393-5905

E-mail: myoung@mewbourne.com

PECOS DISTRICT CONDITIONS OF APPROVAL

OPERATOR'S NAME:	MEWBOURNE OIL
LEASE NO.:	NM14758
WELL NAME & NO.:	1H-LONG DRAW 9 AP FED COM
SURFACE HOLE FOOTAGE:	0330' FSL & 0950' FEL
BOTTOM HOLE FOOTAGE:	0330' FSL & 0950' FEL
LOCATION:	Section 04, T. 20 S., R. 25 E., NMPM
COUNTY:	Eddy County, New Mexico

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- ☐ **General Provisions**
- ☐ **Permit Expiration**
- ☐ **Archaeology, Paleontology, and Historical Sites**
- ☐ **Noxious Weeds**
- ☒ **Special Requirements**
 - Cave/Karst
- ☐ **Construction**
 - Notification
 - V-Door Direction – Not stipulated
 - Topsoil
 - Closed Loop System
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- ☐ **Road Section Diagram**
- ☒ **Drilling**
 - Drainage packer required
 - Production casing options
 - Logging requirements
 - Waste Material and Fluids
- ☐ **Production (Post Drilling)**
 - Well Structures & Facilities
 - Pipelines
 - Electric Lines
- ☐ **Interim Reclamation**
- ☐ **Final Abandonment & Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

Cave and Karst

**** Depending on location, additional Drilling, Casing, and Cementing procedures may be required by engineering to protect critical karst groundwater recharge areas.**

Cave/Karst Surface Mitigation

The following stipulations will be applied to minimize impacts during construction, drilling and production.

Construction:

In the advent that any underground voids are opened up during construction activities, construction activities will be halted and the BLM will be notified immediately.

No Blasting:

No blasting will be utilized for pad construction. The pad will be constructed and leveled by adding the necessary fill and caliche.

Pad Berming:

The pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the pad. All sides will be bermed.

Tank Battery Liners and Berms:

Tank battery locations will be lined and bermed. A 20 mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.

Leak Detection System:

A method of detecting leaks is required. The method could incorporate gauges to measure loss, situating valves and lines so they can be visually inspected, or installing electronic sensors to alarm when a leak is present. Leak detection plan will be submitted to BLM for approval.

Automatic Shut-off Systems:

Automatic shut off, check valves, or similar systems will be installed for pipelines and tanks to minimize the effects of catastrophic line failures used in production or drilling.

Cave/Karst Subsurface Mitigation

The following stipulations will be applied to protect cave/karst and ground water concerns:

Rotary Drilling with Fresh Water:

Fresh water will be used as a circulating medium in zones where caves or karst features are expected. SEE ALSO: Drilling COAs for this well.

Directional Drilling:

Kick off for directional drilling will occur at least 100 feet below the bottom of the cave occurrence zone. SEE ALSO: Drilling COAs for this well.

Lost Circulation:

ALL lost circulation zones from the surface to the base of the cave occurrence zone will be logged and reported in the drilling report.

Regardless of the type of drilling machinery used, if a void of four feet or more and circulation losses greater than 70 percent occur simultaneously while drilling in any cave-bearing zone, the BLM will be notified immediately by the operator. The BLM will assess the situation and work with the operator on corrective actions to resolve the problem.

Abandonment Cementing:

Upon well abandonment in high cave karst areas additional plugging conditions of approval may be required. The BLM will assess the situation and work with the operator to ensure proper plugging of the wellbore.

Pressure Testing:

Annual pressure monitoring will be performed by the operator on all casing annuli and reported in a sundry notice. If the test results indicated a casing failure has occurred, remedial action will be undertaken to correct the problem to the BLM's approval.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5972 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. V-DOOR DIRECTION: Not stipulated

C. TOPSOIL

The operator shall stockpile the topsoil in a low profile manner in order to prevent wind/water erosion of the topsoil. The topsoil to be stripped is approximately 4 inches in depth. The topsoil will be used for interim and final reclamation.

D. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

E. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

F. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation.

The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

G. ON LEASE ACCESS ROADS

Road Width

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed thirty (30) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning


Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts

Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall be constructed on all blind curves. Turnouts shall conform to the following diagram:




Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outslowing and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

Culvert Installations

Appropriately sized culvert(s) shall be installed at the deep waterway channel flow crossing.

Cattleguards

An appropriately sized cattleguard(s) sufficient to carry out the project shall be installed and maintained at fence crossing(s).

Any existing cattleguard(s) on the access road shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattleguard(s) that are in place and are utilized during lease operations.

A gate shall be constructed and fastened securely to H-braces.

Fence Requirement


Where entry is required across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting.

The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fence(s).

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Figure 1 – Cross Sections and Plans For Typical Road Sections



VII. DRILLING

A. DRILLING OPERATIONS REQUIREMENTS

The BLM is to be notified a minimum of 4 hours in advance for a representative to witness:

- a. Spudding well
- b. Setting and/or Cementing of all casing strings
- c. BOPE tests

☒ **Eddy County**

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

1. **Although Hydrogen Sulfide has not been reported in this section, it is always a potential hazard. If Hydrogen Sulfide is encountered, please report measured amounts and formations to the BLM.**
2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval. **See Option 1 and 2 in casing section.**
3. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
4. **The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) will be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies.**

B. CASING

Changes to the approved APD casing and cement program require submitting a sundry and receiving approval prior to work. Failure to obtain approval prior to work will result in an Incident of Non-Compliance being issued.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

Wait on cement (WOC) time prior to drilling out for a primary cement job will be a minimum 18 hours for a water basin, 24 hours in the potash area, or 500 pounds compressive strength, whichever is greater for all casing strings. DURING THIS WOC TIME, NO DRILL PIPE, ETC. SHALL BE RUN IN THE HOLE. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. See individual casing strings for details regarding lead cement slurry requirements.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

HIGH CAVE/KARST – CONTINGENCY CASING WILL BE REQUIRED IF LOST CIRCULATION OCCURS WHILE DRILLING THE SURFACE HOLE. THE SURFACE HOLE WILL HAVE TO BE REAMED AND A LARGER CASING INSTALLED.

Possible lost circulation in the San Andres formation.

1. The 9-5/8 inch surface casing shall be set at approximately 785 feet and cemented to the surface. **Additional cement may be needed.**
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.**
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

A CIT shall be performed on the production casing with either option.

A packer shall be set a minimum of 340' from the North line of Section 9 to prevent drainage of acreage to the north.

Production casing — Option 1 — use completion unit

2. **The BLM (575-361-2822) is to be notified immediately if pressure is detected on the 9-5/8" by 5-1/2" annulus during the time period while the rig is being moved and the well service unit is installed. Pressure relief valve to be set between 150 and 200 psi. Operator to notify BLM when drilling rig is removed and when well service unit is connected to the well. Completion rig to be moved on location within 3-5 days.**
3. **The minimum required fill of cement behind the 5-1/2 and 4-1/2 inch production casing is:**
 - ☒ **Cement to surface from FO cementer at KOP. If cement does not circulate, contact the appropriate BLM office. Additional cement may be needed as excess cement calculates to 11%. Due to high cave/karst – one inch operations will not be approved – cement to be in a solid sheath.**

Production casing — Option 2 — use drilling rig.

Operator will use drilling rig if hole conditions do not allow option one to be put in place. These conditions could include such items as lost circulation, pressure problems, etc. Casing will be cemented as shown in item 3 above.

4. **If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.**

C. PRESSURE CONTROL

1. **All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.**
2. **Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 2000 (2M) psi.**

3. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips or where the float does not hold, the minimum wait time before cut-off is eight hours after bumping the plug or when the cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. BOP/BOPE testing can begin after the above conditions are satisfied.
 - b. The tests shall be done by an independent service company utilizing a test plug **not a cup or J-packer**. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (18 hours) or potash (24 hours) prior to initiating the test.
 - c. The results of the test shall be reported to the appropriate BLM office.
 - d. All tests are required to be recorded on a calibrated test chart. **A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.**
 - e. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug.

D. DRILL STEM TEST

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

E. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

WWI 111310

VIII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Containment Structures

The containment structure shall be constructed to hold the capacity of the entire contents of the largest tank, plus 24 hour production, unless more stringent protective requirements are deemed necessary by the Authorized Officer.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color
Shale Green, Munsell Soil Color Chart # 5Y 4/2

B. PIPELINES –

STANDARD STIPULATIONS FOR SURFACE INSTALLED PIPELINES

A copy of the grant and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. The holder agrees to indemnify the United States against any liability arising from the

release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to activity of the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. The holder shall be liable for damage or injury to the United States to the extent provided by 43 CFR Sec. 2883.1-4. The holder shall be held to a standard of strict liability for damage or injury to the United States resulting from pipe rupture, fire, or spills caused or substantially aggravated by any of the following within the right-of-way or permit area:

- a. Activities of the holder including, but not limited to construction, operation, maintenance, and termination of the facility.
- b. Activities of other parties including, but not limited to:
 - (1) Land clearing.
 - (2) Earth-disturbing and earth-moving work.
 - (3) Blasting.
 - (4) Vandalism and sabotage.
- c. Acts of God.

The maximum limitation for such strict liability damages shall not exceed one million dollars (\$1,000,000) for any one event, and any liability in excess of such amount shall be determined by the ordinary rules of negligence of the jurisdiction in which the damage or injury occurred.

This section shall not impose strict liability for damage or injury resulting primarily from an act of war or from the negligent acts or omissions of the United States.

5. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil, salt water, or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil, salt water, or other pollutant, wherever found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any responsibility as provided herein.

6. All construction and maintenance activity will be confined to the authorized right-of-way width of 25 feet.
7. No blading or clearing of any vegetation will be allowed unless approved in writing by the Authorized Officer.
8. The holder shall install the pipeline on the surface in such a manner that will minimize suspension of the pipeline across low areas in the terrain. In hummocky or dune areas, the pipeline will be "snaked" around hummocks and dunes rather than suspended across these features.
9. The pipeline shall be buried with a minimum of 24 inches under all roads, "two-tracks," and trails. Burial of the pipe will continue for 20 feet on each side of each crossing. The condition of the road, upon completion of construction, shall be returned to at least its former state with no bumps or dips remaining in the road surface.
10. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.
11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.
12. Excluding the pipe, all above-ground structures not subject to safety requirement shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be a color which simulates "Standard Environmental Colors" – **Shale Green**, Munsell Soil Color No. 5Y 4/2; designated by the Rocky Mountain Five State Interagency Committee.
13. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. Signs will be maintained in a legible condition for the life of the pipeline.
14. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway.

15. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the authorized officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the authorized officer. An evaluation of the discovery will be made by the authorized officer to determine appropriate cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the authorized officer after consulting with the holder.

C. ELECTRIC LINES

IX. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

X. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory

revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Seed Mixture 1, for Loamy Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed will be either certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (small/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

<u>Species</u>	<u>lb/acre</u>
Plains lovegrass (<i>Eragrostis intermedia</i>)	0.5
Sand dropseed (<i>Sporobolus cryptandrus</i>)	1.0
Sideoats grama (<i>Bouteloua curtipendula</i>)	5.0

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed