

Submit 1 Copy To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
October 13, 2009

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

|   |
|---|
| WELL API NO.<br>30-015-38261  |
| 5. Indicate Type of Lease<br>STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No.<br>VB-0815   |
| 7. Lease Name or Unit Agreement Name<br>Trojans BQT State   |
| 8. Well Number<br>1H  |
| 9. OGRID Number<br>025575   |
| 10. Pool name or Wildcat<br>Rock Spur; Bone Spring  |

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
Yates Petroleum Corporation

3. Address of Operator  
105 South Fourth Street, Artesia, NM 88210

4. Well Location  
Unit Letter P : 660 feet from the South line and 330 feet from the East line  
Unit Letter M : 660 feet from the South line and 330 feet from the West line  
Section 36 Township 25S Range 28E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
2916'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐


OTHER: ☐

OTHER: Surface casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1/10/11 - Made 40'. Drilled to 63'. Set 40' of 20" conductor and cemented with 5 sx redi-mix to surface.

1/14/11 - TD 17-1/2" hole to 408' at 9:15 AM. Set 13-3/8" 48# J-55 8rd ST&C casing at 400'. Cemented with 180 sx Class "C" + 675#/sx D020 + 34#/sx D046 + 22#/sx D130 + 16878#/sx D903 + 338#/sx S001 (yld 1.97, wt 12.9). Tailed in with 200 sx Class "C" + 11kg D130 + 8460kg D903 (yld 1.33, wt 14.8). Circulated 57 sx to half round. WOC. Tested casing to 600 psi for 30 min. WOC 29 hrs 50 min. Reduced hole to 12-1/4" and resumed drilling.



Spud Date:

11/30/10

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE January 20, 2011

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: Donald Gray TITLE Field Supervisor DATE 1-26-11

Conditions of Approval (if any)