

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
June 19, 2008

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-38187
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name AID 24 STATE
8. Well Number #7
9. OGRID Number 255333
10. Pool name or Wildcat: Empire, Glorieta-Yeso (96210)

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

LIME ROCK RESOURCES A, L.P.

3. Address of Operator

c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

4. Well Location

Unit Letter M : 330 feet from the SOUTH line and 330 feet from the WEST line  
Section 24 Township 17-S Range 28-E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3679' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒

OTHER: Spud & Surface & Production Casings ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spud well on 12/20/10. Drilled 12-1/4" hole to 366'. Landed 8-5/8" 24# J-55 csg @ 350'. Cmted lead w/175 sx (236 cf) "C" cmt w/2% Cacl2, & 1/8#/sx p-e-flake. Tailed w/200 sx (264 cf) "C" cmt w/2% Cacl2. Circ 150 sx cmt to surface. On 12/21/10, PT 8-5/8" csg to 600 psi for 30 min - OK.

Drilled 7-7/8" hole to TD5280' on 1/9/11. Ran open hole logs. Landed 5-1/2" 17# J-55 csg @ 5269'. Cmted lead w/550 sx (1045 cf) 35/65 poz C cmt w/0.125#/sx p-e-flake, 3#/sx salt, 0.5% Halad-9, & 3#/sx gilsonite. Tailed w/650 sx (865 cf) "C" cmt w/0.125#/sx p-e-flake, 0.4% Lap-1, 0.5% CFR-3, & 1/4#/sx D-air. Circ 183 sx cmt to pit. Released drilling rig on 1/10/11. Plan to pressure test the 5-1/2" csg before completion operations.

Spud Date: 12/20/10

Drilling Rig Release Date: 1/10/11

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 1/21/11

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

For State Use Only

APPROVED BY: Donald Gray TITLE Field supervisor DATE 1-26-11

Conditions of Approval (if any):

