NIIOCD

Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an

	FORM APPROVED OMB NO. 1004-0135
	Expires: November 30, 2000
5.	Lease Serial No.

NMNM53218

abandoned we	6. If indian, Allouee or Tribe Name						
SUBMIT IN TRI	7. If Unit or CA/Agreement, Name and/or No.						
1. Type of Well Gas Well Oth	пет		- 4 2004		IYON 34 FEDERAL 8		
Name of Operator DEVON ENERGY PRODUCT	Contact: CANDA CONTACT: CANDA E-Mail: c	CE R. GRAHAMD.	ARTESI	9. API Well No. 30-015-32771-00)-X1		
3a. Address 20 NORTH BROADWAY SUI OKLAHOMA CITY, OK 7310	TE 1500 Ph: 40	ne No. (include area code) 05.552.4520 5.552.4621		10. Field and Pool, or Exploratory N INDIAN BASIN			
4. Location of Well (Footage, Sec., T				11. County or Parish, and State			
Sec 34 T21S R24E NENE 63	5FNL 680FEL			EDDY COUNTY,	NM		
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA							
TYPE OF SUBMISSION		ACTION					
☐ Notice of Intent	☑ Acidize □	Deepen	☐ Producti	on (Start/Resume)	■ Water Shut-Off		
	☐ Alter Casing ☐	Fracture Treat	□ Reclamation		☐ Well Integrity		
☑ Subsequent Report		New Construction	☐ Recomplete		☐ Other		
☐ Final Abandonment Notice		Plug and Abandon	g and Abandon				
13. Describe Proposed or Completed Ope	•	Plug Back	☐ Water Disposal				
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) THE BHL AFTER DRILLING HAS BEEN CALCULATED AT 776' FNL & 1749' FEL, NWNE SECTION 34-T21S-R24E, EDDY CNTY, NM. COMPLETION ACTIVITIES OCCURRED AS FOLLOWS. 6-22-2003 thru 7-3-2003 DRLD DV TOOLS AND CEMENT (PRESS TESTED AFTER EACH) TO FLOAT COLLAR. CIRC'D HOLE CLEAN. RAN SCRAPER TO PBTD 8398'. PICKLED 2 7/8" TUBING. TOH WITH TUBING. SCHLUMBERGER RAN CBL WHICH SHOWED TOC AT APPROX 920'. PERF'D WITH 2 SPF AS FOLLOWS: 7881-7885' WITH 10 HOLES, 7890-7894' WITH 10 HOLES, 7898-7908' WITH 22 HOLES, 7913-7926' WITH 28 HOLES, 7928-7932' WITH 10 HOLES, 7936-7940' WITH 10 HOLES, AND 7944-7954' WITH 22 HOLES; TOTAL 112 HOLES (0.41" EHD). SET RBP AT 8116', PACKER AT 7769'. PRESS TESTED LINES AND CASING. ACIDIZED PERFS 7881-7954' DOWN TUBING WITH 10,800 GALS 20% HCL + 105 BS AT AIR 20 WITH 2600 PSI;							
14. I hereby certify that the foregoing is true and correct. Electronic Submission #28375 verified by the BLM Well information System For DEVON ENERGY PRODUCTION CO L P, sent to the Carlsbad Committed to AFMSS for processing by ARMANDO LOPEZ on 03/01/2004 (04AL0141SE) Name (Printed/Typed) CANDACE R. GRAHAM Title OPERATIONS TECH II							
Timber 1 year) Of (10) (10)	I. OIGHIAM	TIME OF ETAK	TONG TEO				
Signature (Electronic S	submission)	Date 03/01/20	04				
	THIS SPACE FOR FED	ERAL OR STATE C	FFICE US	SE)			
Apptroved By ACCEPT	ED	ALEXIS C S Title PETROLEL	SWOBODA JM ENGINE	ER	Date 03/02/2004		
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to condu	itable title to those rights in the subject le						
Fitle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent s	U.S.C. Section 1212, make it a crime for a tatements or representations as to any materials.	my person knowingly and water within its jurisdiction.	villfully to ma	ke to any department or ag	ency of the United		

Additional data for EC transaction #28375 that would not fit on the form

32. Additional remarks, continued

ISIP 0 PSI. RAN BHP BOMBS WHICH SHOWED BHP OVER 1177 PSI. BLEW DOWN, FLUID HIT SURFACE, KILLED WELL, TOH. TOH WITH RBP AND PACKER.
RAN REDA PUMP ASSEMBLY (216 HP MOTORS, DN3000 PUMPS) AND 244 JTS 2 7/8" 6.5# L-80 TUBING; END OF TUBING AT 7940', BOTTOM OF MOTOR AT 8132'. BEGAN PUMP TESTING. WILL TEST FOR POTENTIAL WITH A LARGER PUMP AFTER RIG MOVES OFF THE RIGHTHAND CANYON "34" FEDERAL #6.
8-28-2003 RAN REDA GN5200 PUMPS AND ASSEMBLY; MOTOR SETTING DEPTH 8093'. ND BOP, NU WELLHEAD. RESUMED PUMP TESTING.