

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised June 10, 2003

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other	7. Lease Name or Unit Agreement Name Ruby Jo ATY
2. Name of Operator Yates Petroleum Corporation	8. Well Number 1
3. Address of Operator 105 S. 4 th Street, Artesia, NM 88210	9. OGRID Number 025575
4. Well Location Unit Letter <u>O</u> : <u>660</u> feet from the <u>South</u> line and <u>1980</u> feet from the <u>East</u> line Section <u>14</u> Township <u>8S</u> Range <u>26E</u> NMPM <u>Chaves</u> County	10. Pool name or Wildcat Foor Ranch Pre-Perm, North
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3388'GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Completion Operation ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/25/04 – TOC 3270'. Perforate Silurian 6134'-6158' (50), 6162'-6172' (22), 6176'-6184' (18), 6188'-6194' (14), 6199'-6204' (12), 6206'-6212' (14) for a total of 130 holes. Set 5-1/2" AS-1 packer with 2.25" on/off tool at 6066'.
2/27/04 – Acidize Silurian 6134'-6212' with 1000g 20% IC HCL acid.
3/2/04 – Re-acidize Silurian 6134'-6212' with 2500g 20% IC HCL acid with 100 ball sealers.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: Tina Huerta TITLE: Regulatory Compliance Supervisor DATE: February 24, 2004

Type or print name Tina Huerta E-mail address: tinah@ypcnm.com Telephone No. 505-748-1471
(This space for State use)

FOR RECORDS ONLY

MAR 11 2004

APPROVED BY _____ TITLE _____ DATE _____
Conditions of approval, if any: