

NEW MEXICO OIL CONSERVATION COMMISSION
 DRAWER DD
 ARTESIA, NEW MEXICO

Plugging
 FIELD REPORT FOR ~~CEMENTING~~ OF WELLS

Operator <i>Wagon T. Spencer</i>		Lease <i>Zimmerman</i>			Well # <i>2</i>	
Location of Well	Unit <i>F 5CRW</i>	Section <i>35</i>	Township <i>10^s</i>	Range <i>25^E</i>	County <i>Chaves</i>	
Plugging Contractor	<i>Cap Fulton</i>			Type of Equipment <i>pulling unit</i>		
APPROVED CASING PROGRAM <i>in hole</i>						
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement	
<i>7 7/8</i>	<i>5 1/2</i>	<i>14[#]</i>	<i>new</i>	<i>1293</i>	<i>500 sks.</i>	
					<i>para. 1197-1205</i>	
					<i>1228-1231</i>	
Casing Data:						
Surface _____ joints of _____ inch _____ # Grade _____						
(Approved) (Rejected)						
Inspected by _____ date _____						
Cementing Program						
Size of hole _____ Size of Casing _____ Sacks cement required _____						
Type of Shoe used _____ Float collar used _____ Btm 3 jts welded _____						
TD of hole <i>1293</i> Set _____ Feet of _____ Inch _____ # Grade _____						
New-used csg. @ _____ with _____ sacks neat cement around shoe						
+ _____ sax _____ additives _____						
Plug down @ _____ (AM) (PM) Date _____						
Cement circulated _____ No. of Sacks _____						
Cemented by _____ Witnessed by _____						
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____						
Casing test @ _____ (AM) (PM) Date _____						
Method Used _____ Witnessed by _____						
Checked for shut off @ _____ (AM) (PM) Date _____						
Method used _____ Witnessed by _____						
Remarks: _____						

well was plugged as follows.

Hole loaded with mud between plugs. 3-23-63 H.L.

- 1. 21 sks. at T.O. 3-27-63 H.L.*
- 2. 10 sks. @ 400' 3-27-63 H.L.*
- 3. 5 sks in surface*

