

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

C O R R E C T E D
RECEIVED

5a. Indicate Type of Lease
State Fee
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS **JUL 9 1979**
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DEEPER WELL. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER- **O. C. C.**
ARTESIA, OFFICE
2. Name of Operator **STEVENS OIL COMPANY**
3. Address of Operator **P. O. Box 2203 - Roswell, New Mexico 88201**
4. Location of Well
UNIT LETTER **D**, **990** FEET FROM THE **North** LINE AND **330** FEET FROM
THE **West** LINE, SECTION **31** TOWNSHIP **8-S** RANGE **19-E** NMPM.

7. Unit Agreement Name
8. Farm or Lease Name **O'Brien "I"**
9. Well No. **1**
10. Field and Pool, or Wildcat Assoc. **Twin Lakes-San Andres**
12. County **Chaves**

15. Elevation (Show whether DF, RT, GR, etc.)
3965.3 Gr., 3971.3 K.B.

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work) SEE RULE 1103.

6-18-79 Spud 4:00 p.m., drilled 117' and ran 117 8-5/8" surface casing; circulated cement w/75 sacks, Class C with 2% calcium chloride. WOC/48 hrs., then tested to 1000# for 30 minutes logging no pressure decline. Drilled out and drilled ahead.

6-25-79 Ran 2770' 4-1/2" 9.5# casing & cemented with 225 sacks, 150 sacks Class C with 2% calcium chloride and 75 sacks self-stress w/3% calcium chloride.

6-29-79 Perf. 2645.5, 46, 46.5, 49.5, 50, 50.5, 57.5, 58, 58.5, 59, 65, 65.5, 66, 66.5, 67, 71, 71.5, 74.5, 75, 75.5, 78.5, 79, 79.5, 82.5, 83, 83.5

7-01-79 Acidized perfs. w/7000 gals. 28%, swbg.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Regina S Taylor TITLE Agent DATE 7-6-79

APPROVED BY W. C. Williams TITLE OIL AND GAS INSPECTOR DATE JUL 10 1979

CONDITIONS OF APPROVAL, IF ANY: