

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
LG-0336

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

OIL WELL GAS WELL OTHER

6. Name of Operator
Yates Petroleum Corporation/

7. Address of Operator
207 South 4th St., Artesia, NM 88210

8. Location of well
UNIT LETTER P 660 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 35 TOWNSHIP 4S RANGE 24E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name
Redman "OY" State

9. Well No.
1

10. Field and Pool, or WHdcat
Undes. Abo

12. County
Chaves

15. Elevation (Show whether DF, RT, GR, etc.)
3964.3' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17-1/2" hole at 10:00 AM 5-1-81. TD 423' - Ran 10 joints of 13-3/8" 54.50# K-55 ST&C casing set at 423'. 1-notched guide shoe at 423'. Flapper insert float at 377'. Cemented w/400 sacks Class "C" 4% CaCl. Slurry weight 14.8, 1.32 cu ft/sack. Compressive strength of cement - 1180 psi in 12 hours. PD 9:00 PM 5-1-81. Bumped plug to 500 psi, released pressure & float held okay.* WOC 20 hours & 45 minutes. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Core #1 - 60' - 835-895'; Core #2 - 22' - 895-917'; Core #3 - 38' - 917-955'; Core #4 - 12' - 995-1017'; Core #5 - 7' - 1017-1023'; Core #6 - 4' - 1023-1029'; Core #7 - 4' - 1029-1033'. Resumed drilling @1033'. Deviation @1210' 3/4 degree. Lost circulation at 1318'. Twisted off drill pipe at 426'. Fish consists of 20 - 6 1/2" drill collars & 6 joints of 4 1/2" drill pipe from 426' to 1318'. Attempted to catch fish for several days. Abandoned fishing operations & attempted to drill down beside fish & set casing. Drilled to 725' & lost circulation. Pulled up into surface casing & mixed lost circulation pill. Attempted to go back to 725' to spot lost circulation pill & found hole filled up to surface casing at 423'. Drilled 60' below surface casing to check for bridge. Hole filled in. Plan to plug and abandon & skid rig 100' to West.

* Circulated 45 5x

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Engineering Secretary DATE 5/14/81

APPROVED BY [Signature] TITLE SUPERVISOR, DISTRICT III DATE MAY 18 1981

CONDITIONS OF APPROVAL, IF ANY: