

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPL  
(Other instructions  
verse side)

FE  
re

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 29610

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME RECEIVED

8. FARM OR LEASE NAME

Huggins Draw

9. WELL NO.

#2

10. FIELD AND POOL, AND FIELD OFFICE

Undesignated Abo

11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA

Sec. 31, T5S, R24E

12. COUNTY OR PARISH 13. STATE

Chaves

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL  GAS WELL  OTHER

2. NAME OF OPERATOR  
Sanders Petroleum Corporation

3. ADDRESS OF OPERATOR  
11000-D Spain Road NE, Albuquerque, NM 87111

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

990' FNL & 660' FEL, Sec. 31, T5S, R24E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4170 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing and cement

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Ran 21 jts. 10-3/4" 40.5# J55 API casing, set at 853'. Cemented with 400 sx. Pacesetter "C" 2% CaCl, plus 300 sx. "C" 2% CaCl. Circulated cement, circulated out 100 sx. Plug down 2:18 p.m. 1-8-82. Pressure tested casing and BOP to 1500 psi before drilling out.

RECEIVED  
JAN 14 1982  
OIL & GAS  
U.S. GEOLOGICAL SURVEY  
LOSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Helen A. Chapman

TITLE Office Manager

DATE 1-11-82

(This space for Federal or State office use)

APPROVED BY JAN 20 1982  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side