

RECEIVED

197

Form 9-331  
Dec. 1973

OCT 12 1982

NM OIL CONS. COMMISSION

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
ARTESIA, OFFICE  
GEOLOGICAL SURVEY

Drawer DD  
Artesia, NM

5. LEASE  
NM-14294

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
PZ Federal

9. WELL NO.  
2

10. FIELD OR WILDCAT NAME  
Undesignated *abc*

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 7-T9S-R25E

12. COUNTY OR PARISH  
Chaves

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3724' G.L.

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well  gas well  other

2. NAME OF OPERATOR  
McClellan Oil Corporation ✓

3. ADDRESS OF OPERATOR  
P.O. Drawer 730, Roswell, New Mexico, 88202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: <sup>660 N 1980 C</sup> 1980' FFL & 660' FML  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: *413*

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Cement & Casing	

(NOTE: Report results of multiple completion or change on Form 9-330)

RECEIVED  
SEP 29 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9-24-82: Move in Tex-Mex Rig #3. Spud with 12-1/4" bit.

9-26-82: Drilled to 925'. Ran 915' of 8-5/8", 24 lb/ft, J-55, new casing. Cemented with 300 sx Halliburton Light cement with 2% CaCl<sub>2</sub>, and 250 sx Class "C" with 2% CaCl<sub>2</sub>. Circulated 40 sx. WOC - 18 hrs. Nipple up B.O.P. Tested to 500 psi for 30 min. Resume drilling.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *David R. Glass* TITLE Operations Manager DATE September 28, 1982

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL OCT 8 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side