

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Alameda, NM 88210

Budget Bureau No. 10044
Expires August 31, 1985
LEASE DESIGNATION AND SERIAL

NM-19829

6 IF INDIAN, ALLOTTEE OR TRIBE

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

McKay Oil Corporation

JAN 23 '91

3. ADDRESS OF OPERATOR

Post Office Box 2014, Roswell, NM 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirement.
See also space 17 below.)
At surface

660' FSL & 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3574' GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

McKay Harvey Fed.

9. WELL NO.

#X /

10. FIELD AND POOL OR WILDCAT

Wildcat

11. SEC., T., S., M., OR BLM. AND SURVEY OR AREA

Sec. 17-9S-25E

12. COUNTY OR PARISH 13. STATE

Chaves

NM

16

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

Horizontal Drilling

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Set CIBP's @ 3850' and 3745.5'.

2. Cut window in 4½" casing from 3720' - 3738', 18'.

3. Spot cement plug from 3745' to 3671'. WOC 48 hrs.

4. Drill cement plug to 3725'.

5. Horizontally drill approximately 300' from existing well bore @ 3754' to the North. Estimated location of the bottom of the hole will be 960' FSL & 660' FEL, Sec. 17-9S-25E.

6. Drill cement plug to 3732'. Horizontally drill approximately 300' from existing well bore @ 3754' to the West. Estimated location of the bottom of the hole will be 660' FSL & 960' FEL, Sec. 17-9S-25E.

7. Run directional surveys to determine location of bottom of holes.

8. Run tubing and production test.

9. Build 40' long x 10' wide x 5' deep workover pit in same location as old reserve pit.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Operations Manager

DATE 12-11-89

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

SUBJECT TO LIKE
APPROVAL BY STATE

*See Instructions on Reverse Side

APPROVED
PETER W. CHESTER

DEC 14 1989

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA