

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

RECEIVED
NOV 26 1986
O. C. D.
ARTESIA OFFICE

P. O. BOX 2088

RED BLUFF STATE, NEW MEXICO 87501

5a. Indicate Type of Lease
State Fee
5. State Oil & Gas Lease No.
LG 4336

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR TO GO BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Location of Well
UNIT LETTER P 660 FEET FROM THE South LINE AND 660 FEET FROM
THE East LINE, SECTION 11 TOWNSHIP 7S RANGE 24E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name
Red Bluff State Unit

9. Well No.
1

10. Field and Pool, or Wildcat
Pecos Slope Abo

15. Elevation (Show whether DF, RT, GR, etc.)
3970.4' GR

12. County
Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
OTHER <input type="checkbox"/>		OTHER <u>Production Casing, Perforate, Treat</u> <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

TD 4000'. Ran 94 joints 4-1/2" 9.5# J-55 casing, set 4000'. 1-Regular guide shoe set 4000'. Float collar set 3941'. Cemented w/225 sx 65/35 Class C Poz with 5# salt, .7% CF-1, 1/4# celloseal and 5#/sack Hi-seal (Yield 1.39- weight 14.2). PD 2:00 AM 11-14-86. Bumped plug to 1500 psi, released pressure, float and casing held okay. WOC 18 hrs. Perforated 3561-3564' w/12 .41" holes (4 SPF). Acidized perfs 3561-64' w/750 gals 7-1/2% NEFE acid. Frac'd perfs 3561-64' w/20000 gals Mini-Max III-30 and 32000# 20/40 sand. Recovering load and swabbing.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Les A. Clements TITLE Production Supervisor DATE 11-24-86

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: Supervisor District II NOV 26 1986

