

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

RECEIVED BY  
APR -2 1987  
O. C. D.  
ARTESIA, OFFICE

SANTA FE, NEW MEXICO 87501

5a. Indicate Type of Lease  
State  Free   
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator McKay Oil Corporation	8. Farm or Lease Name S. Four Mile Draw St.
3. Address of Operator Post Office Box 2014, Roswell, New Mexico 88201	9. Well No. Comm. #11
4. Location of Well UNIT LETTER M 990 FEET FROM THE West LINE AND 660 FEET FROM THE South LINE, SECTION 22 TOWNSHIP 6S RANGE 22E NMPM.	10. Field and Pool, or Wildcat W. Pecos Slope Abo
15. Elevation (Show whether DF, FT, GR, etc.) 4223' GL	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	Spud, surface & Production csg. <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 3-17-87 Spudded 12 1/4" hole @ 4:30 a.m.
- 3-19-87 Ran in hole w/19 jts. 8 5/8" casing, 23#, set @ 855', cemented w/50 sxs. Premium Plus w/4% CaCl, 150 sxs. Halliburton Lite, w/4% CaCl, 100 sxs. Premium Plus. Plug #1 set @ 240', cemented w/35 sxs. Premium Plus w/4% CaCl, tagged @ 255'; Plug #2 set @ 180', cemented w/35 sxs. Premium Plus w/4% CaCl, tagged @ 92'; Plug #3 set @ 30' cemented w/35 sxs. Premium Plus w/4% CaCl + 50 gals. flocheck. Plug dn. @ 4:30 p.m.
- 3-23-87 Ran in hole w/79 jts. 4 1/2", used, 11.5# casing, set @ 3280'. Cemented w/325 sxs. Premium Plus w/2% ge, 4/10th of 1% Halad 4, 3/10th of 1% CFR3, 5# salt, 1/4" floseal, 5# gilsonite. Plug dn. @ 11 p.m.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Theresa Rodriguez TITLE Production Analyst DATE 4-1-87

Original Signed by  
Les A. Clements

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE **APR 15 1987**

CONDITIONS OF APPROVAL, IF ANY: Supervisor District II