

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER		5a. Indicate Type of Lease State ☐ Fee ☒	
2. Name of Operator Horizon Oil & Gas Co. ✓		3. State Oil & Gas Lease No.	
3. Address of Operator P.O. Box 7 Spearman, Texas 79081		7. Unit Agreement Name	
4. Location of Well UNIT LETTER I 1650 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 23 TOWNSHIP 5S RANGE 27E		8. Farm or Lease Name Denton	
15. Elevation (Show whether DF, RT, CR, etc.) 4079 GR		9. Well No. #1	
16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐ SUBSEQUENT REPORT OF: REMEDIAL WORK ☐ COMMENCE DRILLING OPER. ☐ CASING TEST AND CEMENT JOB ☒ OTHER ☐ PLUG AND ABANDON ☐ CHANGE PLANS ☐ ALTERING CASING ☐ PLUG AND ABANDONMENT ☐		10. Field and Pool, or Wildcat Wildcat	
12. County Chaves			

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Drilled well to T.D. of 7528'.
2. Set 6 30 sx. class "H" cement plugs at following depths:
7200' - 6625' - 5725' - 5025' - 4285' - 3100'
3. Ran 5 1/2" 15.5# Casing to 2980'. Cemented with 575 sx. class "C" containing 5#/sack salt + 5/10 of 1% Halad 4 + 4/10 of 1% CFR-3 + 1/4#/sack Flocele.
4. Ran Bond Log - Top of cement at 1906'.
5. Pressure tested Casing and Blow Out Preventor to 1500# for 30 minutes. Held OK.
6. Perforated 2408-2486 OA w/70 Holes using 4" Casing gun. Acidized w/4000 gallons 15% NEFE acid. Swabbed load back. Did not get any shows of oil or gas.
7. Set CIBP @ 2395'.
8. Perforated 2314 - 2326' with 25 Holes using 4" Casing gun. Acidized with 2500 gallons 15% NEFE acid. Swabbed load back. Did not get any shows of oil or gas.
9. Preparing to plug.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mike Williams TITLE Engineer DATE 12-13-89
ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II
APPROVED BY Mike Williams TITLE Engineer DATE DEC 26 1989
CONDITIONS OF APPROVAL, IF ANY: