

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-63071	
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-3329	
7. Lease Name or Unit Agreement Name Ponderosa State	
8. Well No. 2	
9. Pool name or Wildcat Chaves Unders Grp 1 66001	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3933 GR	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
Hanson Operating Company, Inc.

3. Address of Operator
P.O. Box 1515, Roswell, New Mexico 88202-1515

4. Well Location
Unit Letter G : 1650 Feet From The North Line and 1650 Feet From The East Line
Section 23 Township 8 S Range 27E NMPM Chaves County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <u>Perforating & Acidizing</u> <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 7-6-95 a well service unit was rigged up and the float collar and cement was drilled to a PBTD of 2174'. The casing was treated to 750 psi.

On 7-7-95 the San Andres was perforated with 4" bullet casing guns in the following: (2120, 25, 26, 27, 28, 34, 37, 38, 43, 49, 50, 52, 53, 54, 55 & 56) 16 holes. These perforations were acidized with 5000 gal of 20% acid with additives. The swabbing operations were started.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Betsy Speer TITLE Production Analyst DATE 7-11-95
TYPE OR PRINT NAME Betsy Speer TELEPHONE NO. 505-622-7330

(This space for State Use)

APPROVED BY ORIGINAL SIGNED BY TIM W GULI TITLE DISTRICT II SUPERVISOR DATE JUL 14 1995
CONDITIONS OF APPROVAL, IF ANY: