

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-005-63082

Operator <u>McKay Oil Corp</u>		Lease <u>Samedan 16-B St.</u>		Well # <u>3</u>	
Location of Well	Unit <u>C</u>	Section <u>16</u>	Township <u>7</u>	Range <u>26</u>	County <u>Chaves</u>
Drilling Contractor <u>United Drilling</u>	Type of Equipment <u>R</u>				

APPROVED CASING PROGRAM

* Witness 8 5/8

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>12 1/4</u>	* <u>8 5/8</u>	<u>24 J-55</u>		<u>900+</u>	<u>850+ Surf</u>
<u>7 7/8</u>	<u>4 1/2</u>	<u>10.5 J-55</u>		<u>TD</u>	<u>470 +</u>
				<u>4400'</u>	<u>2500'</u>

Casing Data:

Surface 25 joints of 8 5/8 inch 24 # Grade J-55

(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 470 sxsType of Shoe used Guide Float collar used TEXAS Btm 3 jts welded YesTD of hole 943 Set 930 Feet of 8 5/8 Inch 24 # Grade J-55New-used csg. @ _____ with 500 sxs sacks neat cement around shoe+ _____ sax _____ additives 22 cc 25% 024Plug down @ 4:30 (AM) (PM) Date 2/12/96Cement circulated 445 No. of Sacks 8 1/2 sxs to pitCemented by Dowell Witnessed by Gary Williams

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: S-cont.