



LOCATE WELL CORRECTLY

RECEIVED  
SEP 21 1960  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
LAND OFFICE  
SERIAL NUMBER LC-063623-2  
LEASE OR PERMIT TO PROSPECT  
D. E. PRICE  
30-015-00567

# LOG OF OIL OR GAS WELL

Company Wayne J. Spears Address 291 Three Cross, Roswell, New Mexico  
Lessor or Tract Hanson A Field Undesignated State New Mexico  
Well No. 10 Sec. 27 T. 16S R. 27E Meridian N7PM County Eddy  
Location 1800 ft. {N.} of S Line and 1900 ft. {E.} of E Line of Sec. 27 Elevation \_\_\_\_\_  
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.  
Signed \_\_\_\_\_ Title Operator

Date September 14, 1960  
The summary on this page is for the condition of the well at above date.

Commenced drilling \_\_\_\_\_, 19\_\_\_\_ Finished drilling PLUGGED & ABANDONED September 14, 1960

## OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ No. 6, from \_\_\_\_\_ to \_\_\_\_\_

## IMPORTANT WATER SANDS

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ No. 3, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 4, from \_\_\_\_\_ to \_\_\_\_\_

## CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
7"	177			150					

## MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
7"	150	50	pump & plug		

## PLUGS AND ADAPTERS

Heaving plug—Material \_\_\_\_\_ Length \_\_\_\_\_ Depth set \_\_\_\_\_  
Adapters—Material \_\_\_\_\_ Size \_\_\_\_\_

## SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

## TOOLS USED

Rotary tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet  
Cable tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

## DATES

Put to producing \_\_\_\_\_, 19\_\_\_\_  
The production for the first 24 hours was \_\_\_\_\_ barrels of fluid of which \_\_\_\_\_% was oil; \_\_\_\_\_% emulsion; \_\_\_\_\_% water; and \_\_\_\_\_% sediment. Gravity, °Bé. \_\_\_\_\_  
If gas well, cu. ft. per 24 hours \_\_\_\_\_ Gallons gasoline per 1,000 cu. ft. of gas \_\_\_\_\_  
Rock pressure, lbs. per sq. in. \_\_\_\_\_

## EMPLOYEES

\_\_\_\_\_, Driller  
\_\_\_\_\_, Driller  
**Walker Drilling Company**, Driller  
**Pecos, Texas**, Driller

## FORMATION RECORD

DEPTH	FORMATION	TOTAL FEET
1000		
1020		
1040		
1060		
1080		
1100		
1120		
1140		
1160		
1180		
1200		
1220		
1240		
1260		
1280		
1300		
1320		
1340		
1360		
1380		
1400		
1420		
1440		
1460		
1480		
1500		

