



County Eddy Depth 2000' Pool Red Lake*

11

SCOUT REPORT
NEW MEXICO OIL CONSERVATION COMMISSION

Company Red Lake Oil Company Well No. 19 Lease State ~~1111~~
~~990'~~ Feet from S Line 1650' Feet from W Line 21' Sec. 28 Twp. 17S Rge 28E

Land State Contractor Co. Rig

T. A 300
 T. X
 B. X
 T. Del. Li.
 T. Del. Sd.
 T. Y
 T. SR
 T. Q
 T. GB 1910
 T. SA
 T. Glo.
 T. Blby
 T. CF

Elevation 3600 Spudded 6-21-54 Completed 7-10-54
 T. Tu. Total Depth 2006 P. B. 1933
 T. Full Top Pay 1910 District 7
 T. DR I. P. P 15 BOPD
 T. Wich. Alb. Base BO 24 Hrs.
 T. Abo Choke: Open Inch
 T. WC Tubing 2 @ 1925 Ft.
 T. Hu. Pressures: Tubing Casing
 T. Per-Pe GOR Gravity 35
 T. Penn Effective Perforations
 T. Strawn 30h 1910-1920
 T. Miss.
 T. WF

CSG. & CEMENTING REC'D

Size	Feet	Sax Cement
<u>2 7/8</u>	<u>454</u>	<u>200 + PV</u>
<u>1</u>	<u>765</u>	<u>44</u> ✓
<u>5 1/2</u>	<u>1972</u>	<u>50'</u>

T. Dev. Acid & Shooting Record:
 T. Fuss. Sandfrac From To
 T. Sil. 10,000 g From all perfor. To
 T. Mon. From To
 T. Simp. From To
 T. McK
 T. Ell.
 T. G.W.
 T. Gr. SHOWS
 T. S/W @ 325
 T. S/W @ 415
 T. S/
 T. S/W @ 688-690
 T. S/
 T. S/

June 14, 1954	Loc	
	<u>Change location</u>	<u>1725 li</u>
	<u>-prep. spud.</u>	<u>4 @ 1900 li</u>
<u>30</u>	<u>+ D 765 tubing</u>	<u>1994-1900</u> <u>1900' li</u>
	<u>WOC on 7" seg.</u>	<u>1972 li</u>
	<u>d 760 tubing</u>	<u>TD 2006' li</u>
	<u>d 1290</u> ✓	<u>1933' sand frac</u> <u>cut 1910-20 w/30h.</u> <u>sandfrac 10000 gal</u> <u>+ 15000 # sd 1910-</u> <u>20</u>

7A 2006' li, SR 1933

—

TL 5 — 1723 *fitting pump*

1580 24'