

Form 9-331a
(Feb. 1951)

(SUBMIT IN TRIPLICATE)

Land Office _____

Lease No. **NM 041284**

Unit _____

RECEIVED
APR 22 1977
O. C. C.
ARTESIA, OFFICE

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

McGrady **4-1**, 19**60**

Well No. 1 is located 1980 ft. from S line and 660 ft. from E line of sec. 3

C NE SE Sec. 3 16 S 29 E N.M.P.M.

(¼ Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Wildcat Eddy New Mexico

(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3745 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

T. D. 2642. Pulled and recovered 1776' 7" intermediate casing. Plugged back from T. D. with mud to top of Premier Sand at 2170' and set 50' cement plug. Plugged back with mud from this interval to 1760', and there set 75' cement plug across water interval encountered in red sand, namely 1730' to 1750'. From 1685' plugged back to the base of salt at 900' with mud and set 50' cement plug. Recovered 245' of the 445' of 8-5/8" surface pipe which was cemented. Plugged back with mud to top of salt and base of surface pipe and set 50' cement plug from shoe of surface pipe. Plugged back with mud from this cement plug to surface, and set 6' foot marker with 15 sacks cement. Marker cemented in firmly.

APR 21 1977
[Signature]
ACTING DISTRICT ENGINEER

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Len Mayer

Address P. O. Box 5613

Roswell, N.M.

By *[Signature]*
Title Owner

03V1303R

PP: 11. 11. 11

11. 11. 11
2011. 11. 11