

(SUBMIT IN TRIPLICATE)


Land Office ROSWELL, N.M.

Lease No. 100-028477

Unit _____

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

30-815-02733



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 4, 1956

Well No. G Davis is located 600 ft. from {N} line and 1900 ft. from {E} line of sec. 15

c-15/4-15/4 Sec 15 (1/4 Sec. and Sec. No.) 100 (Twp.) 29E (Range) _____ (Meridian)

High Lonesome (Field) Eddy (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 3701 ft. G.L.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drill with rotary tools a 12 1/4" hole to top of salt at approx. 425'. Set 8 5/8" H-40 cals. csg. to 420' and cement to surface. Drill a 1 1/4" hole to top of pay at approx. 1900'. Core pay zone and run 4 1/2" P-25 butt weld csg. to 1.0. Cement to surface. Perforate and treat well.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Rob Drilling Company

Address Box 1268

Artesia, New Mexico

By A. M. Spier

Title Production Engineer