

W. W. D. C. C.
BUREAU'S COPY

APPROVED
JUL 12 1962
RONNIE E. SHOOK
ACTING DISTRICT ENGINEER

copy to SF.
(SUBMIT IN TRIPLICATE)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office New Mexico
Lease No. 026418
Unit L

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	X
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	X
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 21, 1961

Federal 15-10
Well No. 7 is located 2310 ft. from N line and 650 ft. from W line of sec. 10
NW 1/4 Sec. 10 16S 31E NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
North Square Lake (Grayburg) Ady New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the ~~depth~~ ^{ground} above sea level is 4178 ft.

RECEIVED
JUL 13 1962
D. C. C.
METESIA OFFICE

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding logs, cementing points, and all other important proposed work)

Drilled 6-3/4" hole to 3624'. Cut 6-3/4" core from 3624' to total depth 3719' (Premier 5d). Pulled core 1 bl. and recovered 76' core with no shows. Ran Gamma Ray-sonic and Induction - Laterolog.

John H. Trigg resumed operations for attempted completion in Queen section 6:15 PM 6-16-61. Spotted 25 ex. cut from total depth to 3637'. Ran and landed 4-1/2", 11.6 w/ft. J-55, 272, new casing at 2993. Cemented 4-1/2" oil string with 100 exs req. at cement. Perforated Queen section 2948-60. Swb tested perf recovering 100% salt water. Pulled 2100' of 4-1/2" casing. Spotted cement plugs 2979-2829', (12 ex.), 940-1050' (25 ex) and 10 ex. in top of 2-5/8" surface casing. Well location properly marked with 4" pipe. Officially plugged and abandoned 6-21-61.

RECEIVED
JUL 26 1961

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Standard Oil Company of Texas, a Division of California Oil Co.

Address Drawer #3
Monahans, Texas

By J. L. Rowland
Title District Engineer