

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Amaco Prod. Co.</i>		Lease <i>State CD Gas Com</i>			Well # <i>1</i>
Location of Well	Unit <i>G</i>	Section <i>11</i>	Township <i>17</i>	Range <i>27</i>	County <i>Eddy</i>
Drilling Contractor	<i>1880/N 1980/E Sharp Drilling Co.</i>		Type of Equipment <i>Rotary</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2"</i>	<i>13 3/8"</i>	<i>48 #</i>		<i>400'</i>	<i>Cin to Surface</i>
<i>* 12 1/4"</i>	<i>9 5/8"</i>	<i>36 #</i>		<i>2000'</i>	<i>Cin to Surface</i>
<i>8 3/4"</i>	<i>5 1/2"</i>	<i>17 #</i>		<i>9700'</i>	<i>Cont to 500' above abo</i>

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole *12 1/4* Size of Casing *9 5/8* Sacks cement required *1700 Sks*

Type of Shoe used \_\_\_\_\_ Float collar used \_\_\_\_\_ Btm 3 jts welded *yes*

TD of hole *2000* Set \_\_\_\_\_ Feet of *9 1/2* Inch *36* # Grade \_\_\_\_\_

New-used csg. @ \_\_\_\_\_ with \_\_\_\_\_ sacks neat cement around shoe

+ *5* sax \_\_\_\_\_ additives \_\_\_\_\_

Plug down @ *11:30* (AM) (PM) Date *8/9/81*

Cement circulated \_\_\_\_\_ No. of Sacks *1200*

Cemented by *P. ...* Witnessed by *...*

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_