

SANTA FE  
ARTESIA  
HOLDS  
OPENED

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<b>X</b>		

Artesia, New Mexico

Place

August 14, 1951

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Allen &amp; Fair Operating, Inc.

State A

Well No. 2

in the \_\_\_\_\_

Company or Operator

Lease

SW-SW

of Sec. 36

T. 17 S

R. 29 E

N. M. P. M.,

Leco Hills

Field,

Eddy

County.

The dates of this work were as follows: July 18, to August 5, 1951

Notice of intention to do the work was (~~XXXX~~) submitted on Form C-102 on July 16 1951and approval of the proposed plan was (~~XXXX~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Hole was filled with mud and a 10 sack cement plug was dumped on bridge set in open hole at 2580', this plug extending up into the 7" casing. The 7" casing was knocked off and pulled at 729'. A 10 sack cement plug was placed at base of salt at 990' and a 5 sack cement plug was placed in the top of 8" at 729'. The 8" casing was knocked off and pulled at 168' and a 10 sack cement plug dumped on bridge at 510' just below 8" casing shoe. Hole was filled with mud between plugs. Cement plug and pipe marker was run at base of 5' collar and collar filled to surface.

Witnessed by E. D. Ackerman Ackerman Well Service Owner

Name

Company

Title

Subscribed and sworn before me this 14th

I hereby swear or affirm that the information given above is true and correct.

day of Aug

1951

Name Gus W. Arnold

Position Supr.

Representing Allen &amp; Fair Operating, Inc.

Company or Operator

My commission expires 6/26/55

Address 711 Dallas St. Artesia, N. M.

Remarks:

APPROVED

OIL CONSERVATION COMMISSION

APR 22 1952

Name

Title

